

CONTACT INFORMATION

Mining Records Curator Arizona Geological Survey 1520 West Adams St. Phoenix, AZ 85007 602-771-1601 http://www.azgs.az.gov inquiries@azgs.az.gov

The following file is part of the

Arizona Department of Mines and Mineral Resources Mining Collection

ACCESS STATEMENT

These digitized collections are accessible for purposes of education and research. We have indicated what we know about copyright and rights of privacy, publicity, or trademark. Due to the nature of archival collections, we are not always able to identify this information. We are eager to hear from any rights owners, so that we may obtain accurate information. Upon request, we will remove material from public view while we address a rights issue.

CONSTRAINTS STATEMENT

The Arizona Geological Survey does not claim to control all rights for all materials in its collection. These rights include, but are not limited to: copyright, privacy rights, and cultural protection rights. The User hereby assumes all responsibility for obtaining any rights to use the material in excess of "fair use."

The Survey makes no intellectual property claims to the products created by individual authors in the manuscript collections, except when the author deeded those rights to the Survey or when those authors were employed by the State of Arizona and created intellectual products as a function of their official duties. The Survey does maintain property rights to the physical and digital representations of the works.

QUALITY STATEMENT

The Arizona Geological Survey is not responsible for the accuracy of the records, information, or opinions that may be contained in the files. The Survey collects, catalogs, and archives data on mineral properties regardless of its views of the veracity or accuracy of those data.

ARIZONA DEPARTMENT OF MINES AND MINERAL RESOURCES FILE DATA

-t.c.s

PRIMARY NAME: BLACK DIAMOND

ALTERNATE NAMES:

MOHAVE COUNTY MILS NUMBER: 359A

LOCATION: TOWNSHIP 11 N RANGE 12 W SECTION 6 QUARTER NE LATITUDE: N 34DEG 19MIN 39SEC LONGITUDE: W 113DEG 32MIN 24SEC TOPO MAP NAME: ARTILLERY PEAK - 15 MIN

CURRENT STATUS: PAST PRODUCER

COMMODITY:

MANGANESE NODULES CALCIUM CALCITE

BIBLIOGRAPHY:

ADMMR BLACK DIAMOND-AMERICAN MINE FILE ADMMR MOHAVE CUSTOM MILL PROJECT ADMMR MOHAVE FILES FARNHAM, L.L. "MANGANESE DPSTS OF W AZ" USBM IC 7843, P. 38-40, 1958 "MIN. & WTR. RES. OF AZ" AZBM BULL 180 P 217 MALACH, R. "MOHAVE CTY MINES" P 33, 1977 AZ. BLM AMC FILE #49658

BLACK DIAMOND GROUP

REFERENCES

MOHAVE COUNTY ARTILLERY MTS. DIST. T11N R12W Sec. 6

Mohave County MILS Index #359A

USGS Prescott Map

USGS Artillery Peak, AZ 15' Topo (included in file)

IC 7843, p. 38-40

ABM Bull. 180, p. 217

Malach, Mohave Co. Mines, 1977, p. 33

Mohave Custom Mill Proj Card File

BLM AMC File (#49658)



Name of Mine or Prospec	Township Rar	Section Priority		
Black Diamond	11N 12W	6acc C		
rincipal Minerals:	1:250,000 Quad 7	.5' - <u>15'</u> Quad		
Psilomelane. Manganite	Prescott Artillery Peak			
ssociated Minerals:	District P	Principal Product		
	Artillery Mtn.	Manganese		
Type of Operation:	County State T	ype of Deposit		
Surface: Underground	Mohave AZ	Sedimentary host		
Dwnership or Controlling Interest: Consul- Lewis Peterson, Kingman, AZ, Floyd Brown an	t current USBLM mining cl d J. Robinette, Wenden, A th on Alamo Road for .5 m	aim records; AZ (1958) ⁴ miles, turn		
right on unimproved road for 1.5 miles, tur is located on topographic quadrangle.	n left on jeep trail for	l mile. Mine		
Structural Control or Geological Association:				
"Brecciated closely spaced fissures and sha with manganese oxides which form 1.5 to 10% grades into a typical vein type deposit."1	ttered wall rocks. The solution of the total rock mass.	voids are filled The deposit		
"The manganese minerals consisted entirely manganite, occurring as nodules, fissure fi fragments, associated mainly with calcite."	of hard oxides, psilomei 11ings, and rims around 4	the breccia		
Age of Mineralization: Tertiary				
Age of Mineralization: Tertiary Production History	Geochemical Analyses			
Age of Mineralization: Tertiary Production History Production 135 tons ¹ Reserves greater than 1000 tons ¹ (1954) ⁴ 8600 tons at 19.3% Mn. (1955) ⁴ 600 tons at 19.0% Mn.	Geochemical Analyses Average ore produced reserves 10%	¹ 29% Mn. Mn.		
Age of Mineralization: Tertiary Production History Production 135 tons ¹ Reserves greater than 1000 tons ¹ (1954) ⁴ 8600 tons at 19.3% Mn. (1955) ⁴ 600 tons at 19.0% Mn.	Geochemical Analyses Average ore produced reserves 10%	¹ 29% Mn. Mn.		
Age of Mineralization: Tertiary Production History Production 135 tons ¹ Reserves greater than 1000 tons ¹ (1954) ⁴ 8600 tons at 19.3% Mn. (1955) ⁴ 600 tons at 19.0% Mn.	Geochemical Analyses Average ore produced reserves 10%	¹ 29% Mn. 3 Mn.		
Age of Mineralization: Tertiary Production History Production 135 tons ¹ Reserves greater than 1000 tons ¹ (1954) ⁴ 8600 tons at 19.3% Mn. (1955) ⁴ 600 tons at 19.0% Mn.	Geochemical Analyses Average ore produced reserves 10%	¹ 29% Mn. Mn.		
Age of Mineralization: Tertiary Production History Production 135 tons ¹ Reserves greater than 1000 tons ¹ (1954) ⁴ 8600 tons at 19.3% Mn. (1955) ⁴ 600 tons at 19.0% Mn.	Geochemical Analyses Average ore produced reserves 10%	¹ 29% Mn. 3 Mn.		
Age of Mineralization: Tertiary Production History Production 135 tons ¹ Reserves greater than 1000 tons ¹ (1954) ⁴ 8600 tons at 19.3% Mn. (1955) ⁴ 600 tons at 19.0% Mn.	Geochemical Analyses Average ore produced reserves 10%	¹ 29% Mn. 3 Mn.		
Age of Mineralization: Tertiary Production History Production 135 tons ¹ Reserves greater than 1000 tons ¹ (1954) ⁴ 8600 tons at 19.3% Mn. (1955) ⁴ 600 tons at 19.0% Mn.	Geochemical Analyses Average ore produced reserves 10%	¹ 29% Mn. Mn.		
Age of Mineralization: Tertiary Production History Production 135 tons ¹ Reserves greater than 1000 tons ¹ (1954) ⁴ 8600 tons at 19.3% Mn. (1955) ⁴ 600 tons at 19.0% Mn.	Geochemical Analyses Average ore produced reserves 10%	¹ 29% Mn. 3 Mn.		
Age of Mineralization: Tertiary Production History Production 135 tons ¹ Reserves greater than 1000 tons (1954) ⁴ 8600 tons at 19.3% Mn. (1955) ⁴ 600 tons at 19.0% Mn. Refer	Geochemical Analyses Average ore produced reserves 10%	¹ 29% Mn. 3 Mn.		

.

1

)

COUNTY: MOHAVE NAME: BLACK DIA MOND GROUD SEILX R 12 W SEC. 546 El 2400' DISTRICT: ARTILLERY (MTS) t / / N Artilley Ph 15 Mineralization: Mn

Geology:

Type Operation:

Production:

References: USBM 1.C. 7843 p38 22 unpal. ilaimo

Mohave Cty. Card File

AMERICAN-BLACK DIAMOND Owens Dist., Mohave County MINE & MILL 6 Claims

Information from MINE INSPECTOR'S OFFICE - August 15, 1957

✓ MANGANESE

/LEWIS-PETERSON, Owner - Mines - Kingman, Ariz. /FLOYD BROWN- Oper Mill - Wenden, Arizona) Lessees. /JIM ROBINETTE - Supt.)

DEVELOPING 4-19-57

L.A.S.

See:MINING WORLD, December, 1958, p 58

AMERICAN - See: "MANGANESE DEPOSITS OF WESTERN ARIZONA" VISEM - 10. 7843, p 51

BLACK DIAMOND GROUP - See: " p 38

See: SITTON MILL (file)

ABM Bull. 180, p. 217

1165 743 30-50

DEPARTMENT OF MINERAL RESOURCES STATE OF ARIZONA FIELD ENGINEERS REPORT

Mine	BLACK DIAMOND G	ROUP	1	Date	January	26, 1	A43 - 19
District	Owens, Mohave	Co., .	Ariz.	Engineer	Elgin B.	Holt	the second se

Subject:

OWNERS: George H. Lewis, Joe Lewis and Mrs. Bessie Thompson, Box 151 Kingman, Arizona.

METALS: Manganese.

LOCATION & AREA: This group, consisting of 4 mining claims, is located in the Owens Mining District, Mohave County, Arizona, at a point about five miles southeasterly from Artillery Peak, and about 7 miles easter-ly from Alamo Crossing, about two miles north of the Williams River. It is reached by a newly constructed road, which leaves the Alamo-Wenden road about 4 miles east of Alamo Crossing. Thence the new road extends north-east and crosses the Williams River, about 6 miles northeasterly from Alamo Crossing. Thence the road goes north two miles up Needles-Eye sand wash, from which point the property is reached by a foot path which leads up a mountain side two miles to the east.

GEOLOGY - VEINS: The country rock consists of sandstone and conglomerate, with andesite in evidence here and there. The sandstone and conglomerate, within the boundary lines of property, are traversed bu a series of manganese veins, from one to 4 feet wide, striking northwest and southeast and dipping slightly northeast.

MINE WORKINGS: Consist of test pits only, from 5 to 8 feet deep on several of the veins, composed of psilomelane and pyrolusite, with bands of calcite.

CRE RESERVES: No ore reserves have as yet been developed; but as these manganese veins are traceable on the surface for long distances, there is a possibility of developing considerable milling ore, of undetermined grade. I samples two piles of ore, containing from one to two tons each; one/sample assaying 16% and the other 18% manganese. However, it is likely if this property could be developed, considerable shipping ore might be found assaying above 35% Mn. For instance, George H. Lewis furnished me with an assay certificate of a sample taken during August, 1942, by an engineer representing the Humphries Gold Corporation; said samplebeing taken from sorted dump material and the same assayed 35.1% Mn.

ROADS: Should operations be started at this property, it would be necessary to build a road, about 5 miles in length, northwesterly to - exe B Hot apoint where it would connect with an old road leading from Signal to Alamo, via the M. A. Hanna holdings. Such a road would cost about \$6,000 to construct, mainly by bulldozers.

VISIT: This property was inspected by me on January 15, 1943.

Elgin B. Holt, Field Engineer.

DE. ARTMENT OF MINERAL RESOURCES STATE OF ARIZONA FIELD ENGINEERS REPORT

Mine VELACK DIAMOND VAMERICAN District Artillery Peak

Date June 21, 1957

Engineer B. J. Squire

Subject: Activity Report

LOCATION: Mines are located 2 mi N of the Bill Williams Crossing in the ridge on the west side of the Big Sandy. S6,TllN, Rl3W - G & SR Meridian.

ORE:

The American is a vertical 40 foot wide hydrothermally altered zone in the sandstone carrying 7% Mn mine run, with excellent recovery of 39% concentrate by sink-float. Tails are running a little over 2% Mn and jigs and tables recover a 44% concentrate from the sands. Final blend is + 40% Mn concentrate.

The Black Diamond was operated as an underground vein carrying + 15% Mn across 8 feet. It has been opened as an open pit carrying + 12% Mn across 25 feet. Ore tends to run high barite on the hanging wall and recovery by sink float is lowered due to presence of sooty wad. Mine run grade is commercial under present conditions and sink float and jigging recover a + 40% product.

MILL: Twenty ton per hour HMS plant with jigs and tables.

OPERATOR: Floyd Brown & Dale Robinette - leasors from Sitton Minerals & Development Co.

DEFARTMENT OF MINERAL RESOURCES STATE OF ARIZONA FIELD ENGINEERS REPORT

Mine Black Diamond Manganese Date June 2, 1953

Artillery Peak District

Engineer

Geo. F. Reed

Subject: Recent Developments

Note: This property has been covered by earlier reports, now on file.

Present Owners:

Claude Neal and Mark Hall, mail receivable at Kingman, Arizona.

Present Operators:

Sevier Minerals, General Delivery, Kingman, c/o Scott Ellis, Mgr. Phone Black 305.

Recent History:

F.A.Sitton, the well known Uranium operator had the property under lease and option until a few months ago. He did a few hundred feet of adit work and sank a shaft about 80 fest and did some drifting. From this work, he produced some 500 tons of ore assaying about 21.% manganese. The main vein on which he did this work as well as much stripping, is about 12 feet wide. It dips about 60 degrees to the NE. Wall rock is mainly sandstone and gangue is calcite. The manganese is largely hard Psilomelane and mills well according to gov't reports, giving over 90% recovery. Mr. Sitton quit his operation because he thought it looked unprofitable to operate.

Present Operation:

Sevier Minerals, also a Uranium Operator in Utah, plans to build a jigging mill. They are now grading the site for the mill on the Bill Williams River about $2\frac{1}{2}$ miles from the mine. They have at the mine and in Kingman the following new equipment:

> Grizzly to precede jaw crusher Kue Ken 12 by 24 jaw crusher Kue Ken 18 inch cone crusher

Conveyors & screen in closed circuit with secondary crusher

Denver Mineral Jig Duplex 24 by 36 inches.

It is thought that the ore will be reduced to about 3/16 or $\frac{1}{4}$ inch and jigged at possibly 20 tons per hour with this outfit. Custom ore as well as Black Diamond Ore may be trated, treated.

No work to speak of has been done at the mine since Sitton left. First ore is expected to to produced largely from open pit work on the 12 foot vein. Grade is expected to be about 12% manganese, with 40% concentrates being produced.

George F. Reed

DEL (TMENT OF MINERAL RESOURCES STATE OF ARIZONA FIELD ENGINEERS REPORT

Mine Black Diamond

Date Sept. 14, 1951

District Map 8-13 Mohave Co.

Engineer Mark Gemmill

Subject: Manganese

The following information was given to me by Mr. Geo. Farley who together with Claude Neal and Mark Hall, all of Kingman now own the property.

They are starting production now and will ship ore to the mill at Aguila. He stated that the ore will run from 15 to 20 % Manganese, and although he could not tell me the form in which mineral occurs, he said that tests had shown that it would concentrate. They will start on a production of about 30 tons daily and expect to increase tonnage if the operation proves to be profitable. I expect to call at the Aguila Mill soon and will see how it is working out.