



Collar
748-S
-40°

.09 No
 .10
 .32 .035
 .29 .021
 .39 .036
 .38 .013
 .28 .004
 .37 Recovery
 .8 \$ 55
 1.15
 .68 .182
 .75 .088
 .90 .057
 .72 .203
 1.53 .050
 1.05 .202
 .94 .072
 1.58 .060
 .44 .090
 .18 .190
 .25 .040
 .13 .035
 .24 .025
 .11 .030
 .12 .020
 .25 .010
 .14 .020
 .28 .008
 .09 .006
 .71 .038
 .45 .039
 .19 .072
 .18 .012
 .13 .006
 .13 .009
 .22 .009
 .15 .010

.88
 .45
 .58
 .67
 1.53
 .88
 .43
 1.23
 4.38
 3.10
 .77
 .29
 3.05
 2.33
 2.68
 1.70
 .28
 2.42
 2.50
 .80
 .78
 .96
 .312
 1.78
 1.40
 .88
 .32
 .18
 .10
 .30
 .20
 .18
 .22
 .10

.10
 .14
 .11
 .14
 .08
 .12
 .08
 .03
 .49
 .52
 .52
 .42
 .50

CORE
 SLUDGE

NOTE:—
 TRENCH SAMPLES & ASSAYS BY
 GOLDEN QUEEN MINING CO.
 MOJAVE, CALIF.
 SAMPLES & ASSAYS IN RED
 BY U.S.B.M.

UNITED STATES
 DEPARTMENT OF INTERIOR
 BUREAU OF MINES
 ZONIA PROJECT 1417
 KIRKLAND, ARIZONA.
 SECTION THROUGH 748 SOUTH
 TRENCH & D.D. HOLE
 119 = 30ft. W.O.H.