

Footage	% Recovery		% Copper		
	Core	Sludge	Core	Sludge	Accepted
0 - 3	42		0.58		0.58
3 - 8	80	189	1.35	4.08	3.30
8 - 13	44	104	0.65	1.12	1.05
13 - 20	27	45	3.32	3.19	3.20
20 - 25	30	143	4.95	4.12	4.21
25 - 30	26	119	3.15	4.64	4.50
30 - 35	72	137	2.90	1.22	1.65
35 - 40	24	127	1.26	5.26	4.92
40 - 45	38	155	5.50	4.84	4.93
45 - 50	36	106	2.84	4.45	4.24
50 - 55	16	102	1.74	2.68	2.63
55 - 57	15	86	0.79	2.31	2.23
57 - 60	20	61	2.99	2.76	2.78
60 - 65	24	147	0.34	4.20	3.87
65 - 70	38	111	1.50	1.86	1.81
70 - 75	32	94		0.91	0.91
75 - 80	30	142		1.10	1.10
80 - 87	16	100	1.63	3.21	3.12
87 - 92	12	71	4.83	3.32	3.38
92 - 97	16	86	5.98	3.46	3.60
97 - 100	30	405	1.86	1.84	1.84
100 - 105	8	152	1.21	4.73	4.63
105 - 110	24	92	6.68	3.25	3.54
110 - 117	57	107	1.11	1.74	1.61
117 - 121	5	195		5.97	5.97

770 level

Coordinates: 7514.5 north
6190.2 east
Elevation: 2322.7
Bearing: North 10 west
Dip: Minus 55
Depth: 145
Size hole EX

For ore block, see fig. 31

0 100' 200'

Elev. 2,000