



**DIAMOND DRILLING RECOMMENDATIONS
AS SUBMITTED TO U.S. BUREAU OF MINES
INDICATED IN GREEN**

HOLE	BEARING	INCLINATION	LENGTH
GROUP I NO.1	N 75° E	-45°	300 FT
NO.2	"	"	280
NO.3	"	"	280
NO.4	"	"	200
NO.5	"	"	200
GROUP II NO.1	N 70° E	-45°	170
NO.2	"	"	170
NO.3	"	"	170
NO.4	"	"	170
GROUP III NO.1	S 42° E	-45°	200
NO.2	"	-50°	235
NO.3	"	-70°	225
GROUP IV NO.1	N 75° W	-45°	165
NO.2	"	-55°	280
NO.3	DUE W	-45°	280
NO.4	"	-65°	200
NO.5	"	-55°	110
TOTAL			3645 FT.

**CALLAHAN ZINC-LEAD CO.
TOPOGRAPHIC MAP
SOUTHERN SECTION**

1 INCH = 100 FEET

Reduced from 40' scale. Source date 1940, 1941, 1942
Final completion 12-29-42
Topography by C.P. Knobel
Geology by C.R.K.

LEGEND

- Limestone, largely marbleized
- Marble, Quartzite, etc.
- Granite rock
- Vein Quartz
- Granitic intrusives, post-sediment
- Older intrusives, possibly pre-sediment