CONTACT INFORMATION
Mining Records Curator
Arizona Geological Survey
3550 N. Central Ave, 2nd floor
Phoenix, AZ, 85012
602-771-1601
http://www.azgs.az.gov
inquiries@azgs.az.gov

The following file is part of the Walter E. Heinrichs, Jr. Mining Collection

ACCESS STATEMENT

These digitized collections are accessible for purposes of education and research. We have indicated what we know about copyright and rights of privacy, publicity, or trademark. Due to the nature of archival collections, we are not always able to identify this information. We are eager to hear from any rights owners, so that we may obtain accurate information. Upon request, we will remove material from public view while we address a rights issue.

CONSTRAINTS STATEMENT

The Arizona Geological Survey does not claim to control all rights for all materials in its collection. These rights include, but are not limited to: copyright, privacy rights, and cultural protection rights. The User hereby assumes all responsibility for obtaining any rights to use the material in excess of "fair use."

The Survey makes no intellectual property claims to the products created by individual authors in the manuscript collections, except when the author deeded those rights to the Survey or when those authors were employed by the State of Arizona and created intellectual products as a function of their official duties. The Survey does maintain property rights to the physical and digital representations of the works.

QUALITY STATEMENT

The Arizona Geological Survey is not responsible for the accuracy of the records, information, or opinions that may be contained in the files. The Survey collects, catalogs, and archives data on mineral properties regardless of its views of the veracity or accuracy of those data.



E Profile
Horizontal = Vertical
1" = 25'

Champion Pass — Apache Summit Area
Globe — Show Low Highway
Gila County, Arizona

HEINRICHS GEOEXPLORATION COMPANY
80 WEST CRAIT ROAD
P.O. BOX [illegible] TEL. MA 2-4402
TUCSON, [illegible] ARIZONA

KEUFFEL & ESSER CO. MADE IN U.S.A.
K&E STANDARD © CROSS SECTION
KEUFFEL & ESSER CO. MADE IN U.S.A.
K&E STANDARD © CROSS SECTION
KEUFFEL & ESSER CO. MADE IN U.S.A.

July 27, 1960

Mr. Harold Hall, V.P. Engineering
MIN-A-CON Equipment Company
1914 E. Buchanan
Phoenix, Arizona

Mr. Furman Byers, Vice-President
Isbell Construction Company
2808 N. 27th Avenue
Phoenix, Arizona

Mr. Jack DuPont, Chief Engineer
Isbell Construction Company
2808 N. 27 th Avenue
Phoenix, Arizona

Mr. Louis Scott, Chief Geologist
Arizona State Highway Department
1739 W. Jackson
Phoenix, Arizona

DynaMetric, Inc.
2955 East Colorado Blvd.
Pasadena, California

Gentlemen:

In accordance with the joint venture seismic demonstration conducted at Champion Pass - Apache Summit area along proposed new Globe - Show Low state highway alignment on June 20, 1960 and June 21, 1960, we herewith submit to each of you a copy of the results of our interpretation.

Although the results are not as clean cut as we would desire, I believe some definite benefit will be realized. Our average maximum depth of penetration was likely not much over 70 feet, however, with more experience and heavier hammer, and maybe heavier hammer operator too, when necessary, I am sure this could be efficiently extended to 100 feet and, of course, even deeper with caps and primer cord, etc. In any case, there were no indications of major higher velocity increases to any of the cut depths to grade.

Velocity-rippability notes are based on some assumptions and conditions, such as:

1. Diabase seems to be fairly weathered with a strong decomposing tendency which should aid ripping somewhat consistent within reasonable recorded velocity variations. In every case, it should rip.
2. Shale notes are purely on various published experiences elsewhere, as I did not get a good look at the shale exposures. From velocity data only, it would appear to be rippable.
3. Quartzite near surface is quite brittle, seems fairly well laminated and fractured - not massive, all of which often help rippability, even though the velocities might be otherwise too high. Nevertheless, much of the quartzite, and probably the conglomerate, will be either unrippable or extremely tough to rip.
4. Other than the above, most rock less than 4000 feet per second is often found to be rippable, between 4000 feet per second to 6000 feet per second questionable, and above 6000 feet per second very seldom will rip with present available equipment. With heaviest available equipment, the simplest average cut-off point now is to say: below 5000 feet per second may rip and above 5000 feet per second may not rip.
5. Unfortunately, we have not yet had the opportunity to inspect the core and soil samples in Phoenix.

Let us know if there are any questions. On the plotted travel time curves, velocities were purposely left off in case any one wished to apply re-interpretations. For ourselves, we used the original graphs.

We will look forward to keeping in touch with progress and further correlation of data and results.

Very truly yours,

Walter E. Heinrichs Jr.
President & General Manager

WEH/pr

FED. ROAD DIVISION	STATE	PROJECT NO.	SHEET NO.	TOTAL SHEETS	AS BUILT
7	ARIZ.	F-026-1(9)			

GLOBE - SHOW LOW HWY.
APACHE PEAK TO McMILLAN
GILA COUNTY

Geologic Profiles
July 1959

STA. 463+41.24
BEG. F-026-1(9)
END F-026-1(8)

Diabase - Stony Soil

+3.22000%

Diabase - Seamy & Weathered
Rip - Shrinkage Even to 5%
Cut Slope - 1/4:1 or C-2
Est. PI-15 to 30

Note: Diabase cut on Old Hwy
Rt. of Sta. 468+50
is 53° for 25' Hgt.

PI Elev. 4504.00
Corr. +1.39'

+6.60%

Fill

Fill
Old Hwy

outcrop - weathered Sandy Diabase

Ditch Lt.

outcrop - weathered Sandy Diabase

PI Elev. 4521.66
Corr. - 2.76'

+6.00007%

SOUTH CAMP
TO ROMAN

800' V.C.

100' V.C.

+40 Ditch Rt.
New 24" x 1.00 CMP
Area 0.01

NOTE: All cuts thru Diabase should have cut-ditches 8' to 12' wide for cuts upto 25' high; 12' to 20' wide for cuts up to 100' high; and 28' wide for cuts over 100' high; because of rapid raveling and weathering of Diabase rock, which in this area is commonly highly fractured and has numerous seams & fissures filled with clay.

REDUCED SIZE
DO NOT SCALE.

4580 4570 4560 4550 4540 4530 4520 4510 4500 4490 4480

4670 4660 4650 4640 4630 4620 4610 4600 4590 4580 4570 4560 4550

450 51 52 53 54 455 56 57 58 59 460 61 62 63 64 465 66 67 68 69 470 71 72 73 74 475 76 77 78 79 480

GLOBE - SHOW LOW HWY.
APACHE PEAK TO McMILLAN
GILA COUNTY

FED. ROAD DIVISION	STATE	PROJECT NO.	SHEET NO.	TOTAL SHEETS	AS BUILT
7	ARIZ.	F-026-1(9)			

REDUCED SIZE
DO NOT SCALE.

Note: Pioneer Formation: Upper part of Pioneer Fm. consists essentially of very hard sandy shale gray to blue-black in color - highly fractured.

Ditch + Dyke Lt.

Talus & Slope Wash 1' to 10' over Diabase

Pioneer Fm. Dip 13° to Bedding - Exaggerated on this profile due to Vertical Scale.

Weathered Diabase Exposed in bank of Borrow Cut

Note: This Contact is very irregular due to nature of the Diabase intrusion as a sill.

Diabase - Seamy Weathered
Rip - Shrink Even to 5%
Cut Slope - 3/4:1
Est. PI = 20 to 40

Note: For Engineering Data on Pioneer Formation See Next Sheet

Ditch + Dyke Lt.

Boulder Slope Wash 1' to 5' deep over Weathered Diabase

Weathered Diabase exposed in Bank of Borrow Cut

FILL OLD HWY 60

Boulders Slope Wash 5' to 8' deep

Weathered Diabase

Diabase - Seamy & Weathered
Rip: Shrink: Even to 5%
Cut Slope - 3/4:1 or 1:1
Est. PI = 15 to 30

Note: Diabase Cut on Old Hwy 240' Rt Sta. 481+00 is 54° for 20' Hgt.

Area .120

+30' 6'x6' Conc. Box Culvert 25° Skew Lt

FILL

Boulder Slope Wash

3' to 16' Soil over Diabase

Weathered Diabase

+30' 42"x 50' RCP Skew 25° Rt Area .031

Area .013

+70' 30"x 84' RCP Extend 90' Rt Skew 18° Rt

FILL

Old Fill

Old Hwy 60

Talus & Slope Wash

Borrow Cut

Pioneer Fm.

Intrusive Contact on Sill

Weathered Diabase - Fractured - Seamy

Profile - Natural Scale
Horizontal - Vertical 1" = 100'

4870 4860 4850 4840 4830 4820 4810 4800 4790 4780 4770 4760 4750 4740 4730 4720 4710 4700 4690 4680 4670 4660 4650 4640 4630

480 81 82 83 84 485 86 87 88 89 490 91 92 93 94 495 96 97 98 99 500 01 02 03 04 505 06 07 08 09 510



Distance in feet →

E. Profile

Horizontal = Vertical

1" = 25'

CHAMPION - PASS - APACHE SUMMIT AREA

GLOBE - SHOW LOW HIGHWAY

GILA COUNTY, ARIZONA

HEINRICHS GEOEXPLORATION COMPANY
806 WEST GRANT ROAD
P.O. BOX 5671 TEL. MAIN 2-6702
TUCSON ARIZONA

KE STANDARD ① CROSS SECTION
KEUFFEL & ESSER CO.
MADE IN U.S.A.

FED. ROAD DIVISION	STATE	PROJECT NO.	SHEET NO.	TOTAL SHEETS	AS BUILT
7	ARIZ.	F-026-1(9)			

GLOBE - SHOW LOW HWY.
APACHE PEAK TO McMILLAN
GILA COUNTY

Description of Rock Formations:

Diabase - Seamy & Weathered

Pioneer Fm - Very hard sandy shale - gray to blue-black in color - highly fractured.

Barnes Conglomerate - 15' to 35' thick - rounded pebbles & cobbles of Quartzite in matrix of Arkosic S.S. - Gray color

Dripping Spring Quartzite - medium-grained, gray to light brown color - Quartzite in laminated beds from 1" to 8' in thickness

Engineering Properties of Rock Formations

Weathered Diabase: Rip - Shrink Even to 5% - Cut Slope = ¾:1 - Est. PI = 20 to 40 - Chunky (less than 6" dia) becomes soap

Pioneer Shale Fm: Shoot - Swell 20-25% - Cut Slope = ¾:1 or ½:1 - Est. PI = 5 to 15 - Blocky & Slabby (6" to 2' dia) on dip & bedding

Barnes Conglomerate: Shoot - Swell 20% - Cut Slope = ½:1 or ¾:1 - Est PI = 5 to 10 - Blocky (1' to 3' dia) irregular on Jts.

Dripping Spring Quartzite: Shoot - Swell 20-25% - Cut Slope = ½:1 - Est PI = N.P. to 10 - Blocky (6" to 8' dia) cubical on Jts.







Note: Log data shown for Core Holes No.'s A1 & A4 based on driller's interpretation. The writer has not seen these cores.

JDIII
9-15-59

REDUCED SIZE
DO NOT SCALE.



Note: This profile is schematic only, because the drill hole data has been projected on to the ℄ plane. For true representation of the geologic conditions, see natural scale profiles below.







GLOBE - SHOW LOW HWY.
APACHE PEAK TO McMILLAN
GILA COUNTY

FED. ROAD DIVISION	STATE	PROJECT NO.	SHEET NO.	TOTAL SHEETS	AS BUILT
7	ARIZ.	F-026-1(9)			

REDUCED SIZE
DO NOT SCALE.

Cr. D & L

Pl Elev 5014.00
Corr. - 48.00

Outcrop Spring

Spring Quarter

Soil-Rubble-Stone Mixture 1'-10'

Sandstone Outcrop

Stratified Blocky (3'-5' dia) Quartzite
Shoot - Swell 20 - 25%
Cut Slope - ½:1 or ¾:1 Bottom 20' - Max 34:1
and round off top of slope
Need 15' to 20' cut ditch to pocket against falling rock because dip of strata is into Highway at 17%.
Est. PI's = NP to 10

Outcrop Quartzite Stony Fractured

Slope Wash & Rubble

Core B1

Apparent dip about 7°

Apparent dip about 10°

Weathered Diabase Stony

Diabase - Stony Soil

Weathered Diabase
Rip - Shrink + Swell 5%
Cut Slope - ¾:1 or 1:1
Est. PI's 15 to 20

Rock is Sound
Varies from
Solid to Stony
fractured

Shoot - Swell 10 to 15%
Cut Slope - ½:1
Est. PI's 15 to 30

Diabase - Stony Soil

Outcrop - Weathered Diabase

Profile - Natural Scale
Horizontal = Vertical
1" to 100'

3200' U.C.

Note: Need Drill Data from Core B1 to complete Section - Do not know exactly what depth the Barnes conglomerate or Diabase may be encountered

Area 10.12 Acres
Area 43.80 Acres
Area 42.44 Acres
Area 1.04 Acres
+40
5X16PR

#1 #2 #3 #4

STANDARD ® CROSS SECTION 10 X 10

GLOBE - SHOW LOW HWY.
APACHE PEAK TO McMILLAN
GILA COUNTY

FED. ROAD DIVISION	STATE	PROJECT NO.	SHEET NO.	TOTAL SHEETS	AS BUILT
7	ARIZ.	F-026-1(9)			

REDUCED SIZE
DO NOT SCALE.

Diabase - Streamy Soil

Diabase - Boulders on surface

Weathered Diabase - Rock may be buried at depth - fractured - Seamy

Rip - (Maybe to Short some) Shrink & Swell - Extra
Est PT = 15 to 30
Cut Slope - 3/4:1

Diabase - Streamy Soil

-6.0000 %

Diabase - Sandy Soil

Sandy Soil with Diabase Float

Area 0.19 30" Pipe x 190'

Diabase - Sandy Soil

Sandy Soil with Diabase Float

Area 1.26 49

Wash Alluvium - Sandy with Boulders 1'-3' deep over Diabase

Mixed Alluvium and Slope Wash

Weathered Granite

Granite

Fault (See Air Photo No. 1-9-6)

Alluvium & Slope Wash

Wash Boulders Alluvium

Weathered Diabase

Granite

Fault - Location inferred

6.0000 %

Highly Weathered Diabase Sandy - loose boulders Breaks rip

Rip - Shrink - 10 to 15%
Cut Slope - 1:1
Est. PT = 15 to 40

Apparent Contact of Pediment Gravels

Sandy Soil - Diabase Float

Slope wash - Diabase and Granite

Depth inferred

Weathered Diabase Sandy - Unweathered Spheroidal Boulders of Weathering Boulders are hard 2' to 4' in diameter

Rip - (May have to shoot some)
Shrink - Even to 5%
Est. PT = 15 to 30
Cut Slope - 3/4:1

Depth inferred

Slope wash - Diabase and Granite

Weathered Granite - Partly Disintegrated

Irregular intrusive contact of Diabase into "Granite"

Sandy Soil with Diabase Float and Diabase Boulders

Slope wash with Diabase Float and Sandy Soil

PI Elev. 4660.00
Curve # 11.19'

4660+00

1000' V.C.

4575+00

Apparent Contact of Pediment Gravels

Weathered Diabase - Sandy

Weathered Diabase - Boulderous

Grades

Slope wash

Irregular intrusive contact inferred

Outcrop of Weathered Diabase

Weathered Diabase

5650+00

5750+00

6000+00

℄ Profile - Natural Scale
Horizontal = Vertical
1" to 100'

4900 4890 4880 4870 4860 4850 4840 4830 4820 4810 4800 4790 4780 4770 4760 4750 4740 4730 4720 4710 4700 4690 4680 4670 4660 4650 4640 4630 4620 4610

570 71 72 73 74 575 76 77 78 79 580 81 82 83 84 585 86 87 88 89 590 91 92 93 94 595 96 97 98 99 600

GLOBE - SHOW LOW HWY.
APACHE PEAK TO McMILLAN
GILA COUNTY

FED. ROAD DIVISION	STATE	PROJECT NO.	SHEET NO.	TOTAL SHEETS	AS BUILT
7	ARIZ.	F-026-1(9)			

615 620 625

Thin Cover of Pediment Gravels - 1 to 5' deep
High in Clay

Residual Sandy Clay Soil 3' to 5' deep over Diabase

Weathered Diabase fractured - Seamy

Weathered Diabase fractured - Seamy

Diabase - Strong Ground

Diabase

P.I. Elev. 4722.00
Corr. 23.24

-5500.00'

Diabase

Diabase - Strong Ground

+2952.48'

P.I. Elev. 4660.00
Corr. 11.19'

-6200.00'

Note: Condition of Diabase at Grade Not Known - Will need data from Core Holes C1 & C2 to Complete Section

1000' V.C.

2200' V.C.

Ditch Lt.

Area of 19
10'x6' Box

Overlay - Highly Weathered Sandy Loose Diabase Boulders up to 2' dia.

Highly Weathered Diabase

Irregular Intrusive Contact Inferred

Diabase - Weathered Fractured Seamy

E Profile - Natural Scale
Horizontal = Vertical
1" = 10.00'

REDUCED SIZE
DO NOT SCALE.

Core C1 617+25 - "A"

Core C2

4760 4750 4740 4730 4720 4710 4700 4690 4680 4670 4660 4650 4640 4630 4620 4610 4600 4590 4580 4570

600 01 02 04 605 06 07 08 09 610 11 12 13 14 615 16 17 18 19 620 21 22 23 24 625 26 27 28 29 630

FED. ROAD DIVISION	STATE	PROJECT NO.	SHEET NO.	TOTAL SHEETS	AS BUILT
7	ARIZ.	F-026-1(9)			

GLOBE - SHOW LOW HWY.
APACHE PEAK TO McMILLAN
GILA COUNTY



℄ Profile - Natural Scale
Horizontal = Vertical
1" = 100'

REDUCED SIZE
DO NOT SCALE.

GLOBE - SHOW LOW HWY.
APACHE PEAK TO McMILLAN
GILA COUNTY

FED. ROAD DIVISION	STATE	PROJECT NO.	SHEET NO.	TOTAL SHEETS	AS BUILT
7	ARIZ.	F-026-1(9)			

REDUCED SIZE
DO NOT SCALE.

Note: Condition of Diabase at Grade not known. Will need data from Core Hole D1 to complete section

Core D1 - 680+25 - 60 feet

E Profile - Natural Scale
Horizontal & Vertical
1" to 100'

GLOBE - SHOW LOW HWY.
APACHE PEAK TO McMILLAN
GILA COUNTY

FED ROAD DIVISION	STATE	PROJECT NO.	SHEET NO.	TOTAL SHEETS	AS BUILT
7	ARIZ	F-026-1(9)			

Profile - Natural Scale
Horizontal = Vertical
1" to 100'

Weathered Diabase
fractured - Seamy
Shoot (May Rip Some)
Swell - 15%
Cut Slope ½:1
Est. PI = 10 & 25

Short - Swell - 20%
Cut Slope ½:1
Est. PI = NP - 10

Hard Dense - fine grained Blue Diabase

Shoot this Section
Swell - 20 to 25%
Cut Slope - will Stand ½:1
Est. PI = NP - 5

Rip this section
(May want to shoot some)
Shrink - 10 to 15%
Cut Slope - will Stand ½:1
Est. PI = 15 to 30

Shoot this section
Swell - 20 - 25%
Cut Slope - Will Stand ½:1
Est. PI = NP - 5

Rip this section
(May want to shoot some)
Shrink - 10 to 15%
Cut Slope - will Stand ½:1
Est. PI = 15 to 30

Rip this Section
Shrink - 15 to 20%
Cut Slope - will Stand ½:1
but need 12' wide cut ditch
to catch cuttings - Easily
eroded - material thin-bedded
Est. PI = over 30+
High in Clay

Contact inferred
(See Cut - Old Hwy 60
150' Right Sta. 715+00)

691+42
Area 0.017
30" Pipe x 160'
3:1 Slope

695+85
Area 0.007
24" Pipe x 170'

Area 0.942
10 x 6 Box

700
30" x 60' Right
24" x 46' Lt.
Outlet Ditches
10 C.Y. Drop Exc.
20 C.Y. Struct. Exc.

Rock Berm Lt.
or Type A BK. Prot.

Channel Change Lt.
20' x 5' D x 250' L

10' 10' 20'

Wash or Arroyo

Ordovician Hard Fractured Diabase

Diabase - Seamy Ground

Weathered Diabase Seamy

Hard Fractured Blue Diabase Seamy

Dense Blue Diabase

Altered Gray Diabase

Linear Seamy Diabase

Contact inferred
Old Hwy 60 Cut
150' Right Sta. 715+00

REDUCED SIZE
DO NOT SCALE.

STANDARD ® CROSS SECTION 10 X 10

690 91 92 93 94 695 96 97 98 99 700 01 02 03 04 705 06 07 08 09 710 11 12 13 14 715 16 17 18 19 720

4690 4680 4670 4660 4650 4640 4630 4620 4610 4600 4590 4580 4570 4560 4550 4540 4530 4520 4510 4500

July 27, 1960

Mr. Harold Hall, V.P. Engineering
MIN-A-CON Equipment Company
1914 E. Buchanan
Phoenix, Arizona

Mr. Furman Byers, Vice-President
Isbell Construction Company
2808 N. 27th Avenue
Phoenix, Arizona

Mr. Jack DuPont, Chief Engineer
Isbell Construction Company
2808 N. 27 th Avenue
Phoenix, Arizona

Mr. Louis Scott, Chief Geologist
Arizona State Highway Department
1739 W. Jackson
Phoenix, Arizona

DynaMetric, Inc.
2955 East Colorado Blvd.
Pasadena, California

Gentlemen:

In accordance with the joint venture seismic demonstration conducted at Champion Pass - Apache Summit area along proposed new Globe - Show Low state highway alignment on June 20, 1960 and June 21, 1960, we herewith submit to each of you a copy of the results of our interpretation.

Although the results are not as clean cut as we would desire, I believe some definite benefit will be realized. Our average maximum depth of penetration was likely not much over 70 feet, however, with more experience and heavier hammer, and maybe heavier hammer operator too, when necessary, I am sure this could be efficiently extended to 100 feet and, of course, even deeper with caps and primer cord, etc. In any case, there were no indications of major higher velocity increases to any of the cut depths to grade.

Velocity-rippability notes are based on some assumptions and conditions, such as:

1. Diabase seems to be fairly weathered with a strong decomposing tendency which should aid ripping somewhat consistent within reasonable recorded velocity variations. In every case, it should rip.
2. Shale notes are purely on various published experiences elsewhere, as I did not get a good look at the shale exposures. From velocity data only, it would appear to be rippable.
3. Quartzite near surface is quite brittle, seems fairly well laminated and fractured - not massive, all of which often help rippability, even though the velocities might be otherwise too high. Nevertheless, much of the quartzite, and probably the conglomerate, will be either unrippable or extremely tough to rip.
4. Other than the above, most rock less than 4000 feet per second is often found to be rippable, between 4000 feet per second to 6000 feet per second questionable, and above 6000 feet per second very seldom will rip with present available equipment. With heaviest available equipment, the simplest average cut-off point now is to say: below 5000 feet per second may rip and above 5000 feet per second may not rip.
5. Unfortunately, we have not yet had the opportunity to inspect the core and soil samples in Phoenix.

Let us know if there are any questions. On the plotted travel time curves, velocities were purposely left off in case any one wished to apply re-interpretations. For ourselves, we used the original graphs.

We will look foreward to keeping in touch with progress and further correlation of data and results.

Very truly yours,

Walter E. Heinrichs Jr.
President & General Manager

WEH/pr


NO. 340/ -10 DIETZGEN GRAPH PAPER
10 X 10 PER INCH
EUGENE DIETZGEN CO.
MADE IN U. S. A.
S ←
545+50'
G
7/21/60
546+00
546+50
547+00
547+50
G
→ N
(0,192 Sec.?)
Top Soil & Talus = 3'
68
74 74 75
50
192 - 188
Grade
100
Grade
Av. Depth = 5000'/11
175
150
125
100
75
50
25
0
225/.075" = 3000'/11
40'/.010" = 4000'/11
20'/.005" = 2665'/11
30'/.010" = 3000'/11
45'/.015" = 6000'/11
30'/.015" = 4000'/11
22.5'/.015" = 1500'/11
1000'/11
28'±
~8'
3'
25'
50'
75'
100'
125'
150'
175'
200'
3'

NO. 340/ -10 DIETZGEN GRAPH PAPER
10 X 10 PER INCH
EUGENE DIETZGEN CO.
MADE IN U. S. A.

S ← 547+50'

G

548+00

7/21/60

548+50

549+50

549+50'

G

175

150

125

100

75

50

25

0

(8)

Bse Rock Otc.

11 37-37-37 = Bse Rock

11 11 10 both check ok

Plate

39/22 - 37-37

Ridge or BR-Lo.

gullie or BR-hi

200/.050' = 4000'/11 Av.

11 000
7000
18 000

Av = 9000'/11

Av = 10,000'/11

Av section 5 = 9000'/11

17 13
3 3 33
50 46

Av = 2500'/11

11 000
1 000
1 380
3 49 380
6 460

10'/.0075 = 1333 1/3'/11

35'/.005 = 7000'/11

30'/.0075 = 10,000'/11

32.5'/.025 = 2600'/11

27.5'/.0025 = 11,000'/11

25'/.0075 = 3333 1/3'/11

39'/.015 = 1713 1/3'/11

225'/.010 = 2250'/11

25'/.0025 = 10,000'/11

9 1/2'

25'

0 1.5' 25' 50' 75' 100' 125' 150' 175' 3' 200' 1.5'

NO. 340/ -10 DIETZGEN GRAPH PAPER
10 X 10 PER INCH
EUGENE DIETZGEN CO.
MADE IN U. S. A.

S ←
549+50
G

7/21/60

→ N
G
551+50'

550+00'
550+50'
551+00'

175
150
125
100
75
50
25

Looking Westerly

Slight down hill to N →
but even
Fractured Qtzite ote
most of way

9

4000
1800
5800
4
2900

3500
1600
4300
2150'/"

Hd rift.

Avdep 3500'/"

Middle Av = 2150'/"

Hd rift

Sft zone.

?

32.5'/12.5" = 3000'/"

couldn't get energy thru

45'/.225" = 1600'/"

1'/.30" = 833'/"

27.5'/.125" = 2200'/"

30'/.0075" = 4000'/"

1800'/"

0 ≅1.5' 2.5' 25' 50' 75' 100' 125' 150' ≅17' 175' ≅1.5' 200'

NO. 340/ -10 DIETZGEN GRAPH PAPER
10 X 10 PER INCH
EUGENE DIETZGEN CO.
MADE IN U. S. A.

5 ←

551+50 G

7/21/60

552+00 552+50 553+00 553+50 DH B-1 554+00 G

→N

0.224 Sec

0.214 Sec

Mitchell - 2 gears

58 60 61

57 58 62 62

10

9

4 of 5

4500 2880 7380

7380 / 11 = 3690 / 11 = 3700 / 11

Hard-ite

7000 / 11

5500 / 11 ?

?

In Door Cut

Mitchell

57.5' / .020" = 2850 / 11

22.5' / .005" = 4500 / 11

67.5' / .175" = 3860 / 11

75' / .005" = 15,000 / 11

47.5' / .075" = 2713 / 11

1000 / 11

0.8'

100 75 50 25 0 Feet

N = 3'


S
530+00
530+50
531+00
531+50
N
G
G
175
529+50
150
125
100
75
50
0.025
SECONDS
TIME IN
7/20/60
Looking Westerly.
High Speed
Low Speed
100'/0.117 = 855'/"
50'/0.125 = 400'/" ±
Penetration
50±
Penetration
33'±
= Shaley diabase?
50'/0.007 = 7150'/"
100'/0.0375 = 2665'/"
Relative Hi V
up dip?
" elev
down dip?
down elev.
Relative Lo V
25'/0.025 = 1000'/"
50'/0.014 = 3570'/"
40'/0.023 = 1740'/"
13'/0.025 = 480'/"
28'/0.020 = 1400'/"
Xc3 = 100'
D3 ≈ 33'
Xc1 = 10/2 | 030/2410 = 5 | 0.36
25
D1 = 5 x 0.6 = 3'
Xc2 = 48'
D2 ≈ 16'
Xc2 = 22'
D2 ≈ 7'
Xc1 = 5'
D1 = 1.5'
At V1 = 740'/"
" V2 = 1570'/"
" V3 = 2920'/"
" V4 = 6175'/"
= Shale?

Hi ⟷ Lo

← Hi → Lo



V_3 = 7000'/m ±

Pronicer Shale.