CONTACT INFORMATION
Mining Records Curator
Arizona Geological Survey
3550 N. Central Ave, 2nd floor
Phoenix, AZ, 85012
602-771-1601
http://www.azgs.az.gov
inquiries@azgs.az.gov

The following file is part of the Anderson Mine Collection

ACCESS STATEMENT

These digitized collections are accessible for purposes of education and research. We have indicated what we know about copyright and rights of privacy, publicity, or trademark. Due to the nature of archival collections, we are not always able to identify this information. We are eager to hear from any rights owners, so that we may obtain accurate information. Upon request, we will remove material from public view while we address a rights issue.

CONSTRAINTS STATEMENT

The Arizona Geological Survey does not claim to control all rights for all materials in its collection. These rights include, but are not limited to: copyright, privacy rights, and cultural protection rights. The User hereby assumes all responsibility for obtaining any rights to use the material in excess of "fair use."

The Survey makes no intellectual property claims to the products created by individual authors in the manuscript collections, except when the author deeded those rights to the Survey or when those authors were employed by the State of Arizona and created intellectual products as a function of their official duties. The Survey does maintain property rights to the physical and digital representations of the works.

QUALITY STATEMENT

The Arizona Geological Survey is not responsible for the accuracy of the records, information, or opinions that may be contained in the files. The Survey collects, catalogs, and archives data on mineral properties regardless of its views of the veracity or accuracy of those data.

MINERALS EXPLORATION CO.

CASPER, WYOMING

LOCATION	ANDERSEN MINE
COUNTY	YAVAPAI
STATE	ARIZONA
GP.	1683'SOU 894'WE SEC
ELEV.	2033
SEC.	
TWP.	
RGE.	
DATE	2-2-77
DEPTH DRILLED	800
DEPTH LOGGED	802
FOOTAGE LOGGED	915
HOLE DIAMETER	5 5/8
WATER FACTOR	1.02
RESISTIVITY	150 OHMS/INCH
SELF POTENTIAL	M.V./IN.

RERUNS	1ST. RUN	2ND. RUN	3RD. RUN
BOTTOM	780		
TOP	767		
TOTAL FEET	13		
SCALE RUN	2K:200CPS/in		

HOLE NO.	AM 361
GAMMA SCALE	500+500CPS/in
PROBE TYPE	SCINT.
K-FACTOR	5.70x10-5
DEAD TIME	7.18m
TIME CONSTANT	1
PROBE DIA.	1 5/8
CALIPER	
DIRECTIONAL SURVEY	
TEMPERATURE	
OPERATOR	KETCHUM
DRILLER	SAM
CONTRACTOR	UNIVERSAL
LAST A.E.C. PIT RUN	
FLUID LEVEL	
REMARKS:	



MINERALS EXPLORATION CO.

CASPER, WYOMING

HOLE NO. AM 362

LOCATION ANDERSEN MINE

COUNTY YAVAPAI STATE ARIZONA

GR. ELEVATION ELEV. 2061

SEC.	TWP.	RGE.

DATE	2-3-77
DEPTH DRILLED	825
DEPTH LOGGED	823
FOOTAGE LOGGED	823
HOLE DIAMETER	5 5/8
WATER FACTOR	1.22
RESISTIVITY	200
SELF POTENTIAL	

RESONS	1ST. RUN	2ND. RUN	3RD. RUN
BOTTOM	653	629	604
TOP	592	617	573
TOTAL FEET	11	12	31
SCALE RUN	2R=200CPS/in	2R=100CPS/in	2R=200CPS/in

OHMS/INCH M.V./IN.

GAMMA SCALE	200-400CPS/in
PROBE TYPE	SCINT.
K-FACTOR	5.70x10-5
DEAD TIME	7.18 m.
TIME CONSTANT	1
PROBE DIA.	1 5/8
CALIPER	
DIRECTIONAL SURVEY	
TEMPERATURE	
OPERATOR	HETHERING
DRILLER	JIM
CONTRACTOR	UNIVERSAL
LAST A.E.C. PT. RUN:	

FLUID LEVEL

REMARKS:



MINERALS EXPLORATION CO.

CASPER, WYOMING

HOLE NO. AM-363

LOCATION	ANDERSON MINE
COUNTY	HAYDAY STATE WYO.
GR. COUNTER-CLOCKWISE	ELEV. 2041

SEC.	TWP. RGE.
DATE	2/18/77
DEPTH DRILLED	780'
DEPTH LOGGED	780'
FOOTAGE LOGGED	890'
HOLE DIAMETER	5⅞" to 780'
WATER FACTOR	
RESISTIVITY	175 OHMS/AMP 75 ohm meters
SELF POTENTIAL	100 M.V./IN FLUID LEVEL

RERUNS	1ST. RUN	2ND. RUN	3RD. RUN
BOTTOM	890'		
TOP	530'		
TOTAL FEET	60'		
SCALE RUN	2.5K-250CPS/IN		

GAMMA SCALE	500+50CPS/IN.
PROBE TYPE	Scint.
K-FACTOR	.5 in^2
DEAD TIME	7 μ sec.
TIME CONSTANT	1
PROBE DIA.	1⅝"
CALIPER	
DIRECTIONAL SURVEY	
TEMPERATURE	
OPERATOR	Hudson
DRILLER	Jim
CONTRACTOR	Roberts
LAST A.E.C. PIT RUN	

REMARKS:



MINERALS EXPLORATION CO.

CASPER, WYOMING

LOCATION	ANDERSON MINE
COUNTY	UINTAH STATE UTAH
GP. LOCATION	ELEV. 2029
SEC. 28 TWP. 12S RGE. 19E	
DATE	12/8/77
DEPTH DRILLED	820'
DEPTH LOGGED	830' 818'
FOOTAGE LOGGED	675'
HOLE DIAMETER	5⅞" to 760'
WATER FACTOR	
RESISTIVITY	OHMS/INCH
SELF POTENTIAL	M.V./IN.

RUNS	1ST. RUN	2ND. RUN	3RD. RUN
BOTTOM	830'	465'	235'
TOP	500'	455'	720'
TOTAL FEET	334'	10'	10'
SCALE RUN	1K-100 CPS/IN	1K-100 CPS/IN	1K-1000 CPS/IN

GAMMA SCALE	500-5000 CPS/IN.
PROBE TYPE	Delta
K-FACTOR	4.44
DEAD TIME	7.19 μsec
TIME CONSTANT	1
PROBE DIA.	1⅝"
CALIPER	
DIRECTIONAL SURVEY	
TEMPERATURE	
OPERATOR	Malone
DRILLER	Jim Roberts
CONTRACTOR	
LAST A.E.C. PIT RUN	
FLUID LEVEL	
REMARKS:	

HOLE NO. AMP-364

0'
50'
100'
150'
200'
250
300'
350'
400'
450'
500'
550'
600'
650'
700'
750'
800'
818'

1K-100 CPS/IN

2.5K-2500 CPS/IN

1K-1000 CPS/IN

500-5000 CPS/IN 60MV 150Ω 100 ohm meters

MINERALS EXPLORATION CO.

CASPER, WYOMING

HOLE NO. AM-365

LOCATION	ANDERSON MINE
COUNTY	Yavapai STATE ARIZ.
GP. ~~1202,414.6N-641,002.3E~~ ELEV. 1970	
SEC. 13 ~~81,339.9~~ 82E TWP. 13N RGE. 9W	
DATE	1-4-77
DEPTH DRILLED	620'
DEPTH LOGGED	615'
FOOTAGE LOGGED	615'
HOLE DIAMETER	5⅝" TO 620'
WATER FACTOR	
RESISTIVITY	OHMS/INCH
SELF POTENTIAL	M.V./IN.

RERUNS	1ST. RUN	2ND. RUN	3RD. RUN
BOTTOM	600'	445'	405'
TOP	590'	430'	390'
TOTAL FEET	10'	15'	15'
SCALE RUN	1K=100CPS/IN.	2.5K-250CPS/IN.	1K=100CPS/IN.

GAMMA SCALE	500=50CPS/IN.
PROBE TYPE	SCINT.
K-FACTOR	57.10-3
DEAD TIME	7.14 μ SEC
TIME CONSTANT	1
PROBE DIA.	1⅝"
CALIPER	
DIRECTIONAL SURVEY	
TEMPERATURE	
OPERATOR	Hudson
DRILLER	Morgan
CONTRACTOR	Adams
LAST A.E.C. PIT RUN	
FLUID LEVEL	
REMARKS:	



MINERALS EXPLORATION CO.

CASPER, WYOMING

HOLE NO. AM-366

LOCATION	ANDERSON MINE	GAMMA SCALE	500=50CPS/IN.
COUNTY	YAVAPAI STATE ARIZ.	PROBE TYPE	SCINT
GP. ~~1202,202.5N 644,167.5~~ 1204,607.03W	ELEV. 1961	K-FACTOR	5.2
SEC. 17 TWP. 12N RGE.		DEAD TIME	7.14 M SEC.
DATE	1-6-77	TIME CONSTANT	1
DEPTH DRILLED	700'	PROBE DIA.	1⅝"
DEPTH LOGGED	694'	CALIPER	
FOOTAGE LOGGED	75%	DIRECTIONAL SURVEY	
HOLE DIAMETER	5⅞" TO 694'	TEMPERATURE	
WATER FACTOR		OPERATOR	HUDSON
RESISTIVITY	OHMS/INCH	DRILLER	SHARP
SELF POTENTIAL	M.V./IN.	CONTRACTOR	ROBERTS
		LAST A.E.C. PIT RUN	
		FLUID LEVEL	

	1ST. RUN	2ND. RUN	3RD. RUN
REMARKS:			
RERUNS			
BOTTOM	595'	465'	400'
TOP	580'	435'	385'
TOTAL FEET	15'	30'	15'
SCALE RUN	1K=100CPS/IN. 2.5K=250CPS/IN	1K=100CPS/IN	



MINERALS EXPLORATION CO.

CASPER, WYOMING

HOLE NO. AM 367

LOCATION ANDERSEN MINE

COUNTY YAVAPAI STATE ARIZONA

1264976.37N 882867.23E

GP. ~~1262,515.9N 648,736.5E~~ ELEV. 1929

SEC. TWP. RGE.

DATE	1-29-77		
DEPTH DRILLED	960		
DEPTH LOGGED	960		
FOOTAGE LOGGED	477		
HOLE DIAMETER	5 5/8		
WATER FACTOR	1.22		
RESISTIVITY	100 OHMS/INCH		
SELF POTENTIAL	M.V./IN.		
RERUNS	1ST. RUN	2ND. RUN	3RD. RUN
BOTTOM	351		
TOP	334		
TOTAL FEET	17		
SCALE RUN	2K=200CPS/IN		

GAMMA SCALE	500=50CPS/IN
PROBE TYPE	SCINT.
K-FACTOR	5.70X10-5
DEAD TIME	7.19u
TIME CONSTANT	1
PROBE DIA.	1 5/8
CALIPER	
DIRECTIONAL SURVEY	
TEMPERATURE	
OPERATOR	KETCHING
DRILLER	SIM
CONTRACTOR	UNIVERSAL
LAST A.E.C. PIT RUN	
FLUID LEVEL	
REMARKS:	



MINERALS EXPLORATION CO.

CASPER, WYOMING

HOLE NO. AM 368

LOCATION	ANDERSEN MINE
COUNTY	YAVAPAI STATE ARIZONA
GP. ~~1208,626.NN 618,007.NE~~ 1205 615 .89N	ELEV. 1916
SEC. 18 33N 7E	TWP. RGE.
DATE	1-25-77
DEPTH DRILLED	500
DEPTH LOGGED	498
FOOTAGE LOGGED	532
HOLE DIAMETER	5 5/8
WATER FACTOR	1.22
RESISTIVITY	100 OHMS/INCH
SELF POTENTIAL	M.V./IN.

	1ST. RUN	2ND. RUN	3RD. RUN
RERUNS			
BOTTOM	913	373	
TOP	392	360	
TOTAL FEET	21	13	
SCALE RUN	SR=500CPS/IN	SR=500CPS/IN	

GAMMA SCALE	500 = 50CPS/IN
PROBE TYPE	SCINT.
K-FACTOR	5.70X10-5
DEAD TIME	7.14 M
TIME CONSTANT	1
PROBE DIA.	1 5/8
CALIPER	
DIRECTIONAL SURVEY	
TEMPERATURE	
OPERATOR	KETCHUM
DRILLER	JIM
CONTRACTOR	UNIVERSAL
LAST A.E.C. PIT RUN	
FLUID LEVEL	
REMARKS:	



MINERALS EXPLORATION CO.

CASPER, WYOMING

HOLE NO. AM 369

LOCATION	ANDERSEN MINE
COUNTY	YAVAPAI
STATE	ARIZONA
GP. ~~1208,516.7N-643,278.3E~~ 1204,884.06N	
SEC. 89 606.74E TWP.	RGE.
ELEV.	1984
DATE	1-28-77
DEPTH DRILLED	540
DEPTH LOGGED	538
FOOTAGE LOGGED	553
HOLE DIAMETER	5 5/8
WATER FACTOR	122
RESISTIVITY	100 OHMS/INCH
SELF POTENTIAL	M.V./IN.

RERUNS	1ST. RUN	2ND. RUN	3RD. RUN
BOTTOM	462		
TOP	447		
TOTAL FEET	15		
SCALE RUN	2.5K=250CPS/IN		

GAMMA SCALE	500=250CPS/IN
PROBE TYPE	SCINT
K-FACTOR	5.70X10-5
DEAD TIME	7.19 μs
TIME CONSTANT	1
PROBE DIA.	1 5/8
CALIPER	
DIRECTIONAL SURVEY	
TEMPERATURE	
OPERATOR	KETTERLING
DRILLER	PRICE
CONTRACTOR	PETRO-LOG
LAST A.E.C. PIT RUN	
FLUID LEVEL	
REMARKS:	



MINERALS EXPLORATION CO.

CASPER, WYOMING

HOLE NO. AM 370

LOCATION	ANDERSEN MINE
COUNTY	YAVAPAI
STATE	ARIZONA
GP. 1305 051 DIN 38 720.60E 1303,667.6N-642,388.5E	ELEV. 1916

SEC.	
TWP.	
RGE.	
DATE	1-28-77
DEPTH DRILLED	420
DEPTH LOGGED	421
FOOTAGE LOGGED	453
HOLE DIAMETER	5 5/8
WATER FACTOR	1.22
RESISTIVITY	100 OHMS/INCH
SELF POTENTIAL	M.V./IN.

RERUNS	1ST. RUN	2ND. RUN	3RD. RUN
BOTTOM	355	295	
TOP	345	273	
TOTAL FEET	10	22	
SCALE RUN	2K=2000CPS/IN	2K=200CPS/IN	

GAMMA SCALE	500=50CPS/IN
PROBE TYPE	SCINT.
K-FACTOR	5.70X10-5
DEAD TIME	7.1μs
TIME CONSTANT	1
PROBE DIA.	1 5/8
CALIPER	
DIRECTIONAL SURVEY	
TEMPERATURE	
OPERATOR	KETTERLING
DRILLER	JIM
CONTRACTOR	UNIVERSAL
LAST A.E.C. PIT RUN	
FLUID LEVEL	
REMARKS:	



PROJECT Anderson Mine — HOLE SIZE ____ ☐ AIR ☑ WATER — HOLE NO. AM 361

ELEVATION 2033 — NORTH 1,201,524.4 — EAST 642,630.2 — LOGGED BY C2H — DATE 2-2-77

SECTION ____ — TOWNSHIP ____ — RANGE ____ — T.D. 800 — P.D. ____

GEOPHYSICAL LOG	DEPTH	P	C	A	STRIP LOG	LITHOLOGY LOG
	0					
	20					
	40					
	60					
	80					Cgl, V. Crs, Tan to Gry w/large Volcanic Frags + Granitic Frags (2' Diameter)
	100					
	120					
	140					
	160					Basalt, DK Gry to Blk
	180					
	200					
	220					
	240					
	260					
	280					
	300					Cgl, Crs SS, Wtan to Tan Brn, Granitic
	320					
	340					
	360					
	380					
	400					
	420					
	440					
	460					
	480					Sltst, Brn, Srdy
	500					

AM 361
1 of 2

PROJECT Anderson Mine — HOLE SIZE ____ ☐ AIR ☑ WATER — HOLE NO. AM 361

ELEVATION 2033 — NORTH 1,201,524.4 — EAST 642,630.2 — LOGGED BY C2H — DATE 2-2-77

SECTION ____ — TOWNSHIP ____ — RANGE ____ — T.D. 800 — P.D. ____

GEOPHYSICAL LOG	DEPTH	P	C	A	STRIP LOG	LITHOLOGY LOG
	500					
	520					
	540					
	560					
	580					
	600					
	620					
	640					
	660					
	680					
	700					
	720					
	740					
	760					
	780					
	800					
	820					
	840					
	860					
	880					
	900					
	920					
	940					
	960					
	980					
	1000					

Sltst, Brn, Srdy

Sltst, Grn Tan, Trace Bentonite

Calcareous Tuff + Grn Sltst, Silicified, w/ Brn Chert, Calc,

Carbonaceous Sltst + Lignite, DK Gry to Blk, Silicified Calc. w/ Intbdd Brn Calc Tuff

SS, Vcl, Med, Slty sorting Poor

Carbonaceous Sltst, DK Gry, Calc Silicified

SS, med, Grn, Poor, Slty w/ Intbdd Grn Mdst

Sltst, Vcl Grn, Bentonitic, Calc

SS + Intbdd Grn Bentonitic Sltst, Samples Very Poor

Samples Very Poor, SS, Blk Volcanics Grn Sltst ?

SS, Crs Cgl, Red Brn Volcanic Frags?

361
2/2

MINERALS EXPLORATION CO.

CASING, WYOMING		HOLE NO.	AM 361
LOCATION ANDERSON MINE		CASING SIZE	200'-10 3/4"
COUNTY YAVAPAI STATE ARIZONA		CASING TYPE	Surf.
SEC. 32 TWP. 13 RGE. 4 ELEV. 2033		ELEVATION	2033 ±
		TIME CASING	1 hr.
		HOLE NO.	1 of 2
		DATE	
		CASING SHOES	
		DRILLING	REVERSE
		CIRCULATION	AIR (INTERMIT.)
		CORE BARREL	
		CORE ALL OR RUN	
		DRILL LEVEL	
		REMARKS	

PROJECT Anderson Mine HOLE SIZE ____ ☐ AIR ☑ WATER HOLE NO. AM 362

ELE. TION 2061 NORTH 201,719.4 EAST 642,179.5 LOGGED BY CJH DATE 2-3-77

SECTION ____ TOWNSHIP ____ RANGE ____ T.D. 840 P.D. 823

GEOPHYSICAL LOG	DEPTH	P	C	A	STRIP LOG	LITHOLOGY LOG
	0					
	20					
	40					
	50					
	60					Cgl, Sndy Slty, V. Crs w/Volcanic + Granitic Frags
	80					
	100					
	1 00					
	20					
	40					Basalt ? or Large Boulder in Cgl Dk Gry to Blk
	60					
	80					
	2 00					Cgl, Sndy, Slty to V. Slty, Lt Tan to Tan Volcanic + Crystalic Frags
	20					
	40					
	60					Cgl, Sndy, Lots (50%) Volcanic Frags
	80					
	3 00					
	20					
	40					
	60					SS Cgl, Med to V. Crs, Ang to Sub Ang, Granitic Tan to Brn, Lower Slty
	80					
	4 00					
	20					
	40					
	60					
	80					
	5 00					Sltst, Tan

AM 362
1 of 2

PROJECT Anderson Mine HOLE SIZE ____ ☐ AIR ☑ WATER HOLE NO. AM 362

ELE. TION 2061 NORTH 201,719.4 EAST 642,179.5 LOGGED BY CJH DATE 2-3-77

SECTION ____ TOWNSHIP ____ RANGE ____ T.D. 840 P.D. 823

GEOPHYSICAL LOG	DEPTH	P	C	A	STRIP LOG	LITHOLOGY LOG
	0					Sltst, Tan
	20					Calc Tuff, Wht + Intbdd Grn Sltst, Silicified
	40					Sltst, Grn, Bentonitic, Non Calc
	50					Sltst, Grn, W/Thin Intbdd Lygitic Sltst
	60					Silicified Sltst, Grn, Sil Calc to Calc, W/Red Brn Chert + Wht Calc Tuff
	80					Sltst, Grn, Trace Carb, Bentonitic, Non Calc Very Slight Silicification
	6 00					
	20					Lignite + Carbonaceous Sltst, Dk Grn Gry to Blk, Calc, Silicified, W/Brn Calc Tuff?
	40					
	60					Silicified Sltst + Calc Tuff, Grn
	80					
	7 00					Sltst, Tan Gry, Bentonitic, Sub to Non Calc
	20					SS, Grn, Med to Crs, Ang to Sub Ang Sorting Poor
	40					Sltst/Mdst, Tan Grn to Grn, Layers of Near Pure Bentonite, Grn Sltst w/Trace Carb. Samples Very Poor V. Sndy due to Slughs From Water Sand @ Est Flow 75 GPm
	60					Lignitic Layers? Carb Com Sltst/Mdst Grade Dk Grn Trace Carb
	80					Lignite + Grn Mdst, Grn + Blk
	8 00					
	20					Slight Brn Tint to Foam All Seeds Abuse have Volcanic Frags but only a few Volcanic Frags increasing Downward
	40					
	60					
	80					
	00					
	20					
	40					
	60					
	80					
	00					

MINERALS EXPLORATION CO.

CASING WITHDRAWN		HOLE NO.	AM 362
LOCATION Anderson Mine		CASING DIAM.	6in Steel
COUNTY Mohave	STATE Arizona	FROM TO	Surf - ?
SW QUARTER SEC. 2061		ELEVATION	2061 ±
		DATE TIME	2-3-77
		TIME STANDING	1 Day
		HOLE DIA.	7 7/8
		CONTRACTOR	
		DRILLING CREW	
		DRILLER	Ringsby
		DRILL	CP 50
		WATER	Well Water
		CAP. & EL. OF MEAS.	
		FLUID LEVEL	
		REMARKS	

AM 362
2 of 2

PROJECT Anderson Mine HOLE SIZE ☐ AIR ☑ WATER HOLE NO. AM363
ELEVATION 2041 NORTH 1,201,796 EAST 642,023.6 LOGGED BY CZH DATE 2-18-77
SECTION TOWNSHIP RANGE T.D. 780 P.D.

GEOPHYSICAL LOG | DEPTH | P | C | A | STRIP LOG | LITHOLOGY LOG

- Cgl, Lt Tan to Lt Gry, W/Volcanic Frags
- Basalt, DK Gry to Blk
- Cgl, Sndy, Lt Tan, Granitic
- Silty to V. Silty
- Sltst, Tan Grn, Bentonitic, w/wht Calc Tuff, Silicified
- Sltst, Grn, Bentonitic
- Carbonaceous, Sltst, Gry, Silicified w/Thin Lignite Layers and Grn Bentonitic Sltst Layers

AM 363
1 of 2

PROJECT Anderson Mine HOLE SIZE ☐ AIR ☑ WATER HOLE NO. AM 363
ELEVATION 2041 NORTH 1,201,797.6 EAST 642,023.6 LOGGED BY CZH DATE 2-18-77
SECTION TOWNSHIP RANGE T.D. 780 P.D.

GEOPHYSICAL LOG | DEPTH | P | C | A | STRIP LOG | LITHOLOGY LOG

- Carb. Sltst, Gry, Silic, w/Thin Lignitic Layers + Grn Bent. Strat Layers
- Silicified Sltst, Gry Grn, w/Intbdd Calc Tuff (wht)
- Sltst, Grn, Bentonitic, Trace to Com Carb
- Carbonaceous Sltst + Lignite, DK Gry to Blk, Calc, Silic, w/Brn Calc Tuff
- Silicified Sltst, Gry Grn, w/Gry Grn + Gry Brn Sub-Chert
- SS, Tan Grn, med, Poor, Trace Hem Stain, Sub Ang
- Sltst, Grn to DK Grn, w/Thin Intbds Lignite
- Sltst, Tan to Tan Grn Bentonitic + Gry Wht Bentonite Layers, Silicified
- SS?, Tan Grn, Sub Ang, Poor, Med, Trace Hem + Lim
- Sltst, Grn, Silicified w/Near Pure Bentonite Layers
- Carbonaceous Sltst, Grn to Gry
- SS, Fine to Med, Tan Grn, Sub Ang, Pool
- Sltst, Tan, Bentonitic
- Carbonaceous Sltst, Gry
- Sltst, Grn
- Carbonaceous, Sltst, Gry
- Sltst w/Volcanic Frags

AM 363
2/2

MINERALS EXPLORATION CO.

CASPER, WYOMING

LOCATION	Anderson Mine	HOLE NO.	AM-363
COUNTY	Uintah	STATE	Utah
QUAD	Myton SE	ELEVATION	2041
SEC.	TWP.	RGE.	
DATE	2/18/77		
DRILL HOURS	1130		
DRILLING HOURS	1030		
HOLE DIAMETER	6 3/4" to 780'		
CASING SIZE			
KEY FORMATION			
CASING	10 3/4	WT.	
BOTTOM	200		
TOP	KB		
TOTAL DEPTH	780		
CORE RUN	0		

LOG TYPE/RUN NO. 1st after surface

	LOG RUN NO. 1		
	DRL. MEAS.	DRL. MEAS.	DRL. MEAS.
	200		
	780		
	KB		
	0		

CASING HEAD	GOOD / LOCATION
ELEVATION	GL+10'
HOLE TYPE	12 1/4 under
HOLE CONDITION	G
HOLE DEV.	1/2
DRILLER	
ADDITIONAL SURVEY	
SURVEYORS	
OPERATOR	Anderson
CONTRACTOR	Mc Kay
LAST 4 1/2, 9.5 CSG.	
FLUID LEVEL	
REMARKS	

PROJECT Anderson Mine HOLE SIZE ☐ AIR ☑ WATER HOLE NO. AM 364

ELEVATION 2029 NORTH 1,202,013.0 EAST 641,807.4 LOGGED BY C ZH DATE 2-16-77

SECTION TOWNSHIP RANGE T.D. 820 P.D.

GEOPHYSICAL LOG | DEPTH | P | C | A | STRIP LOG | LITHOLOGY LOG



100
200
300
400
500

Cgl, Lt Tan to Lt Gry, Volcanic Frags Abnt

Basalt, DK Gry

Cgl, Sndy to V. Crs, Granitic, Slty to V. Slty at Bottom

AM 364
1 of 2

Sltst, Tan

Sltst, Tan Grn, W/Wht Calc Tuff, Trace Brn Chert

Sltst, Grn, Bentonitic, Wht Calc Tuff layers, Trace Silicification

Silicified Sltst, Grn, Calc Tuff, Brn Chert

PROJECT Anderson Mine HOLE SIZE ☐ AIR ☑ WATER HOLE NO. AM 364

ELEVATION 2029 NORTH 1,202,013.0 EAST 641,807.4 LOGGED BY C ZH DATE 2-16-77

SECTION TOWNSHIP RANGE T.D. 820 P.D.

GEOPHYSICAL LOG | DEPTH | P | C | A | STRIP LOG | LITHOLOGY LOG



500
600
700
800

Silicified Sltst, Grn, Calc Tuff, Brn Chert

Sltst, Grn, Bentonitic, Silicified w/Thin Intbds of Lignite, Calc

Calcareous Sltst + Lignite, DK Gry to Blk, w/Brn Calc Tuff and Thin Intbds of Grn moist, Calcareous, Silicified

Calcareous Tuff, Wht to Brn, Lower 10' Much Grn Bentonitic moist, Upper 10' Silicified

Silicified Sltst, Grn, w/Thin Intbds of Lignite and Calc Tuff

SS, Tan Grn, Mod Sorting Poor, Trace Light Hum Stain water Sand Approx 75 to 100 GPM

Sltst, Grn, Silicified, Bentonitic

SS# Silicified Sltst, SS, Crs w/ V. Crs Granitic Frags, Grn w/ Red Brn Tint

Lignitic Material, DK Gry to Blk, Calc, Silicified

SS, Red Brn, Well Cmtd, Granitic, Mod to Crs

moist, Grn

Lignite, Blk, Sub-Calc, Intbdd Carb Sltst + Grn Sltst

SS, w/ Red Granitic Frags + Grn Sltst — Trace Lignite

Sltst Tan + Lt Grn Bentonitic

Sltst, Grn, Lot of Contamination

Sltst, Tan to Lt Pink Tan, W/ orange speckles

Andesitic Volcanics, Red Brn to Gry Brn

MINERALS EXPLORATION CO.

CASPER, WYOMING

LOCATION	ANDERSON MINE
COUNTY	CARBON STATE WYO.
QR. LOC. SEC. TWP. RGE.	SEC. 2029

HOLE NO. AM-364

DATE	2-16-77		
DEPTH DRILLER	820'	820'	
DEPTH LOGGER	820'	818'	
CASING DRILLER	6 5/8"	@ 40'	
CASING LOGGER	6 5/8"	@ 40'	
BOREHOLE FLUID	AIR & WATER		
RECORDED BY	C.H.		
WITNESSED BY	R.L.M.		

RUN NO.	BIT NO.	FROM	TO	FT. DRLD.
1	6 3/4"	SURF.	820'	820'

TYPE FLUID IN HOLE	AIR & WATER		
SOURCE OF SAMPLE			
RM @ MEAS. TEMP.		@	°F
RMF @ MEAS. TEMP.		@	°F
RMC @ MEAS. TEMP.		@	°F
SOURCE OF RMF & RMC			
RM @ BHT		@	°F
TIME SINCE CIRC.	12 HRS.		
MAX. REC. TEMP.	90°		
EQUIP. LOCATION	CASPER		
RECORDED BY	C.H.		
WITNESSED BY	R.L.M.		

RUN NO.	ONE
PASS NO.	ONE
TYPE LOG	G.R.
TYPE CONVEY.	CABLE
SCALE NO.	1"
LOGGING SPEED	30'
TIME CONSTANT	
SENSITIVITY	
LOG MEAS. FROM	GROUND
DRILLER'S DEPTH	820'
LOGGER'S DEPTH	818'
BTM. LOG INTERVAL	818'
TOP LOG INTERVAL	SURF.
CASING-LOGGER	40'
BIT SIZE & TO RUN	
TYPE FLUID	
REMARKS	

AM
364
2/2

PROJECT Anderson Mine — HOLE SIZE ____ ☐ AIR ☑ WATER — HOLE NO. AM 365

ELEVATION 1970 — NORTH 1,202,414.6 — EAST 641,002.3 — LOGGED BY C2H — DATE 1-4-77

SECTION 10 — TOWNSHIP ____ — RANGE ____ — T.D. ____ — P.D. ____

GEOPHYSICAL LOG	DEPTH	P	C	A	STRIP LOG	LITHOLOGY LOG
	0					
50'	20					
	40					
	60					
	80					
100'	100					
	20					Cgl Lt Tan, to Yel tan,
	40					
150'	60					
	80					
200'	200					
	20					Brn Tan, silty
250'	40					
	60					
	80					
300'	300					Sltst Grn to Brn Grn
	20					
	40					
350'	60					Marlst + Grn sltst, Marl. Wht, Thin bdd, Limy Red Brn Ghost
	80					Sltst, Grn
400'	00					Sltst, Grn w/ Carb Cem to Mdst, Sndy
	20					Sltst, Grn, Calcareous
	40					
450'	60					Sltst, Gry, Carbonaceous
	80					
	00					~ silicified Sltst Grn + DK Gry, Carb Cem

AM 365 2/2

PROJECT Anderson Mine — HOLE SIZE ____ ☐ AIR ☑ WATER — HOLE NO. AM 365

ELEVATION 1970 — NORTH 1,202,414.6 — EAST 641,002.3 — LOGGED BY C2H — DATE 1-4-77

SECTION 10 — TOWNSHIP ____ — RANGE ____ — T.D. ____ — P.D. ____

GEOPHYSICAL LOG	DEPTH	P	C	A	STRIP LOG	LITHOLOGY LOG
	500					~ silicified, Sltst, some Carb
550'	20					
	40					Sltst, Gry to Brn Bentonitic
	60					
	80					
	600					Red Sltst
	20					
	40					
	60					
	80					
	00					
	20					
	40					
	60					
	80					
	00					
	20					
	40					
	60					
	80					
	00					

MINERALS EXPLORATION CO.

CASPER, WYOMING

LOCATION	ANDERSON MINE
COUNTY	Uinta
STATE	WYO
SEC	10
TWP	
RGE	
LOG RUN	1-4-77
DEPTH DRILLER	600
DEPTH LOGGER	615
CASING DRILLER	8 5/8"
BTM LOGGED INTVL	615
TOP LOGGED INTVL	SURFACE
TYPE FLUID IN HOLE	AIR
SALINITY	
DENSITY	
LEVEL	
SOURCE OF SAMPLE	
RM @ MEAS TEMP	
RMF @ MEAS TEMP	
RMC @ MEAS TEMP	
SOURCE RMF & RMC	
RM @ BHT	
TIME CIRC	
MAX REC TEMP	
EQUIP LOCATION	
RECORDED BY	
WITNESSED BY	

BOREHOLE RECORD	
RUN NO.	ONE
BIT FROM	SURFACE
BIT TO	615'
TYPE FLUID IN HOLE	AIR
SALINITY	
DENSITY	
LEVEL	
MAX REC TEMP	
EQUIP LOCATION	
RECORDED BY	
WITNESSED BY	

CASING RECORD	
SIZE	8 5/8"
WGT/FT	24
GRADE	
FROM	SURFACE
TO	615'

BOREHOLE NO. AM-365

DIAMETER

1ST STAGE	12 1/4"	FROM	SURFACE
2ND STAGE		TO	615'
3RD STAGE			

REMARKS

CDN CALIPER RUN

AM 365 Page 1 of 2

PROJECT Anderson Mine HOLE SIZE ____ ☐ AIR ☑ WATER HOLE NO. AM 366

ELEVATION 1961 NORTH 1202, 202.2 EAST 641, 167.8 LOGGED BY CPH DATE 1-6-77

SECTION ____ TOWNSHIP ____ RANGE ____ T.D. ____ P.D. ____

GEOPHYSICAL LOG | DEPTH | P | C | A | STRIP LOG | LITHOLOGY LOG

- Cgl, Lav Brn, Slty
- Basalt, DK Gry to Blk
- Slty Cgl Red Bake Zone
- Cgl, Sndy, Yel Tan to Tan
- Sltst, Grn Tan
- Sltst, Yel Grn, Bentonitic
- LS, Marlst, Slic LS (Yel Tan), Grn Wht
- Sltst, Lt Grn, Sub Calc
- Sltst, DK Grn, Carbonaceous
- Interbed Grn Sltst + Brn Silicified Sltst
- Sltst, Grn
- Carbonaceous Sltst + Lignite, DK Grn to Blk
- Sltst, Grn

AM 366 1 of 2

PROJECT Anderson Mine HOLE SIZE ____ ☐ AIR ☑ WATER HOLE NO. AM 366

ELEVATION 1961 NORTH 1202, 202.2 EAST 641, 167.8 LOGGED BY CPH DATE 1-6-77

SECTION ____ TOWNSHIP ____ RANGE ____ T.D. ____ P.D. ____

GEOPHYSICAL LOG | DEPTH | P | C | A | STRIP LOG | LITHOLOGY LOG

- Carbonaceous Sltst + Lignite w/ Interbd Grn Sltst & Brn Tan Sltst
- Red Brn Chert
- Sltst Grn
- Sltst, Tan Grn
- Sltst, DK Grn
- SS, Crs, Biotite Com, Qtz Com
- Sltst, Grn, Yel orange staining
- SS, Tan Brn, Lim + Hem, Crs
- Sltst, Grn, Sndy
- Sltst, Red Brn
- SS, Crs, Lim + Hem Stain, Poor
- Carbonaceous Sltst
- SS, Crs, Lim Stain, Sorting Poor
- Carbonaceous Sltst + Lignite
- Sltst, Lt Grn
- Volcanics + Red Aglomerate
- Red Sltst + Volcanics

MINERALS EXPLORATION CO.

CASPER, WYOMING

LOCATION	ANDERSON MINE	HOLE NO.	AM-366
COUNTY	WASHAKIE STATE WYO.	CASING SIZE	2000-2002 FEET
SW 1/4 NE 1/4 SEC. 8 T. 45 N. R. 91 W. 6TH P.M.		CASING TYPE	Steel
		CASING	4.5"
		TUBE DIAMETER	3.28 o.d.in.
		TUBE GRADE	
		CASING WEL.	lb/ft
		COUPLER	
		DRILLING METHOD	
		CENTRALIZER	
		DRILLER	Andrews
		HELPER	Orange
		CEMENTATION	Gallons
		LAST LOG BY BOT.	
		FLUID LEVEL	
		REMARKS	

DRILLED	12-6-77				
DATE ISSUED	12-6-77				
CASING DRILLER	CASE				
CASING LOGGED	12-6-77				
BOTTOM LOGGED	2000				
HOLE DIAMETER	3 7/8 IN. TO 2,002'				
RUN NUMBER	ONE				
RUN NO.	ONE				
PASS NUMBER	ONE				
DIRECTION	IN				
LOG INTERVAL	2000'	1500'			
SCALE	1" = 100'	1" = 100'			
TOP LOG INTER.	2000'	1500'			
BOTTOM LOG INTER.	1500'	500'			
TYPE FLUID IN HOLE	AIR	AIR			
MAX. REC. TEMP.	90°F	90°F			
EQUIP. NO. & LOCATION	1300 CASPER	1300 CASPER			
RECORDED BY	C. HAMILTON	C. HAMILTON			
WITNESSED BY	C. PETERSON	C. PETERSON			

AM 366 2/2

PROJECT Anderson Mine HOLE SIZE ____ ☐ AIR ☑ WATER HOLE NO. AM367

ELEVATION 1929 NORTH 1,202,595.5 EAST 642,536.5 LOGGED BY CZH DATE 1-24-77

SECTION ____ TOWNSHIP ____ RANGE ____ T.D. 460 P.D. ____

GEOPHYSICAL LOG | DEPTH | P | C | A | STRIP LOG | LITHOLOGY LOG

Alluvium, Tan, Cgl

Cgl, V. Cvs, Tan

SS Cgl, Silty, Lt Tan to Brn

Siltst, Tan, Sndy

Siltst, Grn, Bentonitic, Silicified w/ thin Intbdd Calc Tuff, + Red Brn Chert, Calcareous

Siltst, Grn Bentonitic

Silicified Siltst, Grn w/ Intbdd wht Calc Tuff Calcareous, Brn + Brn Sub-Chert

Carbonaceous Siltst + Lignite, DK Gry to Blk Calc

Siltst DK Grn Sub Calc, Non Calc

Lignite + Lignite Siltst, Blk, Calc, Silicified

Carbonaceous siltst, Grn to DK Gry, Calc, Bentonitic

Siltst Tan

Siltst, Red Brn w/ Red Brn to Brn Volcanic Frags

2K = 200 CPS/IN TC1 5"/M

500 = 50 CPS/IN TC1 15"/M 100Ω

MINERALS EXPLORATION CO.

CASPER, WYOMING

LOCATION ANDERSEN MINE		HOLE NO.	AM 367
COUNTY YAVAPAI	STATE ARIZONA	GAMMA SCALE	500=50CPS/IN
GP. 1,202,595.5N-642,536.5E	ELEV. 1929	PROBE TYPE	SCINT.
SEC.	TWP. RGE.	K-FACTOR	5.70X10-5
DATE	1-24-77	DEAD TIME	7.1μs
DEPTH DRILLED	460	TIME CONSTANT	1
DEPTH LOGGED	460	PROBE DIA.	1 5/8
FOOTAGE LOGGED	417	CALIPER	
HOLE DIAMETER	5 5/8	DIRECTIONAL SURVEY	
WATER FACTOR	1.22	TEMPERATURE	
RESISTIVITY	100 OHMS/INCH	OPERATOR	KETCHLING
SELF POTENTIAL	M.V./IN.	DRILLER	JIM
RERUNS	1ST. RUN / 2ND. RUN / 3RD. RUN	CONTRACTOR	UNIVERSAL
BOTTOM	351	LAST A.E.C. PIT RUN	
TOP	334	FLUID LEVEL	
TOTAL FEET	17	REMARKS:	
SCALE RUN	2K=2000CPS/IN		

PROJECT Anderson Mine HOLE SIZE ____ ☐ AIR ☑ WATER HOLE NO. AM 368

ELEVATION 1916 NORTH 1,202,626.4 EAST 642,007.4 LOGGED BY CZH DATE 1-25-77

SECTION ____ TOWNSHIP ____ RANGE ____ T.D. 500 P.D. ____

DEPTH	P	C	A	STRIP LOG	LITHOLOGY LOG
20					
40					
60					SS, Lt Tan to Tan, Lower cgl + Slty
80					
00					
20					
40					
60					
80					Slt-st, Tan to Brn, Sndy
00					
20					
40					
60					
80					
00					Slt-st, Grn Tan, Lower Bentonitic + More Grn,
20					
40					Int'bdd Grn Silicified Slt-st + Wht Calcareous Tuff, Bentonitic
60					Slt-st, Grn, Bentonitic, Non-Calc
80					Carbonaceous slt-st + lignite, DK Gry to Blk, Calc
00					Calcareous Tuff, Pale Grn, Silicified
20					Carbonaceous Slt-st, DK Grn to Blk, Lignitic, Silicified Calc,
40					Slt-st, Grn, Bentonitic
60					SS, Med to Crs, w/ Grn Slt-st Int'bdd
80					Slt-st, Grn to DK Grn, Trace Carb, Non Calc to Sub Calc Bentonitic, Trace Silicification
00					Carbonaceous slt-st + Lignite DK Gry to Blk, Calc
					Slt-st Red w/ Andesitic Volcanic Frags

.50 .100 .150 .200 .250 .300 .350 .400 .450 498

SP + 500 CPS/IN TC1 5"/M

BK = 500 CPS/IN TC1 5"/M

500 = 50 CPS/IN TC1 15"/M 100Ω

MINERALS EXPLORATION CO.

CASPER, WYOMING HOLE NO. AM 368

LOCATION	ANDERSEN MINE.	GAMMA SCALE	500 = 50 CPS/IN
COUNTY	YAVAPAI STATE ARIZONA	PROBE TYPE	SCINT.
GP.	1,202,626.4N-642,007.4E ELEV. 1916	K-FACTOR	5.70 X 10-5
SEC.	TWP. RGE.	DEAD TIME	7.1 μsec
DATE	1-25-77	TIME CONSTANT	1
DEPTH DRILLED	500	PROBE DIA.	1 5/8
DEPTH LOGGED	498	CALIPER	
FOOTAGE LOGGED	532	DIRECTIONAL SURVEY	
HOLE DIAMETER	5 5/8	TEMPERATURE	
WATER FACTOR	1.22	OPERATOR	ROTH/LING
RESISTIVITY	100 OHMS/INCH	DRILLER	JIM
SELF POTENTIAL	M.V./IN.	CONTRACTOR	UNIVERSAL
RERUNS	1ST. RUN 2ND. RUN 3RD. RUN	LAST A.E.C. PIT RUN	
BOTTOM	413 373	FLUID LEVEL	
TOP	392 360	REMARKS:	
TOTAL FEET	21 13		

PROJECT Anderson Mine HOLE SIZE ____ ☐ AIR ☑ WATER HOLE NO. AM 369

ELEVATION 1984 NORTH 1,202,516.7 EAST 643,278.3 LOGGED BY CZH DATE 1-23-77

SECTION ____ TOWNSHIP ____ RANGE ____ T.D. 540 P.D. ____

GEOPHYSICAL LOG | DEPTH | P | C | A | STRIP LOG | LITHOLOGY LOG

Cgl, Sndy, Slty, Lt Tan to Tan, Granitic Frags

AM 369
1 of 2

V. Slty

SS, Cgl, Tan Brn Fine to Crs, Slty

Sltst, Sndy, Brn,

Sltst, Tan Grn, Bentonitic

Sltst, Grn, Bentonitic, Some Silicification, Gry Wisps

Calcareous Tuffy Dol Brn Chert Silicified

Sltst, Grn, Silicified, Bentonitic, Calc.

Calcareous Tuff, Gry Wht, Red Brn Chert

Carbonaceous Sltst, DK Gry to DK Gry, Calc Silicified, W/Thin Interbd Lignites

Sltst, Grn, Bentonitic, Sndy Trace Silicification Slab-Calc

PROJECT Anderson Mine HOLE SIZE ____ ☐ AIR ☑ WATER HOLE NO. AM 369

ELEVATION 1984 NORTH 1,202,516.7 EAST 643,278.3 LOGGED BY CZH DATE 1-23-77

SECTION ____ TOWNSHIP ____ RANGE ____ T.D. 540 P.D. ____

GEOPHYSICAL LOG | DEPTH | P | C | A | STRIP LOG | LITHOLOGY LOG

Sltst, Grn, Bentonitic, Sndy, Trace Silicification, Slab-Calc

Sltst, Brn, Sndy

Sltst, Grn, Bentonitic, Trace Carb

Sltst, Red, W/Andesitic Volcanic Frags

AM 369
2/2

MINERALS EXPLORATION CO.

CASPER, WYOMING

HOLE NO.	AM 369
LOCATION	ANDERSON MINE
COUNTY	YAVAPAI STATE ARIZONA
QD	1/4 SW 1/4 SW 1/4 SEC. 1984
ELEV.	1984
DATE STARTED	1-23-77
DATE COMPLETED	1-24-77
DRILLED FROM	SURFACE
DRILLED DEPTH	540
CASING DIAMETER	7 5/8
CASING DEPTH	100
CASING WEIGHT	
CASING TYPE	
CASING	
CEMENTING REPORT	
CEMENTED	
DRILLING METHOD	ROTARY
DRILLING CONTRACTOR	ROBERTS
CAP ABLE OF MIN. FLOW LEVEL	
REMARKS	

CASING RECORD	SIZE	WEIGHT	GRADE	DEPTH
CASING	7 5/8			100
CASING SHOE				
CASING PERF.				
CASING PERF.				
CASING PERF.

PROJECT Anderson Mine HOLE SIZE ____ ☐ AIR ☑ WATER HOLE NO. AM 370

ELEVATION 1916 NORTH 1,202,667.6 EAST 642,388.5 LOGGED BY CJH DATE 1-24-77

SECTION ____ TOWNSHIP ____ RANGE ____ T.D. 420 P.D. ____

GEOPHYSICAL LOG	DEPTH	P	C	A	STRIP LOG	LITHOLOGY LOG
	20					Cgl Lt Tan to Tan
	40					
-50-	60					SS, Grn Tan, Fine, Silty
	80					SS, Tan to Red Brn, Silty
-100-	100					
	20					Cgl, Tan Brn
	40					
-150-	60					
	80					Siltst, Sndy, Tan to Tan Brn
-200-	200					
	20					
-250-	40					Calc Siltst, + Calc Tuff, Pale Grn to Grn Wht, Silicified, w/ Yel Brn + Red Brn Chert Bentonitic
	60					
	80					Siltst, Grn, Bentonitic Non-Calc
-300-	300					Calc Tuff + Calc Siltst, Pale Grn, Calc, Trace Silic
	20					Carbonaceous Siltst, Gry, Calc
	40					Calc Tuff + Silicified Siltst, Pale Grn,
350	60					Siltst, Grn, Bentonitic Calc,
	80					Silicified Siltst, Grn, Calc
	400					Carbonaceous Siltst + Lignite DK Gry to Blk Calc, Silicified
-400-	20					Sub-Carbonaceous Siltst, DK Grn, Calc, Bentonitic
421'	40					Carbonaceous Siltst + Lignite, DK Gry to Blk, Calc
	60					
	80					Siltst, Red, W/ Andesitic Volcanic Frags
	500					
	20					
	40					
	60					
	80					
	600					

2K = 200 CPS/IN TC 1 6"/M

2K = 200 CPS/IN TC 1 5"/M

600 = 50 CPS/IN TC 1 15"/M

100 M

MINERALS EXPLORATION CO.

CASPER, WYOMING

LOCATION	ANDERSEN MINE	HOLE NO.	AM 370
COUNTY	YAVAPAI STATE ARIZONA	GAMMA SCALE	500 = 5000 CPS/IN
GP.	1,202,667.6N-642,388.5E ELEV. 1916	PROBE TYPE	SCINT.
SEC.	TWP. RGE.	K-FACTOR	5.70X10-5
DATE	1-24-77	DEAD TIME	7.14 M.
DEPTH DRILLED	420	TIME CONSTANT	1
DEPTH LOGGED	421	PROBE DIA.	1 5/8
FOOTAGE LOGGED	453	CALIPER	
HOLE DIAMETER	5 5/8	DIRECTIONAL SURVEY	
WATER FACTOR	1.22	TEMPERATURE	
RESISTIVITY	100 OHMS/INCH	OPERATOR	KETCHUM
SELF POTENTIAL	M.V./IN.	DRILLER	JIM
RERUNS	1ST. RUN / 2ND. RUN / 3RD. RUN	CONTRACTOR	UNIVERSAL
BOTTOM	355 / 295	LAST A.E.C. PIT RUN	
TOP	345 / 273	FLUID LEVEL	
TOTAL FEET	10 / 22	REMARKS:	