CONTACT INFORMATION
Mining Records Curator
Arizona Geological Survey
3550 N. Central Ave, 2nd floor
Phoenix, AZ, 85012
602-771-1601
http://www.azgs.az.gov
inquiries@azgs.az.gov

The following file is part of the Anderson Mine Collection

ACCESS STATEMENT

These digitized collections are accessible for purposes of education and research. We have indicated what we know about copyright and rights of privacy, publicity, or trademark. Due to the nature of archival collections, we are not always able to identify this information. We are eager to hear from any rights owners, so that we may obtain accurate information. Upon request, we will remove material from public view while we address a rights issue.

CONSTRAINTS STATEMENT

The Arizona Geological Survey does not claim to control all rights for all materials in its collection. These rights include, but are not limited to: copyright, privacy rights, and cultural protection rights. The User hereby assumes all responsibility for obtaining any rights to use the material in excess of "fair use."

The Survey makes no intellectual property claims to the products created by individual authors in the manuscript collections, except when the author deeded those rights to the Survey or when those authors were employed by the State of Arizona and created intellectual products as a function of their official duties. The Survey does maintain property rights to the physical and digital representations of the works.

QUALITY STATEMENT

The Arizona Geological Survey is not responsible for the accuracy of the records, information, or opinions that may be contained in the files. The Survey collects, catalogs, and archives data on mineral properties regardless of its views of the veracity or accuracy of those data.

Denver, Colo.

Minerals Exploration

4-2-78

Anderson Mine
Yavapai
Arizona

Anderson Mine
Yavapai
Arizona

4-2-78

Ground Level
275'

Mineral Logging Co.
M. Dodge
7750

225'
500 cps
60 cps

Trace used #3
Probe E-factor from B.D.A. Proj. 3-10-78 Serial #6
Rig: Universal (A)

SELF POTENTIAL

NATURAL GAMMA RAY COUNTS PER SECOND

DENSITY

RESISTANCE
OHMS

CONFI-LOG V2.5E4 DATE 04-02-78 HOLE #AM 924

GAMMA S.P. RES.

0 0 0

500 CPS

1000 CPS

500 CPS

10 MV/IN 10 OHMS/IN

GAMMA S.P. RES.

0 0 0

AM 924

MIKE DODGE

ORE GRADE CALCULATION

DEPTH SCALE = 5 FEET/INCH

536

95

I 2.0 FT / 0.309 X

I 4.0 FT / 0.618 X

I 0.5 FT / 0.049 X

I 0.5 FT / 0.103 X

I 2.0 FT / 0.927 X

CO 220

.01 $ HOW/INCH
CONVERGENCE FACTOR = 0.983

536

25

I 1.5 FT / 0.278 X

CO

80

.1 $ HOW/INCH
CONVERGENCE FACTOR = 0.976

MINERALS EXPLORATION CO.

CASPER, WYOMING

HOLE NO. AM 925

LOCATION	ANDERSON MINE
COUNTY	YAVAPAI STATE AZ
GP.	ELEV.
SEC.	TWP. RGE.
DATE	3-29-78
DEPTH DRILLED	235
DEPTH LOGGED	231
FOOTAGE LOGGED	
HOLE DIAMETER	5⅞
WATER FACTOR	—
RESISTIVITY	20 OHMS/INCH
SELF POTENTIAL	— M.V./IN.

	1ST. RUN	2ND. RUN	3RD. RUN
RERUNS			
BOTTOM	140	120	80
TOP	120	90	55
TOTAL FEET	20	30	25
SCALE RUN	2K	2K	2K

GAMMA SCALE	500=50CPI
PROBE TYPE	SCINT
K-FACTOR	6.00 E-5
DEAD TIME	9.2 mS
TIME CONSTANT	1
PROBE DIA.	1⅝
CALIPER	—
DIRECTIONAL SURVEY	—
TEMPERATURE	—
OPERATOR	ERICKSON
DRILLER	JIM
CONTRACTOR	HARRIS
LAST A.E.C. PIT RUN	2-24-78
FLUID LEVEL	201
REMARKS:	



RECORDEX CHARTS GRAPHIC CONTROLS CORPORATION BUFFALO, NEW YORK PRINTED IN U.S.A. No. 60-2333

Denver, Colo.

COMPANY: MINERALS EXPLORATION
WELL NAME: AM926
AREA: ANDERSON MINE
COUNTY: YAVAPAI
STATE: ARIZONA
ELEVATION: GROUND LEVEL

DATE: 4-1-78
SURVEY: ANDERSON MINE
COUNTY: YAVAPAI
STATE: ARIZONA
DATE: 4-1-78

AM926
195'
5 7/8"
MUD: LIGNOSULFONATE
MUD WEIGHT: 9.5
VISCOSITY: 40
FLUID LOSS: 10
RM @ MEAS. TEMP: .65 @ 1050
RMF @ MEAS. TEMP: .5 @ 1050
RMC @ MEAS. TEMP: 2.0 @ 1050
SOURCE OF SAMPLE: CIRCULATED
RM @ BHT: .5 @ 1050
TIME SINCE CIRCULATION: 16 HRS.
MAX. REC. TEMP.: 90°F
EQUIPMENT LOCATION: 7750
RECORDED BY: MDODGE
WITNESSED BY: MCCLELLAND, AZ.

TOTAL DEPTH: 196'
CASING DRILLER: 100'
CASING LOGGER: 100'
BOTTOM LOGGED INTERVAL: 196'
TOP LOGGED INTERVAL: SURFACE
TYPE FLUID IN HOLE: GEL-FOAM
SALINITY, PPM CL: 1000
DENSITY: 9.5
VISCOSITY: 40
PH: 10
FLUID LOSS: 10 ml
SOURCE OF SAMPLE: CIRCULATED
RM @ MEAS. TEMP: .65 @ 1050
RMF @ MEAS. TEMP: .5 @ 1050
RMC @ MEAS. TEMP: 2.0 @ 1050
RM @ BHT: .5 @ 1050
TIME SINCE CIRCULATION: 16 HRS.
MAX. REC. TEMP.: 90°F
EQUIPMENT LOCATION: 7750
RECORDED BY: MDODGE
WITNESSED BY: MCCLELLAND, AZ.

RUN NO.: ONE
DATE: 3-10-78
CASING DRILLER: 100'
CASING LOGGER: 100'
BOTTOM LOGGED INTERVAL: 196'
TOP LOGGED INTERVAL: SURFACE
TYPE FLUID IN HOLE: GEL-FOAM
SALINITY, PPM CL: 1000
DENSITY: 9.5
VISCOSITY: 40
PH: 10
FLUID LOSS: 10 ml
SOURCE OF SAMPLE: CIRCULATED
RM @ MEAS. TEMP: .65 @ 1050
RMF @ MEAS. TEMP: .5 @ 1050
RMC @ MEAS. TEMP: 2.0 @ 1050
RM @ BHT: .5 @ 1050
TIME SINCE CIRCULATION: 16 HRS.
MAX. REC. TEMP.: 90°F
EQUIPMENT LOCATION: 7750
RECORDED BY: MDODGE
WITNESSED BY: MCCLELLAND, AZ.

RUN NO.: ONE
DATE: 3-10-78
CASING DRILLER: 100'
CASING LOGGER: 100'
BOTTOM LOGGED INTERVAL: 196'
TOP LOGGED INTERVAL: SURFACE
TYPE FLUID IN HOLE: GEL-FOAM
SALINITY, PPM CL: 1000
DENSITY: 9.5
VISCOSITY: 40
PH: 10
FLUID LOSS: 10 ml
SOURCE OF SAMPLE: CIRCULATED
RM @ MEAS. TEMP: .65 @ 1050
RMF @ MEAS. TEMP: .5 @ 1050
RMC @ MEAS. TEMP: 2.0 @ 1050
RM @ BHT: .5 @ 1050
TIME SINCE CIRCULATION: 16 HRS.
MAX. REC. TEMP.: 90°F
EQUIPMENT LOCATION: 7750
RECORDED BY: MDODGE
WITNESSED BY: MCCLELLAND, AZ.

RUN NO.: ONE
DATE: 3-10-78
CASING DRILLER: 100'
CASING LOGGER: 100'
BOTTOM LOGGED INTERVAL: 196'
TOP LOGGED INTERVAL: SURFACE
TYPE FLUID IN HOLE: GEL-FOAM
SALINITY, PPM CL: 1000
DENSITY: 9.5
VISCOSITY: 40
PH: 10
FLUID LOSS: 10 ml
SOURCE OF SAMPLE: CIRCULATED
RM @ MEAS. TEMP: .65 @ 1050
RMF @ MEAS. TEMP: .5 @ 1050
RMC @ MEAS. TEMP: 2.0 @ 1050
RM @ BHT: .5 @ 1050
TIME SINCE CIRCULATION: 16 HRS.
MAX. REC. TEMP.: 90°F
EQUIPMENT LOCATION: 7750
RECORDED BY: MDODGE
WITNESSED BY: MCCLELLAND, AZ.

LOG TYPE: NAC SCINT. RAY/TEMP
LOG NO.: 196'
RUN NO.: ONE
DATE LOGGED: 3-10-78
CASING SIZE: 4 1/2"
CASING WT. & GRADE: 9.5#
CASING DEPTH: 196'
TYPE JOINTS: 30'
BIT SIZE: 4 3/4"
TYPE FLUID IN HOLE: GEL-FOAM
DENSITY: 9.5
VISCOSITY: 40
PH: 10
FLUID LOSS: 10 ml
SOURCE OF SAMPLE: CIRCULATED
RM @ MEAS. TEMP: .65 @ 1050
RMF @ MEAS. TEMP: .5 @ 1050
RMC @ MEAS. TEMP: 2.0 @ 1050
RM @ BHT: .5 @ 1050
TIME SINCE CIRCULATION: 16 HRS.
MAX. REC. TEMP.: 90°F
EQUIPMENT LOCATION: 7750
RECORDED BY: MDODGE
WITNESSED BY: MCCLELLAND, AZ.

TRACE USED: #3
PROBE K-FACTOR FROM E.R.D.A. Rpt 3-10-78: 5685×10⁻⁴
RIG: HARRIS (SIMMS)

SELF POTENTIAL
NATURAL GAMMA RAY COUNTS PER SECOND
DENSITY
RESISTANCE OHMS

COMPU-LOG V2.5L4 DATE 04-01-78 HOLE #AM 926

GAMMA S.P. RES.
0 0 0

0
50
100
150
196

500 CPS
10 MV/IN
10 OHMS/IN

GAMMA S.P. RES.
0 0 0

AM 926

MIKE DODGE

ORE GRADE CALCULATION
DEPTH SCALE = 5 FEET/INCH

155
X 0.5 FT / 0.031 X
CO
195
.01 X dW/dV/INCH
CONVERGENCE FACTOR = 0.976

55
X 0.5 FT / 0.036 X
X 1.0 FT / 0.048 X
X 0.5 FT / 0.033 X
X 0.5 FT / 0.031 X
X 1.0 FT / 0.068 X
CO
135
.01 X dW/dV/INCH
CONVERGENCE FACTOR = 0.981

25
X 2.0 FT / 0.045 X
CO
45
.01 X dW/dV/INCH
CONVERGENCE FACTOR = 0.981

Century Geophysical Corporation
Denver, Colo.

C-Sec-2 SP-731488

DATE 3-30-78
REC. BASE
COMPANY MINERALS EXPLORATION
BORE HOLE AM 927
AREA ANDERSON MINE
COUNTY YAVAPAI STATE ARIZONA
SECTION TOWNSHIP RANGE
INITIAL RUN
T.D. LOGGED 172'
GAMMA SCALE 500 cpm Per In.
TIME CONSTANT 60 Pu./Min.
CALIBRATION & PROBE DATA
SOURCE NO. 9655-23 PROBE NO. 179
DETECTOR NaI Scint. XTAL 7/8"x4" SHIELD .375" Pb
CALIB. 1.075 μ sec. WARM BACK 5.38×10⁻⁸
RES. SCALE 10 ohms per 1 Inches
S.P. 10 Mv/In.

DATE 3-30-78
REC. BASE
COMPANY ANDERSON MINE
CO. YAVAPAI
STATE ARIZONA
COMPANY MINERALS EXPLOR.
REC. 3-30-78
TOTAL FOOTAGE LOGGED 172'
GAMMA MEDIUM (Initial mix diffusion)
SCALE
SCALE
SCALE
T.C. Cps. Per In. LOGGING SPEED Ft./Min. Sec.
T.C. Cps. Per In. LOGGING SPEED Ft./Min. Sec.
T.C. Cps. Per In. LOGGING SPEED Ft./Min. Sec.
FROM Ft. TO Ft. TOTAL Ft.
FROM Ft. TO Ft. TOTAL Ft.
FROM Ft. TO Ft. TOTAL Ft.

BIT SIZE 5 7/8 CASING
SURF. CSG. SIZE H₂O + foam
DIAMETER PRODUCT
RESISTIVITY
OPERATED BY M. DODGE
MUD WT. 7750
LOCATION Wickenburg Az.
ELEV. KB 6.25 Ms. 1315
GRD. 0.25 Ms. 1345
LOGGED BY 8.5 Hrs.
TOTAL 1.0 Hrs.
RADIOACTIVE MATERIALS Mills
CALIBRATED STANDBY Hrs.

TRACK USED: #2
PROBE K-FACTOR FROM E.R.D.A. ON 3-10-78: 5.695×10⁻⁶
RIG: HARRIS (JIMMY)

SELF POTENTIAL
DENSITY
NATURAL GAMMA RAY COUNTS PER SECOND
RESISTANCE OHMS

COMPU-LOG V2.5L4 DATE 03-30-78 HOLE #AM 927

GAMMA S.P. RES.
0 0 0

2000 CPI

50

100

1000 CPI

150

500 CPI

10 MV/IN 172 10 OHMS/IN

GAMMA S.P. RES.
0 0 0

AM 927

MIKE DODGE

ORE GRADE CALCULATION
DEPTH SCALE = 5 FEET/INCH

125

2.5 FT / 0.056 %

11.0 FT / 0.057 %

160

.02 % eU/INCH
CONVERGENCE FACTOR = 0.975

Century Geophysical Corporation
Denver, Colo.

C-366-E SP 117488

DATE 4-1-78

COMPANY MINERALS EXPLORATION

BORE HOLE AM 928

AREA ANDERSON MINE

COUNTY YAVAPAI STATE ARIZONA

SECTION TOWNSHIP RANGE LOG MEASURED FROM GROUND LEVEL

HOLE NO. AM 928

SEC. TWP. RANGE

AREA ANDERSON MINE

COUNTY YAVAPAI

STATE ARIZONA

COMPANY MINERALS EXPLOR.

DATE 4-1-78

T.D. DRILLER 125' Ft.

BIT SIZE 5.1 In. CASING —

BORE HOLE FLUID H2O + FOAM

DENSITY VISCOSITY

RESISTIVITY

OPERATOR M. DODGE

UNIT NO. 7750

LOCATION WICKENBERG, AZ.

DATE 4-1-78 TIME ON 0.25 Hrs. 1545

STAND BY — Hrs. TIME OUT 1615

LOGGING 0.5 Hrs.

TOTAL 0.75 Hrs.

ROUNDTRIP MILEAGE Miles

CHARGEABLE STANDBY Hrs.

INITIAL RUN

T.D. LOGGED 125'

GAMMA SCALE = 500 Cps. Per In.

TIME CONSTANT LOGGING SPEED 60 Ft./Min.

CALIBRATION & PROBE DATA

SOURCE NO. SOURCE VALUE

PROBE NO. 9055-23 PROBE SIZE 1 7/8 In.

DETECTOR TYPE & SIZE NAI SCINT. XTAL 7/8"x4"

DEAD TIME 1.075 μSEC. K FACTOR 5.58×10⁻⁶

WATER FACTOR 1.135 AIR FACTOR

RES. SCALE 10 ohms per 1 Inches

S.P. 20 Mv/In.

GAMMA RERUNS (Initial run offscale)

SCALE = Cps. Per In.	SCALE = Cps. Per In.	SCALE = Cps. Per In.
T.C. Sec. LOGGING SPEED Ft./Min.	T.C. Sec. LOGGING SPEED Ft./Min.	T.C. Sec. LOGGING SPEED Ft./Min.
FROM Ft.	FROM Ft.	FROM Ft.
TO Ft.	TO Ft.	TO Ft.
TOTAL	TOTAL	TOTAL

TRACK USED: #2
PROBE K-FACTOR FROM E.R.D.A. PITS 3-10-78: 5.695×10⁻⁸
RIG: HARRIS (JIMMY)

SELF POTENTIAL

NATURAL GAMMA RAY COUNTS PER SECOND

DENSITY

RESISTANCE OHMS

COMPU-LOG V2.5L4 DATE 04-01-78 HOLE #AM 928

GAMMA S.P. RES.

0 0 0

1000 CPI

50

5000 CPI

100

500 CPI

20 MV/IN 125 10 OHMS/IN

GAMMA S.P. RES.

0 0 0

636

AM 928

MIKE DODGE

ORE GRADE CALCULATION

DEPTH SCALE = 5 FEET/INCH

65

2.5 FT / 0.109 ⁻

CO

95

.05 % eU₃O₈/INCH

CONVERGENCE FACTOR = 0.976

Century Geophysical Corporation
Denver, Colo.

C-340-E SP 101486

HOLE NO. AM929
SEC. TWP. RANGE
DATE 4-1-78
FIELD ANDERSON MINE
COUNTY YAVAPAI
STATE ARIZONA
COMPANY MINERALS EXPLORATION
OPERATOR M. DODGE
BORE HOLE AM929
AREA ANDERSON MINE
COUNTY YAVAPAI
STATE ARIZONA
DATE 4-1-78
SECTION TOWNSHIP RANGE
LOG MEASURED FROM GROUND LEVEL
TOTAL POSITION LOGGED 101'
LOCATION WICKENBERG, AZ

T.D. DRILLER 100'
T.D. LOGGER 101'
BIT SIZE 5 7/8 in.
CASING
BOREHOLE FLUID WATER
DENSITY
RESISTIVITY
VISCOSITY
SPONTANEOUS
RUN NO. 1
TIME 7750
LOGGED ft. 0.25 hrs. 1645
LOGGED ft. 0.25 hrs. 1715
LOGGED ft. 0.5 hrs.
TOOL ft. 1.0 hrs.
RECORDED MILEAGE miles
CREW NUMBER
STANDBY hrs.

TOTAL RUN
I.D. LOGGED 101'
GAMMA SCALE
TIME CONSTANT
CALIBRATION & PROBE DATA
SOURCE NO. SOURCE STRENGTH
PROBE NO. 9055-23 PROBE SIZE 1 7/8 in.
DETECTOR NAI SCINT. XTAL 7/8x4"
CALIBRATION FACTOR 1.0715 x SEC. AIR FACTOR 5.58 x 10^-4
WATER FACTOR 1.00
RES. SCALE 20 ohms per 1 inches
S.P. 20 Millivolts

GAMMA RANGES (initial run offscale)

SCALE	Cps. Per In.	T.C.	LOGGING SPEED Ft./Min.	Sec.
	500 Cps. Per In.			
	60 Ft./Min.			
FROM	ft.	TO	ft.	
TOTAL	ft.			

SCALE	Cps. Per In.	T.C.	LOGGING SPEED Ft./Min.	Sec.
FROM	ft.	TO	ft.	
TOTAL	ft.			

SCALE	Cps. Per In.	T.C.	LOGGING SPEED Ft./Min.	Sec.
FROM	ft.	TO	ft.	
TOTAL	ft.			

TRACK USED: #3
PROBE K-FACTOR FROM E.R.D.A. PITS 3-10-78: 5.695 x 10^-4
RIG: HARRIS (JIMMY)

SELF POTENTIAL
– 0 MV 0 +
NATURAL GAMMA RAY COUNTS PER SECOND
RESISTANCE OHMS

COMPU-LOG V2.5L4 DATE 04-01-78 HOLE #AM 929

GAMMA S.P. RES.
0 0 0
0
50
500 CPS
100
20 MV/IN 20 OHMS/IN
GAMMA S.P. RES.
0 0 0

AM 929
MIKE DODGE

ORE GRADE CALCULATION
DEPTH SCALE = 5 FEET/INCH
0
1.0 FT / 0.051 %
CO
55
.01 % U3O8/INCH
CONVERGENCE FACTOR = 0.976

MINERALS EXPLORATION CO.

CASPER, WYOMING

HOLE NO. AM 930

LOCATION	ANDERSON MINE
COUNTY	YAVAPAI STATE AZ
GP.	ELEV.
SEC.	TWP. RGE.
DATE	3-28-78
DEPTH DRILLED	85
DEPTH LOGGED	85
FOOTAGE LOGGED	
HOLE DIAMETER	6
WATER FACTOR	—
RESISTIVITY	— OHMS/INCH
SELF POTENTIAL	— M.V./IN.

RERUNS	1ST. RUN	2ND. RUN	3RD. RUN
BOTTOM	70		
TOP	55		
TOTAL FEET	15		
SCALE RUN	2k		

GAMMA SCALE	500=50CPI
PROBE TYPE	SCINT
K-FACTOR	6.00 E-5
DEAD TIME	9.2 μs
TIME CONSTANT	1
PROBE DIA.	1 5/8
CALIPER	—
DIRECTIONAL SURVEY	—
TEMPERATURE	—
OPERATOR	ERICKSON
DRILLER	DENNIS
CONTRACTOR	VENTURE
LAST A.E.C. PIT RUN	2-28-78
FLUID LEVEL	
REMARKS:	



PRINTED IN U.S.A.

No. 62-1333

RECORDING CHARTS GRAPHIC CONTROLS CORPORATION BUFFALO, NEW YORK

PRINTED IN U.S.A.

PROJECT Anderson Mine HOLE SIZE ____ ☑ AIR ☐ WATER HOLE NO. AM 924

ELEVATION ____ NORTH ____ EAST ____ LOGGED BY CBH DATE 4-2-78

SECTION ____ TOWNSHIP ____ RANGE ____ T.D. 250 P.D. ____



DEPTH	P	C	A	STRIP LOG	LITHOLOGY LOG
0					
20					Sltst Grn Intbd Wht calc Tuff
40					Wht Calc Tuff, Brn + Purple Brn chert
60					Sltst Grn
					Silicified Sltst Tan, Red Brn Mottled chert
					Sltst Grn
80					Wht calc Tuff
					Sltst Grn V Sndy Fine Fault Gouge?
					Wht calc Tuff
					Sltst Grn
100					Intbd Wht Calc Tuff and Grn Sltst
					Wht Calc Tuff
20					Sltst Grn
					Wht calc Tuff
					Sltst Grn, Silicified, Red Brn Chert
40					Sltst, Red Tan
60					Carbonaceous Sltst + Lignite, Gry to Blk
80					Silicified Sltst Gry Brn chert
200					SS, Silty, Fine, Yel Tan
20					
40					Sltst, Tan
					Sltst, Brn Tan
					~ Trace Red Sltst
60					
80					
00					
20					
40					
60					
80					
00					
20					
40					
60					
80					
00					

Century Geophysical Corporation, Tucson, Ariz.

Minerals Exploration

Anderson Mine, Yavapai, Arizona

Arizona

Ground Level

AM 924 | 4-2-78 | Anderson Mine | Yavapai | Arizona | Minerals Expl. | 4-2-78 | 225'

255' | 5.1 | Day | M. Dodge | 7750 | Wickenburg, AZ

225' | 500 | 60

0.75 - 1600 | 0.5 - 1645 | 0.75 | 1.5

Trace used: 3

Probe K-factor from E.R.D.A. Run 3-10-78: 5.685*10⁴

Right Universal (N)

PROJECT ANDERSON MINE HOLE SIZE ____ ☐ AIR ☑ WATER HOLE NO. AM 925

ELEVATION ____ NORTH ____ EAST ____ LOGGED BY K. TAYLOR DATE 3/29/78

SECTION ____ TOWNSHIP HARRIS ____ RANGE ____ T.D. 235 P.D. ____

GEOPHYSICAL LOG	DEPTH	P	C	A	STRIP LOG	LITHOLOGY LOG
50	0					interbd green, ss siliceous mudstn & white to lt green mudstn.
100	20					green mudstn.
150						interbd lt green to white mudst & green siliceous mudstn.
200	40					interbd red, green, lt green, white siliceous mudstn.
230	60					
	80					interbd green siliceous & red/orn cherty mudstn.
	100					lignite
						interbd lignite & dk grey mudst
						lignite
	20					interbd maroon & green siliceous mudstn.
	40					brown mudstn
	60					interbd brown, tan, yellowbrown, grey green mudstn.
	80					
	200					interbd brown & brownish green & greenish brown mudstn
	20					
	40					dk grey andesite
	60					
	80					
	00					
	20					
	40					
	60					
	80					
	00					
	20					
	40					
	60					
	80					
	00					
	20					
	40					
	60					
	80					
	00					

500-50 CPS TC 1

20 1/IN AM 925

MINERALS EXPLORATION CO.

CASPER, WYOMING HOLE NO. AM 925

LOCATION	ANDERSON MINE		
COUNTY	YAVAPAI STATE AZ		
OP.	ELEV.		
SEC.	TWP.	RGE.	
DATE	3-29-78		
DEPTH DRILLED	235		
DEPTH LOGGED	231		
FOOTAGE LOGGED			
HOLE DIAMETER	5 7/8		
WATER FACTOR	–		
DENSITY	20	CHANNEL	
MUD POTENTIAL	–	BY/MIN.	
CASING	NO. SIZE	WGT. PER	DEPTH
BOTTOM	140	120	80
TOP	120	90	55
TOTAL DEPTH	80	20	55
CASING SHOE	76	25	55

RECORDED TIME	500-50 CPS
LOGGED TYPE	SCINT
SCALE FACTOR	6.00 E-5
LOGGED TIME	9.7 mA
TIME CONSTANT	1
POWER SUP.	1 5/8
DENSITY	–
DIRECTIONAL DENSITY	–
TEMPERATURE	–
OPERATOR	E. GILLESPIE
LOGGED	3 min
CONTRACTOR	MASON
LAST LOG PD SIZE	2-24-78
FLUID LEVEL	201
REMARKS	

PROJECT ANDERSON MINE HOLE SIZE ☐ AIR ☐ WATER HOLE NO. AM 926

ELEVATION NORTH EAST LOGGED BY K. TAYLOR DATE 3/31/78

SECTION TOWNSHIP RANGE T.D. 190 P.D.

GEOPHYSICAL LOG	DEPTH	P	C	A	STRIP LOG	LITHOLOGY LOG
50	20					interbd green mudstn + red mudstn, some orange stain w/ Fe; some siliceous layers.
100	40					
150	60					interbd green mudstn + white (tuffaceous? calc?) mudstn.
	80					green siliceous mudstn, red mudstn, red chert
	100					interbd green mudstn + white (tuffaceous?) mudst.
						interbd green + red siliceous mudstn.
						interbd brownish red + green siliceous mudstn.
						green mudst, tan mudst.
	120					green + tan mudstn + lignite
	140					dk grey green, brown, greyish tan mudstns (carb?)
	160					brown, yellow brown, brownish green mudstns
	180					dk grey andesite frags.
	200					

500 CPS 10 MV/IN 196 10 OHMS/IN

GAMMA S.P. RES.

0 0

AM 926

MIKE DODGE

Century Geophysical Corporation, Denver, Colo.

4-1-78

MINERALS EXPLORATION

AM926

ANDERSON MINE

YAVAPAI ARIZONA

GROUND LEVEL

196'

500

60

9055-23 1M

NAI SCINT. XMLTR

.075 USEC. 5.58×10⁻⁶

1:15 1:00

AM926 — Anderson Mine — Yavapai — Arizona — 4-1-78 — 196'

195 — 5/8 — 11:01 AM

M. Dodge — 7750 — Wickenberg, Az.

0.5 — 0930 — 1.0 — 1000 — 0.5 — 2.0

TRACK USED: #3

PROBE K-FACTOR FROM E.R.D.A. Pm 3-10-78: 5.45×10⁻⁶

RIG: HARRIS (JIMMY)

PROJECT ANDERSON MINE HOLE SIZE ____ ☐ AIR ☑ WATER HOLE NO. AM 927

ELEVATION ____ NORTH ____ EAST ____ LOGGED BY K. TAYLOR DATE 3/30/78

SECTION ____ TOWNSHIP ____ RANGE ____ T.D. 175 P.D. ____

GEOPHYSICAL LOG	DEPTH	P	C	A	STRIP LOG	LITHOLOGY LOG
						lt brownish green mudstn interbd green, brown red mudstn. grey green siliceous mudstn. greenish tan mudstn.
	20					green mudstn.
	40					lt green to white mudstn.
						green siliceous mudstn.
	60					interbd green + red siliceous mudstn.
						green mudstn interbd green + red mudstn, siliceous
	80					interbd red + green mudst, orange staining, siliceous
						interbd red + green siliceous mudstn.
	100					
	20					
	40					green mudstn.
						brown, yellowbrown mudstn.
	60					
						red + green siliceous mudstn. grey andesite frags
	80					
	00					
	20					
	40					
	60					
	80					
	00					
	20					
	40					
	60					
	80					
	00					
	20					
	40					
	60					
	80					
	00					

2000 CPS
50
100
1000 CPS
150
500 CPS
172
30 MV/IN 30 OHMS/IN
GAMMA S.P. RES.
0 0

AM 927
MIKE DODGE

ORE GRADE CALCULATION
DEPTH SCALE = 5 FEET/INCH
125
2.5 FT / 0.05 IN
1.0 FT / 0.02 IN
160
.02 % eU3O8/INCH
CONVERGENCE FACTOR = 0.975



PROJECT ANDERSON MINE HOLE SIZE ☐ AIR ☐ WATER HOLE NO. AM928

ELEVATION NORTH EAST LOGGED BY K. TAYLOR DATE

SECTION TOWNSHIP RANGE T.D. 125 P.D.

GEOPHYSICAL LOG	DEPTH	P	C	A	STRIP LOG	LITHOLOGY LOG
	20					green mudstn.
	40					green to lt green siliceous mudstn.
						green mudstn
						green siliceous mudstn.
	60					green + red siliceous mudstn
	80					green siliceous mudstn.
						green siliceous mudstn, lt orange chert
						interbd green + red siliceous mudstn.
	100					brownish red mudstn.
						green to grey green siliceous mudstn
						green mudstn, orange Fe stain
	20					interbd green + tan mudstn
						green mudstn + dk grey andesite frags.
	40					
	60					
	80					
	00					
	20					
	40					
	60					
	80					
	00					
	20					
	40					
	60					
	80					
	00					
	20					
	40					
	60					
	80					
	00					
	20					
	40					
	60					
	80					
	00					



PROJECT ANDERSON MINE HOLE SIZE ____ ☐ AIR ☑ WATER HOLE NO. AM 929

ELEVATION ____ NORTH ____ EAST ____ LOGGED BY K. TAYLOR DATE 4/1/78

SECTION ____ TOWNSHIP ____ RANGE ____ T.D. 100' P.D. ____

GEOPHYSICAL LOG	DEPTH	P	C	A	STRIP LOG	LITHOLOGY LOG
	0					green siliceous mudstn.
	20					interbdd green siliceous & white tuffaceous(?) mudstn.
	40					green siliceous mudstn.
						green siliceous mudstn, lt orange chert
						green siliceous mudstone
						lt green to white & pink siliceous mudstn.
	60					grey green siliceous mudstn.
						green siliceous mudstn.
	80					interbd red & green mudstn
	00					dk grey andesite frags
	20					
	40					
	60					
	80					
	00					
	20					
	40					
	60					
	80					
	00					
	20					
	40					
	60					
	80					
	00					
	20					
	40					
	60					
	80					
	00					
	20					
	40					
	60					
	80					
	00					




PROJECT ANDERSON MINE
NORTH
EAST
RANGE
TOWNSHIP
SECTION
GEOPHYSICAL LOG
DEPTH PLOT
STRIP LOG
green to grey g
mudstone
grey green highly siliceous
dk grey, grey green tuffaceous
3 grey carbonate bing
0
20
40
60
80
00
20
40
60
80
00
20
40
60
80

PROJECT ANDERSON MINE HOLE SIZE ☐ AIR ☐ WATER HOLE NO. AM 930

ELEVATION NORTH EAST LOGGED BY K. TAYLOR DATE 3/27/78

SECTION ✓ TOWNSHIP RANGE T.D. 85 P.D.

GEOPHYSICAL LOG	DEPTH	P	C	A	STRIP LOG	LITHOLOGY LOG
	0					green to grey green to lt green, highly siliceous mudstone
	20					
	40					
	60					grey green highly siliceous mudstone
	80					lt grey to white (calc?), pinkish grey, grey green, siliceous mudstn.
	00					dk grey, grey green to brown mudstn.
	20					grey andesite frags
	40					
	60					
	80					
	00					
	20					
	40					
	60					
	80					
	00					
	20					
	40					
	60					
	80					
	00					
	20					
	40					
	60					
	80					
	00					
	20					
	40					
	60					
	80					
	00					

MINERALS EXPLORATION CO.

CASPER, WYOMING

HOLE NO. AM 930

LOCATION	ANDERSON MINE		500-50CPS
COUNTY	YAVAPAI STATE AZ.		SCINT
	SEC. TWP. RGE.		6 cm E-S
DATE	3-28-78		8.2 mA
DEPTH DRILLED	85		1
DEPTH LOGGED	84		1/4
FOOTAGE LOGGED			-
HOLE DIAMETER	6		-
CASING FROM	-		ERICKSON
CASING	-		DRAKE
RADIOACTIVITY	-		TAYLOR
SELF POTENTIAL	-		3-28-78
REMARKS	MIN. DEV. MAX. DEV. MAX. DEV.		
BOTTOM	70		
TOP	55		
TOTAL DEV.	15		
SCALE DEV.	24		