CONTACT INFORMATION
Mining Records Curator
Arizona Geological Survey
416 W. Congress St., Suite 100
Tucson, Arizona 85701
602-771-1601
http://www.azgs.az.gov
inquiries@azgs.az.gov

The following file is part of the JABA, Inc. Tombstone Mining Records

ACCESS STATEMENT

These digitized collections are accessible for purposes of education and research. We have indicated what we know about copyright and rights of privacy, publicity, or trademark. Due to the nature of archival collections, we are not always able to identify this information. We are eager to hear from any rights owners, so that we may obtain accurate information. Upon request, we will remove material from public view while we address a rights issue.

CONSTRAINTS STATEMENT

The Arizona Geological Survey does not claim to control all rights for all materials in its collection. These rights include, but are not limited to: copyright, privacy rights, and cultural protection rights. The User hereby assumes all responsibility for obtaining any rights to use the material in excess of "fair use."

The Survey makes no intellectual property claims to the products created by individual authors in the manuscript collections, except when the author deeded those rights to the Survey or when those authors were employed by the State of Arizona and created intellectual products as a function of their official duties. The Survey does maintain property rights to the physical and digital representations of the works.

QUALITY STATEMENT

The Arizona Geological Survey is not responsible for the accuracy of the records, information, or opinions that may be contained in the files. The Survey collects, catalogs, and archives data on mineral properties regardless of its views of the veracity or accuracy of those data.

Volume 5 ; Book 6 0072

TOMBSTONE

Mining District

Cochise County

ARIZONA

Charleston Drilling - #3
Hewitt Report 8/18/75

THE CHARLESTON MINE
Cochise County, Arizona

JAMES STEWART COMPANY
3033 North Central Avenue
Phoenix, Arizona 85012
(602) 264-2181

8/18/75

CHARLESTON MINE

Charleston, Arizona

INDEX

Hewitt Enterprises 12415 South 960 East Draper, Utah 84020 801 571-1911 Off. 801 571-0157 Res.

THE CHARLESTON MINE PROJECT DATA COMPELATION REPORT

August 10, 1970

The Charleston Mine area lies approximately six miles south west of Tombstone, Arizona. The property is reached by the Charleston highway.

In the Charleston Mine area a large zone of mineralization has been discovered. The zone appears to be at least two miles long and 3/4 mile wide. The estimated size of this zone of mineralization is based primarily on deep induced polarization prospecting. Three preliminary drill holes have tested this zone in the immediate vicinity of the old Charleston Lead Mine. All three holes have encountered ore grade mineralization of copper, lead, zinc and silver. These three holes have, in part, covered only a small area within the mineralized zone. A fourth hole, drilled off the mineralized zone, encountered very little mineralization.

The exploration done, to this date on the mineralized zone, suggests an economic mineral deposit to be present. The nature of the ore indicates the operation would be underground, generally along bedding planes. This, ofcourse, is only conjecture needing much better information for a basis of evaluation.

Since a large zone of mineralization appears to exist, it is a good possibility that the Charleston deposits are related to a mineralized intrusive monzonite porphyry similar to those of Bisbee, Mission, San Manuel, and others near by.

In conjunction with the deep mineralization found, the old Charleston Lead Mine itself should not be overlooked. The mineralization in the old Charleston Lead Mine appears to be unrelated to the deeper material. However, this may be due to a time factor and a long series of mineralization periods. The old Charleston Lead Mine may, at depths, contain sufficient reserves of Pb, Zn, Ag, and sericite to be of economic importance.

Further drilling of the mineralized zone is suggested, both to test the ore in the wide spaced holes 1, 2, and 4, and the general area. The drilling is by far the most important next step in exploration.

CLAIMS AREA

For the most part, the zone of mineralization is covered by mineral mining claims and state mineral leases. These properties are controlled by Horne Enterprises, 3033 North Central Avenue, Phoenix, Arizona.

GEOPHYSICS

Three phases of geophysical exploration were conducted in the Charleston area. Preliminary airborne magnetics covered the general area of interest. This was followed by very broad selected geochemical sampling and then induced polarization plus a small amount of ground magnetics.

AIRBORNE MAGNETICS

The general area covered by the magnetic survey is underlain by outcrops of different rock groups, which have a significant susceptibility difference. At the Schieffelin monument and

in the area surrounding, the Schieffelin granodiorite is exposed. Rock samples of this material are fairly magnetic. At the lower end of the Boquillas Land grant, on both sides of the San Pedro River, granodiorite similar to that at the Schieffelin monument is observed. Although in the Boquillas area the rock may be closer to monzonite and is more magnetic. North of the Charleston Mine many outcrops of the Uncle Sam porphyry are observed. This porphyry seems to be andesitic and is surprisingly non-magnetic. Southeast of the Charleston Mine and vicinity, rock outcrops are principally undifferentiated gray and white tuffs with sills and dikes of magnetic andesites and other basic flows. The tuffs are non-magnetic.

From the airborne magnetics the entire Tombstone district appears to be underlain by Schieffelin granodiorite. In most cases this intrusive lies at depths less than 1,000 feet. The intrusive lies as far westward as Section 39, Twp 20 S, R 22 E. A similar intrusive underlies the San Pedro River valley west of the surveyed area. Regional magnetics suggest the San Pedro River intrusive to be far larger in size than the Schieffelin granodiorite.

Between these intrusives lies the Charleston basin. Magnetically the rocks in this basin all appear to be similar. However, the surface geology suggests otherwise. With the abundance of magnetic andesite dikes and sills in the tuffaceous flows it would seem, if the vertical extent of this section were great, there would be some aggregate magnetic effect. Since this is not the case, two choices are possible: the tuffs are underlain at reasonably shallow depths by non-magnetic Uncle Sam porphyry or sediments. Our original interpretation was that sedimentary rocks

underlie the tuffs. This is borne out in drill holes 1, 2 & 4.

The Uncle Sam porphyry is found to be surprisingly uniform magnetically, almost as if it were a sediment rather than an intrusive sill or extrusive flow. This porphyry seems to have very little relationship to other igneous rocks in the area.

SURFACE MAGNETICS

Some of the igneous dikes, especially the andesite porphyries in drill holes 2 and 4, are altered and mineralized. Also they are fairly magnetic. Some surface profiles in the vicinity of the Charleston Mine indicate the possibility of an intrusive dike striking northeastward and paralleling the interpreted major mineralization zone along its north side. The significance of a porphyry mass in this area is not yet known. Additional information from further drilling will undoubtedly shed some light here.

SURFACE GEOLOGY

In the Charleston basin six geologic units may be observed.

1. Schieffelin granodiorite
2. Uncle Sam porphyry
3. Purple volcanics
4. White volcanic tuffs
5. Green to gray volcanics
6. Recent gravels and soils

1. The Schieffelin granodiorite mass underlying the Tombstone district and the San Pedro River valley is thought by this writer to be older than any of the other units observed, except for the cretaceous Bisbee formation. In the San Pedro River valley

the contacts with the volcanic series show the granodiorite to be much weathered before the deposition of the volcanics. It is believed this unit to be older than the volcanics or the Uncle Sam porphyry.

2. The Uncle Sam porphyry is reported to be of Miocene age and, as stated before, the true nature and age of this unit is not known. It is reported that this unit intrudes the white tuffaceous volcanics but this age relationship is doubted. The porphyry covers a large area to the north of Charleston.

3. The purple volcanics vary from purple tuffs to brown argillites and includes agglomerates with some porphyry fragments. In places these rocks appear to have intruded the white tuffs.

4. White volcanic tuffs cover a large portion of the mine area and southwestward. The rock appears to be bleached and altered along shear zones which strike N 45° E. The rock is very hard and a great amount of silica has been introduced.

5. The green to gray volcanics appear much the same as the purple volcanics and are very similar in mineral composition. They are probably the same unit with insufficient iron for a reddish or purple appearance.

SURFACE MINERALOGY

Numerous shears are noted in a zone one and a half miles wide and striking N 45° E, through the Charleston basin. These shears vary from bleached zones with kaolin and sericite to quartz manganese veins. Parallel to the Charleston highway is a shear zone nearly five miles long and 300 feet wide. This zone has much bleaching by hydrothermal solutions and numerous veinlets of

limonite after pyrite. In most places this zone carries very minor traces of copper, with the exception of the southwest end. On the southwest end of this zone quartz veins with minor copper silicates are present.

Near the central part of the suggested Charleston mineralized area, numerous quartz manganese veins are observed. These veins contain larger amounts of copper than the shear zones.

On the north edge of the outlined mineralized zone the Charleston Mine occupies a shear zone in the volcanics. The shear is noted by considerable sericite alteration containing galena, sphalerite and pyrite. This zone appears to be the only one in any way related to the deep mineralization, and that is questionable.

The only relationship of the surface mineralization to the deeper sulphides is that secondary hydrothermal solution from recent or post mineral faulting may have carried minor amounts of mineral through the overlying volcanics. This in part is the reason for giving emphasis to the deeper sulphide zone.

SURFACE GEOCHEMISTRY

In the Charleston basin numerous veins, shears, and altered zones are noted. The great majority of these zones strike N 45° E. As mentioned earlier, three types of mineralized shears are noted. It was felt that these zones, even though they appear to be post mineral, may contain secondary deposition of minerals, especially the quartz manganese veins. Rock sample tests of the three groups indicate anomalous amounts of copper, zinc, and silver in the quartz manganese veins. The mineralized shears with kaolin, limonite, and

bleaching contained the smallest amounts of these elements, only slightly above the fresher volcanic tuffs. These samples though inconclusive do aid in encouraging the possibility of ore mineralization in the underlying subsurface, outlined by the induced polarization.

INDUCED POLARIZATION

Initial tests made on the Charleston basin, using a Wenner configuration with a 1,000 foot electrode spread, indicated nothing of a polarizing nature at depths less than 1,000 feet. Later tests, using this same configuration, suggest that a shallow zone of mineralization exists in the eastern part of the area, Section 30, Twp 20 S, R 22 E. The depth to this zone is estimated to be approximately 185 feet.

With a modified 2 array (note fig. 1) electrode configuration, depth spacings of 3200 feet were attainable. This consisted of placing one current electrode at electrical infinity and the other at the depth station. A reference potential electrode was placed in the direction of the moving potential electrode at 6400 feet from the current energizing electrode. Resistivity and IP readings were made, out from the current electrode, between the reference pot and the moving potential electrode.

Expanders were made in four quadrants, in most cases, depending on accessibility. By doing a sufficient number of these expanders, data was deemed dense enough to contour. Data values were plotted half way between the current electrode and the moving potential electrode for any given depth separation. For example, the IP value would be 10 milliseconds at 1600 feet from the

8-10

Tom:
Here's who did the IP survey.
Bob

current center. This value was thus plotted at 800 feet in the direction of the reference pot. The data points were then contoured. Note that contours for 2000 and 3000 feet separations are enclosed. The 2000 and 3000 foot contour maps are from data using the modified 2 array configuration. The 1000 foot electrode separation contour map is based on data from Wenner array traverses as mentioned before. Several typical depth curves are enclosed.

Measurements were made using D.C. power-pulses of 4 seconds at 5 to 6 kw. A .35 second delay was used before an IP integration of 0.8 seconds took place. The D.C. pulse system is repetitious for several cycles to give a good repeatable impressed EMF and IP value. The Hewitt Enterprises system is comparable with the Newmont or Huntex methods.

The induced polarization results indicate that a buried polarizer lies beneath the volcanic cover in the Charleston area. The zone appears to be elongated in a northeast southwest direction, striking approximately N 45° E. It appears that this polarization represents sulphide mineralization, having a width of 3000 feet minimum and at least 2 miles in strike length. An average depth to sulphides is estimated at 1000 feet below the surface. From the results of DD#4 it appears that an average total sulphide percentage for the whole mineralized zone may be approximately 3%.

GEOLOGIC SECTION

The enclosed geologic section is based on drill holes 1, 2, 3, and 4. The principle rocks of the section are post mineral Bronco volcanics, the Bisbee formation sediments and the Uncle Sam porphyry. The contact between the post mineral volcanics and the

underlying sediments is noticeably a basal conglomerate. The Bisbee formation in this area consists of bands of quartzites, arkose, redbeds, argillites and silicified limestones. It is most difficult, if not impossible, to find a marker bed which is identifiable across any two drill holes. The section interpretation is based primarily on the predominance of redbeds or quartzite.

MINERALIZATION

Ore mineralization encountered in the drilling consists of, in order of importance, sphalerite, chalcopyrite, galena, and silver. The mineralization is generally associated with the more arkosic sections of the Bisbee formation. However, in many places mineralization occurs in an andesitic porphyry which seems to be abundant as narrow dikes and sills within the Bisbee formation. The stronger ore sections show considerable sericite and quartz alteration.

Mineralization appears to be disseminated along bedding in most cases, althougn sections of massive sulphide may form veins.

From the polished sections data enclosed in this report, it appears that several phases of mineralization occurred in this deposit. Pyrite and quartz seem to be the predominant minerals in several of these stages. The polished sample studies suggest the galena and sphalerite are closely associated. The chalcopyrite and silver also appear to be closely related. Since several stages of mineralization seem to be present in the deposit, economic importance may be considerably enhanced.

CONCLUSIONS

Several sections of mineable ore have been encountered in the drilling to date. The reader is referred to the enclosed assay summaries and drill hole logs for an evaluation of the drilling results. Even though many sections of ore grade material were encountered, it is difficult to relate ore in one hole to the next, because of the wide spaced drilling. However, sufficient mineralization has been found to warrant both the use of definitive drilling on shorter hole spacings and general exploration drilling.

It is important that a very minimum number of holes, within the suggested large mineralized area, have found economic mineralization. It is quite possible that this mineralization lies within the vicinity of a significant porphyry copper deposit.

The geologic environment appears to be favorable to economic mineralization. This, in conjunction with the wide zone of interpreted sulphide mineralization, encourages continued exploration and development. Those familiar with recent mineral discoveries in the southwest will realize that each of them were the result of exploration in situations such as this. We appraise this property to be worthy of a vigorous exploration program.

HEWITT ENTERPRISES

Loyd A. Hewitt



(TOMBSTONE)
3947 II NE
23
24
19
20
3505
26
3504
40'
25
30
TOMBSTONE 4.8 MI.
Charleston Lead Mine
35
31
3502
T. 20
T. 21



EXPLANATION

- Tombstone Mineral Reserve (lode and patent)
- Sierra Mineral Management (lode and patent)
- Horne-Stewart Company (lode and patent)
- Gallager Vanadium & Rare Minerals Corp. (lode and patent)
- Tenneco Land Grant
- State Mineral
- Withdrawal - Charleston dam & Military purposes

PROPERTY MAP
OF THE
CHARLESTON MINING DISTRICT

T. 20-21 S., R. 21-22 E.
COCHISE CO., ARIZONA

SCALE 1:48,000

JRK SEPT. 1973



DEPTH OF DIAMOND DRILL HOLES

•1	2107'	• CHS-1	4002'
•2	3212'	• CHS-2	5020'
•3	2617'	• CHS-3	3005'
•4	3310'		
•5	2528'		
•6	237'		
•7	3595'		
•8	872'		
•9	940'		

DRILL SITE OVER-LAY

18 AUG 75


R21E
R22E
HORNE GROUP
24
SRP
19
SML
FREZSH GROUP
25
L.P.N° 2
STEWART °2
STEWART °1
STEWART °5
STEWART °7
STEWART °6
MARY & GEORGE
STEWART °4
SML
30
APACHE GROUP
SML
36
1
6
5
4
T20S
T21S
CHARLESTON MINE





Fig. 1

Modified 2 array electrode configuration



AEROMAGNETIC SURVEY
TOMBSTONE-CHARLESTON AREA
COCHISE COUNTY, ARIZ.
1968
TOTAL INTENSITY
flight elevation - 1000' scale 1"=2000'
contour interval 75 gammas


DDH 5
Dump
Water
DDH 19
DDH 20
Landing
LEGEND
Uncle Sam Porphyry
Purple Tuff
Tuff (undifferentiated) White and Gray
Brown Tuff
Alluvium Gravel
CHARLESTON MINE ARE
ARIZONA, U.S.A
Scale 1"1000'



TOMBSTONE CHARLESTON

VERTICAL INTENSITY

MAGNETICS

16 MAY 70


14
13
18
17
23
24
19
25
30
31
E
A
C
Position of I.P. traverse lines
Wenner configuration
Centers of 2 array depth profiles & directions
1000' electrode separation contours



TOMBSTONE – CHARLESTON PROJECT
INDUCED POLARIZATION CONTOURS
"A" = 2000'
SCALE 1" = 1000'

TRUE NORTH
MAGNETIC

SCALE 1:24000
1 MILE
0 1000 2000 3000 4000 5000 6000 7000



TOMBSTONE – CHARLESTON PROJECT
INDUCED POLARIZATION CONTOURS
"A" = 5200'
SCALE 1" = 1000'

TRUE NORTH
GEODETIC

SCALE 1:24000
0 1 MILE
1000 0 1000 2000 3000 4000 5000 6000 7000
0


RESISTIVITY EAST
RESISTIVITY NORTH
RESISTIVITY SOUTH
MV SEC/VOLT
OHM FEET
LP EAST
LP NORTH
LP SOUTH
ELECTRODE SPACING
T.D. DEPTH PROFILE No. 1
TOMBSTONE CHARLESTON
PROJECT
TWO ARRAY
HEWITT ENTERPRISES
MAY 1965
LOGARITHMIC
2 X 3 CYCLES
KEUFFEL & ESSER CO.
47 7323






RESISTIVITY SOUTH
RESISTIVITY WEST
RESISTIVITY EAST
OHM FEET
I.P. WEST
I.P. SOUTH
I.P. EAST
MV SEC/VOLT
I.P. DEPTH PROFILE NO. 5
TOMBSTONE CHARLESTON
PROJECT
TWO ARRAY
HEWITT ENTERPRISES
MAY 1961
ELECTRODE SPACING













note - sedimentary section is based on the majority of that rock type found.

CHARLESTON MINE AREA

very generalized

Proposed section looking NE

scale 1" = 500'

Drill Hole No. 1 | Charleston Project | Page 1
Collar Elevation | Cochise County Arizona | By
Coordinates
Bearing | Scale
Depth | Started
Inclination 90° | Completed

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type

Alteration

	Sericite		Garnet
	Kaolin		Serpentine
	Silica		Biotite
	Chlorite		K Feldspar

0-14 No Core
14-148 Fragmental meta-andesite tuff. Hematite (earthy) clay, chlorite. Coarsely fragmental to 63, then tuff to 74, then coarsely fragmental to 148
148-152 Fault zone, gouge and breccia
152-153 Fragmental tuff
153-155 Fault zone, gouge and breccia
155-180 Weathered, bleached, clay-altered tuff.
180-223 Bleached white arg. alt. medium, fragmental tuff, heavily sericitized.

50
100
150
200
250

223-227 Gouge - fault zone
227-243 White arg. alt. tuff - sericitized
243-244 Gouge - fault zone
244-254 White arg. alt. tuff - sericitized

Drill Hole No. 1 | Charleston Project | Page 2
Collar Elevation | Cochise County Arizona | By
Coordinates
Bearing | Scale
Depth | Started
Inclination 90° | Completed

Alteration

Sericite	Garnet
Kaolin	Serpentine
Silica	Biotite
Chlorite	K Feldspar

Core Recovery | Alteration | Chalcopyrite | Sphalerite | Galena | Ag | Pyrite | Rock Type

254-257 Gouge - fault zone
257-303.6 Graywacke, silicified, mosaic appearance, reddish. (Might be a silicified tuff) Scattered pyrite cubes. Grades to fine gray siltstone. Pyrite on seams <1%.
303.6-328.5 Gouge and breccia, heavily sericitized (313)
328.5-340 Fine siltstone, thoroughly bleached, pyritized (2-3% py), sericitized, to 340.
300
340-342.5 Gouge

342.5-400 Fine light grey to white siltstone, considerable fine qtz., sericitized. At 366, ¼" sphalerite - chalcopyrite veinlet. Pyrite 1-3%, locally up to 10%. Rock thoroughly sericitized adjacent to veinlet. Locally abundant (up to 5%) chalcopyrite. (See specimen at 371. Nx core to 400)
350

400-474 Fine granular siltstone, grey, 2-6% pyrite, very little cpy (< 0.2%) at 430, ¼" vein calcite, siderite, galena, chalcopyrite. At 440, 1" vein same.
400

474-476 Fault, gouge
450 476-525 Fine granular siltstone, pyritized (2-6% py), fragmental from 477-1/2-479, then finer grained, light grey. Two or three 1/8" vlts 482-485, sphalerite, galena, cpy. Pyrite up to 10% locally. 6" epidote zone with fine galena, sphalerite, pyrite, tetrahedrite?, 518. Several small (1/16"-1/8") vlts sphalerite. Galena with epidote to 525. Pyrite 2-6%, other
500

Drill Hole No. 1 | Charleston Project | Page 3
Collar Elevation | Cochise County Arizona | By
Coordinates
Bearing | Scale
Depth | Started
Inclination 90° | Completed

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type

Alteration

	Sericite		Garnet
	Kaolin		Serpentine
	Silica		Biotite
	Chlorite		K Feldspar

sulfides <0.1% in interval.

525-573 Conglomerate, 531-1/2-536, py - 2-6%, then fine light gray siltstone, 2-6% py calcite streaks 570-1/2-573. Sericitized.

573-674 Fault, Gouge

550

574-582 Fine gray siltstone, 2-6% pyrite. Sericitized.

582-584 Fault, gouge

584-586 Greenish gray fine siltstone, 1-2% py, becomes fine quartzite at 586.

586-649 Fine quartzite, grades to 1mm qtz locally, vuggy after 630, some py in vugs and on seams, (< 2% py)

600

649-665 Quartzite, 1mm, vuggy in part.

665-671 Fine grained impure qtz, locally with a streak or two of sphalerite, 1-2% py, <0.1% sph.

650

671-676.4 No core

676.4-705 Fine grained impure qtz, grades to 1mm at 679.5, vuggy, continues to 705

700

705-724 Qtz, 1mm, but with pyrite on seams, bulk 5-8% py, to 724

724-769 Bedding at 724, 75° to axis. Fine grained siltstone, light grey, 1-2% py. Becomes gray banded after 750, some what softer.

750

Drill Hole No. 1 | Charleston Project | Page 4
Collar Elevation | Cochise County Arizona | By
Coordinates
Bearing | Scale
Depth | Started
Inclination 90° | Completed

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type

Alteration

	Sericite		Garnet
	Kaolin		Serpentine
	Silica		Biotite
	Chlorite		K Feldspar

769-818 Fragmental (conglomerate) for about 2 feet, then splotchy, local development lime silicates. Gray siltstone with local fragmental horizon, emphasized by epidote splotches, locally fine quartzite for 5-6' intervals to 818.

800 818-824 At 818, bedding at 50° to axis. Fine banded greenish-grey siltstone (epidote and calcite)

824-824.5 Several 1/8" vlts sphalerite and galena

824.5-860 Fine green-grey siltstone, splotchy with epidote, becoming drably uniform after 842-855, then aplotchy.

850

860-886.4 Porphyry, first 18" qtz free. Altered, probably qtz monz.? Pyritized, argillic - sericite to fault at 886.4.

886.4-934 Brecciated (healed) siltstone to 892, then fine gray siltstone, becoming darker grey with depth. Some dark epidote?

900

934-971.5 Dark grey siltstone, mottled (fine mottling) to 955.5, then fine dark gray siltstone to 971.5

950

971.5-974 24" carbonate vein (not calcite), ankerite or siderite

974-1004.3 Dark grey massive siltstone grades into fine-grained arkose.

1000

Drill Hole No. 1 | Charleston Project | Page 5
Collar Elevation | Cochise County Arizona | By
Coordinates
Bearing
Depth
Inclination 90°
Scale
Started
Completed

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type

Alteration

Sericite		Garnet	
Kaolin		Serpentine	
Silica		Biotite	
Chlorite		K Feldspar	

1004.3-1106 At 1056, bedding 55° to axis. Becomes somewhat darker after 1080.

1050

1100 1106-1162.3 Fine grained, nearly quartzite, grey, gradually becomes coarser (about 1mm) at 1117. Stays coarse to 1141, then grades into finer at 1153. Fine arkosic qtz. - medium gray.

1150

1162.3-1178 Arkose, fine grained. Sericitized. Becomes fine grained at 1178.

1178-1248 Grades back into fine grained arkose after 1186. Two or three calcite bands 1207-1208. Mottled locally. 6" healed breccia at 1247.5, then porphyry.

1200

1248-1261 Meta-andesite porphyry

1250

Drill Hole No. 1
Collar Elevation
Coordinates
Bearing
Depth
Inclination 90°

Charleston Project
Cochise County Arizona

Scale
Started
Completed

By

Core Recovery | Alteration | Chalcopyrite | Sphalerite | Galena | Ag | Pyrite | Rock Type

Alteration

Sericite		Garnet	
Kaolin		Serpentine	
Silica		Biotite	
Chlorite		K Feldspar	

1261-1262 8" fault gouge

1262-1320.5 Fine massive grey granular siltstone, mottled with epidote; locally impure quartzite (hard). Becomes darker grey after 1286 to purple, 1290-1291, then 16" lime silicates to 1289.5, then purplish siltstone to 1299, then light grey grading back to purple at 1316, then grey, quartzite.

1300

1320.5-1350.5 Fine grained light grey siltstone, 1% py, some mottling, becoming medium grey with considerable mottling 1330-1336, then lighter grey with epidote patches and blobs, becoming less splotchy after 1337. Splotches end at 1350.5

1350

1350.5-1367 Fine granular impure quartzite. Grades from medium light to medium grey at 1367

1367-1482.5 Banded siltstone, some epidote banding, purplish at 1367, becomes gray and mottled, then finely mottled 1378 to 1385. Fine grained grey quartzite (impure).

1400

1482.5-1585 Fine grained light gray qtz/ (impure). Some epidote veinlets, sphalerite (¼" vein) at 1490. Grey to 1496, then mottled, fragmental looking to 1503. Fine grained grainy-looking to 1511. Fragmental to 1514, then fine grained, meta-arkose, fragmental 1524-1525. Fine grained light

1450

colored quartzite 1525-1566. 12" breccia 1566-1567 (healed). Fragmental light colored impure fine grained qtz to 1574.5

1500

Drill Hole 1 — Charleston — Project — Page 7
Collar Elevation — Cochise — County Arizona — By
Coordinates
Bearing — Scale
Depth — Started
Inclination 90° — Completed

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type

Alteration

	Sericite		Garnet
	Kaolin		Serpentine
	Silica		Biotite
	Chlorite	KK	K Feldspar

1550

1585-1606 Meta-andesite-silicified.

1600

1606-1616 Mixed-meta-andesite.
1616-1630 Mixed-meta-andesite, quartzite (impure)
1630-1650 Mottled meta-arkose-fine

1650 1650-1678 Siltstone, splotchy, grey, grades to light grey at 1657. Fragmental 1662-1664. Purplish 1666-1676.5, bedding 60° to axis, contact 1678
1678-1698 Meta-andesite porphyry, several mixed zones.
1698-1746 Siltstone, purplish, to 1722, 18" fine qtz., then purplish siltstone, gradually grading to more qtz. material.

1700

1746-1757 Siltstone, fragmental (conglomerate)

1750

Drill Hole No. 1
Collar Elevation
Coordinates
Bearing
Depth
Inclination 90°

Charleston Project
Cochise County Arizona

Scale
Started
Completed

Page
By

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type

Alteration

	Sericite
	Kaolin
	Silica
	Chlorite

	Garnet
	Serpentine
	Biotite
	K Feldspar

1757–1810 Siltstone, becomes quartzitic at 1763. Fine grained impure light grey qtz.

1800

1810–1818 Fragmental siltstone (conglomerate)

1818–1951 Light gray impure siltstone (fine qtz.), fragmental intervals, grades to 1mm qtz. at 1905, 2' basal arkose 1949–51.

1850

1900

1950

1951–1954 Light colored grey siltstone
1954– 1981 Quartz latite?
1981–1998 Meta-arkose-conglomerate

2000

Drill Hole 1 | Charleston Project | Page 9
Collar Elevation | Cochise County Arizona | By
Coordinates
Bearing | Scale
Depth | Started
Inclination 90° | Completed

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type

Alteration

	Sericite		Garnet
	Kaolin		Serpentine
	Silica		Biotite
	Chlorite		K Feldspar

1998-2050 Fine grained siltstone to 2007, then 1mm qtz. to 2012, 6" cong., then arkosix qtz. (medium grained, grey) gradually becoming darker grey, more silty to 2050.

2050 2050-2103 Purplish siltstone, fragmental 2061-2068, then grey qtz. siltstone, medium grained, splotchy, to bottom. 2103

2100

2150

2200

2250

Drill Hole No. 2
Collar Elevation
Coordinates
Bearing
Depth
Inclination 90°

Charleston Project
Cochise County Arizona

Scale
Started
Completed

Page 1
By

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type

Alteration

Sericite	Garnet
Kaolin	Serpentine
Silica	Biotite
Chlorite	K Feldspar

0-10 No Core

10-248 Weathered meta-andesite tuff. Fragmental to 123, then fine. At 151, 4" breccia. Fragmental interval 165-168. At 181 - bedding 30° to axis. To 189.5, fragmental to 197. Bedding at 199-65°. Fine to 209, fragmental to 248.

50

100

150

200

248-394 Fine to 262, fragmental to 270, fine and fragmental mixed to 278. Tuff to 323. Fragmental 323-327, fine to 329, fragmental to 394.

250

Drill Hole No. 2
Collar Elevation
Coordinates
Bearing
Depth
Inclination 90°

Charleston Project
Cochise County Arizona

Scale
Started
Completed

Page
By

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type

Alteration

Sericite	Garnet
Kaolin	Serpentine
Silica	Biotite
Chlorite	K Feldspar

300

350

394-506 Meta-andesite tuff-coarsely fragmental, bedding at 442 50° to asix to 437.5, bedded tuff to 453, then fragmental to 506.

400

450

500

Drill Hole No. 2
Collar Elevation
Coordinates
Bearing
Depth
Inclination 90°

Charleston Project
Cochise County Arizona

Scale
Started
Completed

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type

Alteration

	Sericite
	Kaolin
	Silica
	Chlorite

	Garnet
	Serpentine
	Biotite
	K Feldspar

506-534 Meta-andesite tuff - fragmental in part to 527, strongly fragmental to 534.
534-537 Meta-andesite, bleached, some sericite, fault zone at 536.
537-566 Meta-andesite tuff to 566.
550
566-567.5 Gouge and breccia - fault zone.
567.5-577.5 Fine grained meta-andesite tuff.
577.5-578.5 Gouge and breccia - fault zone.
578.5-582 Fine grained meta-andesite tuff.
582-591 Fragmental meta-andesite tuff.
591-598 Bleached meta-andesite sericite, specks of galena, some
600 silicification, argillic alt. FeOx stain.
598-603 Crushed zone, clay, sericite.
603-604 Bleached meta-andesite.
604-605 Fault Zone.
605-623 Crushed and broken zone, bleached meta-andesite tuff 40° dip to axis (fault).
650
623-628 Bleached meta-andesite.
628-675.5 Sericitized meta-andesite tuff, grading downward to shloritic meta-andesite tuff.
675.5-699.5 Andesite tuff (?)
699.5-737.5 Meta-andesite tuff (see specimen at 706.5) dark gray, fine grained, feldspars altered, ferromags altered to
700 chlorite, could also be a meta-volcanic tuff. Splotches of epidote. Epidote bands may reflect bedding? (40° to core) On the whole, prefer to consider this a tuff. Some fine pyrite with epidote. Small fault, 4" gouge and breccia at 724.
750
737.5-761 12" gouge, fault at 30° to axis of core. Meta-andesite tuff, intercalated bands fine grained medium gray siltstone

Drill Hole No. 2 | Charleston Project | Page 4
Collar Elevation | Cochise County Arizona | By
Coordinates
Bearing | Scale
Depth | Started
Inclination 90° | Completed

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type

Alteration

	Sericite		Garnet
	Kaolin		Serpentine
	Silica		Biotite
	Chlorite		K Feldspar

after 741. Crushed zone, 760-761, thereafter gray siltstone.

761-770 Arkose, granular nondescript, specked with fine pyrite cubes. Sercite

770-781 Coarse conglomeratic arkose to 779.5, fine grained light gray siltstone to fault at 781. Bedding at 85° to axis.

800

781-783 Gouge and breccia, some fine pyrite.

783-912 Quartzite, light grey, medium grained, sericite. Becomes fine grained after 869 to 877.5, then medium again to 912. At 911, bedding 56° to axis.

850

900

912-1005 Fine grained gray siltstone

1005-1007 Fine grained quartzite with sphalerite, galena, and pyrite, about 5% total sulfide.

1007-1015 Quartzite, medium grained, light grey

1015-1052 Siltstone, some fine qtz (1/16" veins sphalerite 1019-1020) to pyrite veinlets to 1028, then two or three 1/8" sphalerite veinlets. Siltstone to 1031.5. Quartzite with two or three 1/16" sphalerite veinlets to 1034, then darker gray fine grained siltstone, becoming lighter to 1039, medium grained arkosic qtz. after 1039 to fault zone 1052-1056.

950

1000

Drill Hole No. 2
Collar Elevation
Coordinates
Bearing
Depth
Inclination 90°

Charleston Project
Cochise County Arizona

Scale
Started
Completed

Page
By

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type



Alteration

Sericite			Garnet	
Kaolin			Serpentine	
Silica			Biotite	
Chlorite			K Feldspar	

1052-1056 Fault zone

1050

1056-1094 Arkose, in part conglomeratic with pebbles up to 3/8" to 1070, then pebbles become larger to base at 1094.

1094-1102 Fine grained gray arkosic siltstone, locally medium grained quartzitic. 1/8" band pyrite and sphalerite at 1099. Fine grained to 1102.

1100 1102-1118 Meta-andesite (?) dike. Thoroughly altered prophyritic dike. Chilled border about 18" 1102-1104, then stony groundmass, epidote alt. of feldspars, chlorite. At contact at 1118, 2' mixed rock, contact irregular, welded at 30° to axis.

1118-1173 Fine grained gray arkosic rock grades into gray quartzite. An occasional 1/16 vlt of sphalerite and pyrite. Total sulfide per any 10' int. < 0.1%

1150

1173-1187 Changes from grey to light grey at 1173-1175, then conglomeratic and somewhat mineralized from 1175-1187. Vuggy, some calcite, sphalerite, galena. Perhaps 2-4% total sulfide.

1200 1187-1196.5 Fine grained silicitized arkose

1196.5-1202 Sericitized arkose (?) speckled with galena, pyrite, and sphalerite, total sulfides about 4-6% to 1200.

1202-1249 Quartzite, fine grained, light gray, grades to medium grained.

1250

Drill Hole No. 2 | Charleston Project | Page 6
Collar Elevation | Cochise County Arizona | By
Coordinates
Bearing | Scale
Depth | Started
Inclination 90° | Completed

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type

Alteration

	Sericite		Garnet
	Kaolin		Serpentine
	Silica		Biotite
	Chlorite		K Feldspar

1249-1280 Fine grained light gray arkose-has stony look, not much quartz. Beddings locally present, one at 1262.5 40° to axis. Rock becomes mottled 1270.5-1275, then gray granular (about 1mm), grading into quartzite at 1280.

1280-1330 Quartzite to 1281, then back to granular gray arkose, as above, rock gradually becoming more quartzitic, fair qtz. after 1301.

1300

1330-1363 Arkose, dense granular to 1332, then fine grained siltstone with minor sulfide on bedding (less than 1$ sulfide), to 1334. Quartzitic arkose to 1347.5, then gray granular arkose to 1349.5, then quartz-ark. to 1363.

1350 1363-1368.6 Fine grained gray siltstone.

1368.6-1395 Quartzite with sericite, occasional grain of galena or pyrite. At 1397, 10" altered (bleached) shale and qtz. bedding 45° to axis.

1395-1410 Disseminated sulfides in qtz. after 1397. ½" py vein at 1401, 25° to asix, 1% total sulfides to 1405, then 5% > to 1406.5 then 1% again. Sulfides are galena, sphalerite, minor cpy and pyrite. Sulfide content drops to much less than 1% with rock change (1410)

1400

1410-1416 Dense greenish massive lime silicate rock (diopside?) specimen at 1409-Possible fault at 1416-no gouge but badly broken core.

1450 1416-1457.5 Dense light gray fine grained quartzite. Minor py on seams 1% sulfide. Quartzite gradually becomes coarser, about 1mm at 1454, sulfide content picks up to 2-3%, mostly galena and sphalerite for interval 1454-1457.5

1457.5-1477 Dense light gray fine grained quartzite (sericitized At 1477, bedding plane 50° to core. Sulfide < 1%.

1500

Drill Hole No. 2
Collar Elevation
Coordinates
Bearing
Depth
Inclination 90°

Charleston Project
Cochise County Arizona

Scale
Started
Completed

Page
By

Core Recovery | Alteration | Chalcopyrite | Sphalerite | Galena | Ag | Pyrite | Rock Type

Alteration

	Sericite		Garnet
	Kaolin		Serpentine
	Silica		Biotite
	Chlorite	K	K Feldspar

1477-1512 Quartzite-medium grained (less than 1lm but granular) Sulfide < 1%.
1512-1518.5 Fault zone, minor gouge, poor core
1518.5-1532 Quartzite, somewhat silicified.
1532-1533.6 12" heavy pyrite
1550 1533.6-1543 Quartzite, about 1mm, broken
1543-1546 Gouge and breccia - barren
1546-1594 Purplish siltstone to 1549, then bleaching to gray with lime silicate spots, grading to quartzite at 1552. (Fine grained-gray)
1594-1625 Gray siltstone, scattered blebs of py, changing color
1600 to lt gy and from siltstone to fine qtz with lime silicate streaks at 1601
1625-1727 Dense gy silicified siltstone, blobs of lime silicate minerals, some scattered py, still much less than 1% sulfide This silicified siltstone has a porphyritic look with the quartz grains separate in a dense stony groundmass. Siltstone persists to 1725, then changes to medium grained quartzite, to
1650
1700
1727-1733.5 1-2mm quartzite-sericite, from 1-5% total sulfides, sphalerite, cpy, py, minor galena.
1733.5 6" fault gouge
1733.5-1820 Quartzite, dense, fine grained, py cubes, less than
1750 1% sulfide. Changes from gray to reddish, becoming purplish

Drill Hole No. 2 | Charleston Project | Page 8
Collar Elevation | Cochise County Arizona | By
Coordinates
Bearing | Scale
Depth | Started
Inclination 90° | Completed

Core Recovery | Alteration | Chalcopyrite | Sphalerite | Galena | Ag | Pyrite | Rock Type

Alteration

Sericite		Garnet	
Kaolin		Serpentine	
Silica		Biotite	
Chlorite		K Feldspar	

siltstone at 1748. Purplish siltstone to 1759, then back to dense, fine to coarse cubic pyrite. Minor lime silicate veining. Gray to 1803 then purplish to 1811, then gray as above. Somewhat coarser 1813-1818, denser 1818-1820

1800

1820-1852 Siltstone, dark gray 1820-1831, then light gray 1831-1837, 1mm quartzite 1837-1839, then purple siltstone followed by dull stony quartzite(?) at 1843 - granular. (probably lime silicates) to 1850, then fine grained siltstone to 1852

1850

1852-1853 Arkose? with sphalerite and cpy < 15% sulfides
1853-1923 Quartzite, 1-2mm, becoming finer grained, more stony looking. Minor sphalerite-galena, up to 5% for 4" interval, otherwise negligible (less than 1%). Fine grained gray qtz to 1865, then purplish siltstone to 1875. Lighter colored to 1878.5, then purplish again to 1892. Dense light gray 1892-1897.5, purplish to 1901. Lime silicates vlt at 1901 ($\frac{1}{2}$", 5% sulfide, mostly sphalerite). Fine grained light gy to 1905.5, becomes granular (fine) more quartzitic to 1923.

1900

1923-1924 Arkose, heavy sphalerite, galena. About 10% Z, 3% lead 15-20% total sulfide.
1924-1935 Quartzite with less than 1% sulfide to 1925, then purplish siltstone, becoming dark gray at 1927, then light greenish gray lime silicates with minor py (2% sulfides) to 1928.5. Dark gray siltstone grading to purple siltstone, then to greenish dense lime silicates to 1935.

1950

1935-2002.3 Dense, fine gray siltstone to 1939, greenish gray lime silicates to 1939.5, purplish dense siltstone to 1943.5,

2000

Drill Hole No. 2 | Charleston Project | Page 9
Collar Elevation | Cochise County Arizona | By
Coordinates | Scale
Bearing | Started
Depth | Completed
Inclination 90°

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type

Alteration

ser	Sericite		Garnet
kao	Kaolin	ser	Serpentine
sil	Silica		Biotite
chl	Chlorite	kf	K Feldspar

then gray to light greenish gray lime silicates to 1969, then gray to light gray (some lime silicates) to 1996, then purplish siltstone to 2002. At 2002 3" light gray core. Minor py veining in gray and green gray lime silicate rock < 1% sulfide.

2050 2002.3-2027 Dense fine grey siltstone, grades to purplish siltst at 2014, then to fine grey siltstone at 2027.

2032 Qtzite gy silty

2045 Siltstone - val mud? gritty bxt'd buff gray to purplish gy

2082 Siltstone - lithic mud fg tuff not unlike pre entys but more varigated occ flow? banding

2100

2102 Qtzite - fg silty gy green grades from pre enty to better looking qtzite at bot

2157 Siltstone - fg tuff bxt'd occ lg incls and fine frags not as muddy looking as pre thin (1/16") high veins of sphal occ present the sequence from 2045 seems to be more tuffacious than the previous runs of siltstone (from 2145 call it good tuff)

2150

2165 Ditto

2200

2212 Silicified contact bx gy altd rock, prob tuff

2250

Drill Hole No. 2
Collar Elevation
Coordinates
Bearing
Depth
Inclination 90°

Charleston Project
Cochise County Arizona

Scale
Started
Completed

Page 1
By

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type

Alteration

	Sericite		Garnet
	Kaolin		Serpentine
	Silica		Biotite
	Chlorite		K Feldspar

2271 Porphyry latite andesitic (Uncle Sam latite por) feldspar qtz fprph dk greenish buff to purple contacts bxt'd and altd composite zone qtz latite porph about 6' at 2222

2290 Qtzite-and tuff? siltstone dk gy qtzite-bxt'd zone w/locally heavy sphal as cs diss clots and high < 1/16" stringers

2300

2323 Qtzite-grades from fg silty to med g sandy 2/calcite cement

2350

2407 Siltstone-variable gy, purple buff, local sandy zones numerous fn calcite stringers last 10' strongly alt'd, bxt'd kaolinized ½" wide replacement stringers of cpy at 2399 cuts core at 15° to axis.

2400

2435 Qtzite siltstone interbedded bxt'd diss sphal 2423 over 8" in a dk gy bxt'd qtzite? some cpy diss

2450

2452 Tuff? dk gy to buff-incls n fg silty mud at bot of enty

2458 Qtzite - pinkish

2490 Siltstone-varigated pk and green bleached borders along epidote zones also runs of dk purple mudstone v fg-hemotitic packing (bedding) 45° to core

2500

Drill Hole No. 2 | Charleston Project | Page
Collar Elevation | Cochise County Arizona | By
Coordinates
Bearing | Scale
Depth | Started
Inclination 90° | Completed

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type
		0.060					
		0.044					
		0.031					
		0.019					

Alteration

	Sericite		Garnet
	Kaolin		Serpentine
	Silica		Biotite
	Chlorite		K Feldspar

2553-2572 Siltstone, purplish red, grades into tactite at 2555, f grained, gy, epidote splotches. This in turn grades into qtz at 2560, med gy qtz to 2572

2572-2574.5 Qtz, med gy, grades into banded f gy tactite at 2573. Tactite to 2574.5

2550 2574.5-2626.5 Tactite, metamorphosed calcareous arkose, qtz lenses, mudstones, siltstones, strong epidotized. Diss py at intervals in certain intervals, minor sphal and cpy loc in small veins.

2626.5-2657 Qtz, with chlorite and iron rich cement, epidote & calcite blebs at intervals, minor sphal and cpy 2247-2248.6

2600

2657-2669 Meta-arkose, qtz, epidote and calcite blebs, to 2669

2650 2669-2672 Mudstone, reddish, with epidote spots to 2672

2672-2694 Shale, siltstone to 3688, then qtz to 2694

2694-2704 Shale, dk purplish shale, grading downward to siltstone epidotized in part

2700

2704-2727 Qtz, lt gy in color, f grained grades to med grained

2727-2754 Shale & qtz. F gy shale, loc purple in color to 2731, then f qtz to 2739, then lt gy med f to med grained. Arkosic locally. 2752-2754

2750

Drill Hole No. 2
Collar Elevation
Coordinates
Bearing
Depth
Inclination 90°

Charleston Project
Cochise County Arizona

Scale
Started
Completed

Core Recovery | Alteration | Chalcopyrite | Sphalerite | Galena | Ag | Pyrite | Rock Type

Alteration

Sericite		Garnet	
Kaolin		Serpentine	
Silica		Biotite	
Chlorite		K Feldspar	

2754-2791 Tactite, qtzt. Lime-silicate (tactite), locally serpentinized, followed by qtzt to 2759. Two feet of shale, then gy mottled qtzt to 2770, thereafter increasing lime silicate (epidote), f grained, dense, hard to 2791

2791-2839 Qtzt, tactite. Fine to med grained qtzt to 2808, lime silicate to 2818, f grained qtzt to 2839

2800

2839-2845 Shale and lime-silicate.

2845-2882 Qtzt, f, gy, dk shale to 2850 grading through siltstone to f qtzt to 2868. Med qtzt for 2', then purple shale, locally epidotized, to 2882.

2850

2882-2902 Qtzt, f gy, grading into med grained epidotized qtz, to 2890. At 2890, 6" interval with cpy. (10% cpy) Below cpy zone, mottled f grained siltstone to 2893, then dk gy f siltstone, becomes lighter with depth and grades into epidotized lime-silicate at 2902

2900

2902-2915 Dark purplish shale, lime-silicate 2905-2908, then shale and qtzt.

2915-2973.5 Qtzt, lt gy, f grained, banded with epidote, bedding 60° to axis of core, becoming med grained at 2926. 6" med grained qtzt with cpy at 2929; estimate 5% cpy. Barren shale and lime-silicate below to 2953, then 6" med qtz w/cpy, 7% cpy estimated. Underlain by barren shale and qtz, 30° angle to axis of core. Estimate 25% cpy in this interval, then 6" barren qtz, then 1" solid cpy vein at 30° to axis of core, then barren med grained qtz to 2973.5

2950

2973.5-2997 Qtzt, med to coarse, arkosic, 1/8" cpy vein at 2989, otherwise barren.

3000

Drill Hole No. 2 | Charleston Project | Page
Collar Elevation | Cochise County Arizona | By
Coordinates
Bearing | Scale
Depth | Started
Inclination 90° | Completed

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type

Alteration

Sericite		Garnet	
Kaolin		Serpentine	
Silica		Biotite	
Chlorite		K Feldspar	

2997-3045 Shale, ls-silicate, minor serpentine, epidote bunches, 2' of dk shale 3043-3045

3045-3062 Lime-silicate, shale, (some serpentine), to 3049. 2' dense siltstone, 3049-3051, then lime-silicate. 1" cpy 3051.4. Chert 3054-3054.5, qtz 3057-3061. Fault zone 3061-3062

3050

3062-3072.5 Sericite, argillite, some gouge at 3062, spotted at 3065, py clots and dk angular patches, probably originally a calc-arenaceous rock, sp. 3065.5% py+. Grades downward into quartzitic-looking rock with dark patches, then to 24" dk gy-gr dense hornstone with reddish and greenish patches plus py, to contact with epidotized and pyritized andesite(?) porphyry. Spec. 3074

3100

3072.5-3128.5 Andesite(?) porphyry. Feldspars are epidotized, rock is pyritized. upper contact not cored. Lower contact at 25° to axis of core. Probably a dike.

3128.5-3154 Qtz, very f grained, or tactite, grades into granula ls--sil w/splotches, very f grained, lt to med ty to 3139.5 (at 3141, bedding at 80° to axis) then darker gy to 3142.5, epidotized zone to 3146, then massive very dk gy siltstone w/qtz. frags (less than 0.5 mm) to 3148. Py & epidote on seams at 3148. Med gy siltstone, minor py on seams. Grades to lt gy tactite with splotches at 3150, then to f lt gy qtz at 3154.

3150

3200

3154-3177 Qtz, massive to 3163, then banded, alternate f to med. Bands (bedding) at 75° to axis. Banded to 3167, then massive med grained, to 3175.5, then coarse grained, arkosic, w/py (2%) to 3177. Gradational contact with tactite.

Bot.

3177-3181.5 Tactite, med gy, v f grained, w/epidote splotches

3250

Drill Hole No. 2 | Charleston Project | Page 1
Collar Elevation | Cochise County Arizona | By
Coordinates
Bearing | Scale
Depth | Started
Inclination 90° | Completed

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type

Alteration

Ser	Sericite		Garnet
Kao	Kaolin	Ser	Serpentine
Sil	Silica		Biotite
Chl	Chlorite	K	K Feldspar

3181.5-3187 Arkosic qtz. Epidotized. Spots of cpy at 3185, 8" fairly good cpy 3186.5-3187+. Interval not yet split, will run about 10% cpy - 4%± copper.

3187-3193 Tactite, epidote splotches, variable in color, dk gy to lt gy. Spot of cpy 3192.5 in bleached & epidotized spot, grades to very f gy qtz at 3193.

3300

3193-3207 Qtz, f grained, lt gr, impure, locally splotchy w/dk gy spots grades downward into sitlstone. Impure siltstone w/epidote clots after 3201, grading back into more quartzitic material after 3207

3207-3212 Qartzite, light gray, impure, medium grained.

3350 Bottom - Complete

3400

3450

3500

Drill Hole No. 4
Collar Elevation
Coordinates
Bearing
Depth
Inclination 90°

Charleston Project
Cochise County Arizona

Scale
Started
Completed

By

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type

Alteration

Ser	Sericite		Garnet
K	Kaolin	Serp	Serpentine
Si	Silica	B	Biotite
Chl	Chlorite	K	K Feldspar

0-852 Meta andesite

50

100

150

200

250

Drill Hole No. 4 | Charleston Project | Page 2
Collar Elevation | Cochise County Arizona | By
Coordinates
Bearing | Scale
Depth | Started
Inclination 90° | Completed

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type	
								300
								350
								400
								450
								500

Alteration

Sericite	Garnet
Kaolin	Serpentine
Silica	Biotite
Chlorite	K Feldspar

Drill Hole No. 4
Collar Elevation
Coordinates
Bearing
Depth
Inclination 90°

Charleston Project
Cochise County Arizona
Scale
Started
Completed

By

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type	

Alteration

	Sericite
	Kaolin
	Silica
	Chlorite
	Garnet
	Serpentine
	Biotite
	K Feldspar

550
600
650
700
750

Drill Hole No. 4
Collar Elevation
Coordinates
Bearing
Depth
Inclination 90°

Charleston Project
Cochise County Arizona

Scale
Started
Completed

Page
By

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type

Alteration

Sericite	Garnet
Kaolin	Serpentine
Silica	Biotite
Chlorite	K Feldspar

800

850

852-941 Meta andesite, with calcite stringers

900

941-948 Fault gouge

948-1080 Meta andesite breccia; fragments of andesite, quartzite, red siltstone and arkose. Arkose contains minor diss py.

950

1000

Drill Hole No. 4
Collar Elevation
Coordinates
Bearing
Depth
Inclination 90°

Charleston Project
Cochise County Arizona

Scale
Started
Completed

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type

Alteration

Sericite		Garnet	
Kaolin		Serpentine	
Silica		Biotite	
Chlorite		K Feldspar	

1050

1080-1106 Arkose with less than 1% finely diss py (minor epidote stringers at 1100-1104)

1106-1130 Fault gouge - epidote on fractures

1100

1130-1133 Siltstone
1133-1134 Arkose, banding 50° to core axis, possibly bedding
1134-1137 Red siltstone
1137-1156 White quartzite, very minor diss fine grained py

1150

1156-1159 Quartzite breccia, gougy with inclusions of porphyritic rock
1159-1162 Quartzite
1162-1167 Quartzite breccia with angular fragment of porphyry, gougy material with sericite

200 1167-1210 Porphyry, highly altered with much sericite and clay, 1167 to 1185 brokern with much gouge, py more abundant in gouge zones

1210-1222 Arkose, .5% py, crushed zone
1222-1229 Porphyry, 1% py altered with some sericite
1229-1277 Fine ground white quartzite with very minor diss py, 1% banding 50° to core axis

1250

Drill Ho. No. 4 — Charleston Project — Page 6
Collar Elevation — Cochise County Arizona — By
Coordinates
Bearing — Scale
Depth — Started
Inclination 90° — Completed

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type

Alteration

Sericite		Garnet	
Kaolin		Serpentine	
Silica		Biotite	
Chlorite		K Feldspar	

1277-1307 Fine grained gray hornfels, very little quartz. Rock mottled 1284-1292, fine grained py diss throughout, approx 2%, grades into quartzite

1300

1307-1326 White qtzt, fine grained, very minor diss py, 1% or le
1326-1391 Arkose, crushed zone 1331-1336, healed fault zone 30° to core axis at 1332, mottled and fine grained 1357-1359, mottled and fine grained 1388-1391, Diss py-.5%

1350

1391-1398 Arkose, minor diss py -.5%
1398-1402 Crushed zone with clay and sericite, diss sulphides, minor sphalerite - 3% total sulphide

1400

1402-1424 Arkose, grades to qtzt at 1424
1424-1455 Qtzt, grades to arkose at 1455

1455-1487 Arkose qtzt, 1478-py, galena, sphal and cpy diss through the rock, spal 20%, galena 2%, cpy 1%. 1479 1" solid galena and sphal; 1480-1481 gouge with sericite; 1483-1484 gouge with sericite; 1480-1481 diss sphal and py, 5% sulphides

1450

1487-1494 Stony arkose or qtz, strong silicification, diss py-5%
1494-1496 Same

1500

1496-1498.5 Mottled arkosic qtzt mineralized 5%-10% py some chlorite

Drill Hole No. 4
Collar Elevation
Coordinates
Bearing
Depth
Inclination 90°

Charleston Project
Cochise County Arizona

Scale
Started
Completed

Page
By

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type

Alteration

Ser	Sericite		Garnet
Kao	Kaolin	Ser	Serpentine
Sil	Silica		Biotite
Chl	Chlorite	KF	K Feldspar

1498.5-1501 Qtz andesite - porphyry highly altered some sericite w/chlorite and sulphides 5% py 3% gal. 5% sphal

1501-1590 Porphyry broken and altered but less sericite, more chlorite, sulphide, mostly py-1% mineralized plus 3% sulphides some sphal and gal 190-191, several ½" stringers, minerals 10° to core axis

1550

1590-1688 Greenish grey tuffaceous qtzt, 3% sulphide 1590-1591; badly broken and gougy 1594-1598; fractures 10° to core axis calcite filling on fractures. Some epidote and chlorite? Mottled, 1611-1612 no core, 1612-1616 60% core, 1612-1616 chlorite with 2% py 1% galena 2% sphal .5% cpy; 1626-1631 grades to siltstone, 1631-1636 highly silicified, quarts and epidote stringers 10° to core axis. 1636-1643 badly broken with some sericite. 1626-1688 silicified pink colored tuff. 1663-1665 gouge and broken, badly broken and gouge 1672-1713

1600

1650

1688-1726 Coarse grey qtzt, some chlorite, py 2%, sericite and clay in gouge zone. 1727-1730 minor diss sphal, galena

1726-1745 Grades back into silicified pink arkose

1700 1746-1747 White quartzite

1747-1762 White qtzt ground to powder

1750

Drill Hole No. 4
Collar Elevation
Coordinates
Bearing
Depth
Inclination 90°

Charleston Project
Cochise County Arizona

Scale
Started
Completed

Core Recovery | Alteration | Chalcopyrite | Sphalerite | Galena | Ag | Pyrite | Rock Type

Alteration
- Sericite
- Kaolin
- Silica
- Chlorite
- Garnet
- Serpentine
- Biotite
- K Feldspar

1762-1773 Grades from quartzite to andesite porphyry, very soft and highly altered, some chlorite, 5% py, .5% cpy.

1773-1791.5 Andesite porphyry, green altered feldspars, some introduced pink K feldspar?

1791.5-1802 Mineralized zone, originally arkosic quartzite or greywacke primarily cpy 10-15% average. Minor galena and sphalerite

1800

1802-1812 Arkosic quartzite, 1802-1803 20% core recovery, gouge 1806-1810 60% core recovery, 3% sulphides mostly py, 3% diss cpy 1810-1812

1812-1822 Quartzite with diss 5% cpy, minor galena and sphal

1850

1822-1824 Arkose with numerous calcite stringers 2% sulphides mostly py

1824-1831 Quartzite, 2% sulphides, mostly py

1831-1833 Quartzite, light grey, 1-2% py, silicified vein 6" width sphalerite and lead, 5% sulphides

1833-1854 Silicified arkose, purple and coarse grained with diss galena and sphal, 1852.5-1853.5, 6% sulphides

1900

1854-1871 Arkosic quartzite, light gray to light purple, py .5%

1871-1874 Broken fine grained gray qtzt, with 1% py, minor sphal specks, some chlorite blebs

1874-1882 Light gray qtzt, py filled fracture 45° to core at 1875 sulphides -.5%

1950

1882-1895.5 Gray quartzite, diss py and sphal 1% sulphides, chlorite in last one foot.

1895.5-1903 Mineralized arkosic qtz which appears to be almost porphrytic with introduce chlorite (cpy, sphal, py) 5-6% sulphides

1903-1906 Dark gray very fine grained tuffaceous sandstone with blebs of olivine, diss sulphides, mostly py 3-5%

2000

Drill Hole No. 4 | Charleston Project | Page
Collar Elevation | Cochise County Arizona | By
Coordinates
Bearing | Scale
Depth | Started
Inclination 90° | Completed

Core Recovery | Alteration | Chalcopyrite | Sphalerite | Galena | Ag | Pyrite | Rock Type

Alteration
- Sericite
- Kaolin
- Silica
- Chlorite
- Garnet
- Serpentine
- Biotite
- K Feldspar

1906-1939 Brecciated & cemented arkosic qtzt very much mottled w/chlorite, olivine. Rock appears pink, py -.5%. 1920-1925 very dark gray siltstone silicified with 2% py. Very highly altered and bleached.

1929-1957 Light gray qtzt, 1938-1940 similar to pre section, sulphides .5%, blebs of olivine surrounded by chlorite

2050

1957-1969 Highly altered arkose? with much sericite and minor chlorite highly bleached, banding 50° to core axis, diss sphal at 1963, 6" minor py in section -.5%

1969-2001 Very similar to section from 1906-1929, broken with sericite 1978-1979, 1" sphal vein 15° to core axis at 1998, py approx 1%

2100

2001-2003 Very dark gy-wacke, 3% py, minor specks of cpy

2003-2072 Lt gy arkosic qtzt, py -.5%, 10% py 2023-2026, 2034-2041 finer grained with more py and more highly altered, 1% py, fault zone with sericite, 2044-2046. Fault gouge 2053-2054. Strong alteration 50° to core axis at 2071.

2150

2072-2196 Siltstone, strong silicification w/olivine blebs and minor chlorite patches, some sericite; Arkose 2090.5-2094; 2097.5-2104 healed breccia, mineralized zone, with introduce quartz phenocrysts, 1.5' core lost, 10% sphal, 2% cpy, 5% py; 2101-2104 30% core recovery; 2123-2124 core is deep purple colored with white splotches; 2161-2181 core badly broken with much sericite; mineralized arkose, sphal 6%, cpy 2%, py 8%, 2183-2190, one foot core missing; 2190-2196 broken with sericite.

2200

2196-2225 Purple siltstone, bleached and broken with sericite 2198-2206, very dark purple 2214-2223

2225-2242 Arkosic qtzt lt gy becomes porphyritic 2241 some sericite development near porphyry contact. Mineralized zone 2230.5-2236, sphalerite 4%, cpy 1%

2250

Drill Hole No. 4
Collar Elevation
Coordinates
Bearing
Depth
Inclination 90°

Charleston Project
Cochise County Arizona

Scale
Started
Completed

Page
By

Alteration

	Sericite		Garnet
	Kaolin		Serpentine
	Silica		Biotite
	Chlorite		K Feldspar

Core Recovery | Alteration | Chalcopyrite | Sphalerite | Galena | Ag | Pyrite | Rock Type



2242-2290 Andesite porphyry, 2249-2250 test for sphal. Minerali porphyry silicified altered with gouge and cpy 2% sphal 3% py 5%, sericite 30% core recovery, 2276-2283. 2277-2283 only 2' core recovered.

2290-2313 Arkose 2290-2291, 2" salmon colored igneous veinlet 10° to core axis at 2290, looks aplitic; quartzitic 2300-2309.

2313-2334 Very fine grained gray silicified hornfels with minute angular quartz crystals as eyes looks slightly oplitic from 2329-2334, becomes arkosic about 2330.

2334-2336 Dark Purple arkose, white splotches.

2336-2354 Purple siltstone, white lime silicates splotches. Grades to gray arkose at 2347 grades to gray arkose

2354-2362 Gray arkose becoming very white quartzitic arkose at 2356, becomes gray arkose at 2358

2362-2377 Siltstone, gray to 2364 then purple to2377

2377-2384 Lime silicates with epidote splotches

2384-2387 Purple siltstone

2387-2398 Greenish gray very fine grained silicified arkose ribbon rock or serpentinized 2392 grades into pink fine grained silicified arkose grades to gray 2394 -1% py.

2398-2408 Purple siltstone py -1%

2408-2413 Light gray to light purple arkose

2413-2472 Chlorite & epidote present. Lime silicates, considerable sericite, 10" sphal vein 30° to core axis 2438 gray arkose with sericite 2455-2456, 6" mineralization 2459, 3% sphal 3% cpy, 6' mineralization 2465 2% sphal 3% cpy overall py plus 1%

2472-2487 White silicified tuff, 20% core recovery 2476-2487

2487-2497 Banded grayish purple siltstone grading to qtzt 2489-2497

Drill Hole No. 4 | Charleston Project | Page 1
Collar Elevation | Cochise County Arizona | By
Coordinates
Bearing | Scale
Depth | Started
Inclination 90° | Completed

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type	Alteration: Sericite, Kaolin, Silica, Chlorite; Garnet, Serpentine, Biotite, K Feldspar

2497-2510 Gray arkosic qtzt mixed. 6" sphal at 2500 3% sphal.
2510-2559 White arkosic quartzite with sericite fairly well broken 2% py.
2559-2575 Light gray lime silicates and qzt, grades to gray arkosic qtzt
2550 2575-2613 Light gray arkosic qtzt & tuff, with purple bands 30° to core axis, 4% py, gouge zone 2578-2579, mineralized 2597
2613-2643 Light gray qtz, 5% py, white splotches

2643-2680 Tuff, gray to 2653 then changes to white arkosic qtzt to 2669 then gray qtzt to 2673 then grades to highly bleached
2600 tuff 2680, 8% py.
2680-2693 Fine grained bleached arkosic qtzt, mineralized zone mostly py 5-8% 2691-2693 brecciated with sericite some cpy -.2 average 2% py.

2650

2693-2699 Andesite porphyry py -1%
2699.5-2705.5 Mineralized zone brecciated with much sericite, 50% core recovery split, py 5%, minor diss cpy and sphal.
2700 2705.5-2712 Gray fine grained silicified qtzt, by 3%, very minor specs cpy.
2712-2743 Very fine grained silicified qtzt grades from white to gray containing py 1% with minor sphal argillaceous in spots. Brecciated and healed pink quartzite healed fractures 20° to
2750 core axis, py not present 2717-2722 white argillaceous qtzt 2729-2740

Drill Hole No. 4
Collar Elevation
Coordinates
Bearing
Depth
Inclination 90°

Charleston Project
Cochise County Arizona

Scale
Started
Completed

Page
By

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type
	%						

Alteration

%	Sericite		Garnet
%	Kaolin	%	Serpentine
%	Silica		Biotite
%	Chlorite	%	K Feldspar

2743-2755 Light purple arkosic qtzt. Sulphides oxidized limonite on fractures 1' cpy and sphal 2754' Cu -.5 Zn 2.0

2755-2781 Light pink to purple siltstone purple 2758-2767. All oxidized. 6" mineralization 2768 (split) bleached hornfels 2769-2781. Splotches of epodite and chlorite

2781-2802 Argillaceous quartzite grades to purple siltstone at 2788-2791, mineralized 1' 2784 (split) Bleached with splotches of epidote. Bleached siltstone 2791-2797. Purple siltstone 2797-2802

2800

2802-2824 Bleached fine grained arkosic qtz

2824-2840 White coarse grained silicified arkosic qtzt. Very minor specks black mineral possibly bornite

2850

2840-2852 Fine grained siltstone bleached

2852-2889 Coarse grained white qtzt and tuff, sericite present, minor black specs present. 2882-2885 siltstone dark gray in color 2881-2884 contains 2% py.

2889-2929 Light gray arkosic qtzt banding 40-50° to core axis grades to silicified lime 2895-2929

2900

2929-2958 Bleached siltstone with sections of lime silicates, purple siltstone, large patches of epidote

2958-2973.5 Light gray, fine grained tuff

2973.5-2981 Very coarse grained greenish gray tuff and qtzt. Mineralized slickenside at 2973.5

2950

2981-3001 Bleached siltstone, white to purple same as 2929-2958

3001-3018 Find grained gray arkosic qtzt. Coarse grained 3011-3018

3000

Drill Hole No. 4 | Charleston Project | Page 3
Collar Elevation | Cochise County Arizona | By
Coordinates
Bearing | Scale
Depth | Started
Inclination 90° | Completed

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type

Alteration

Ser	Sericite	Gar	Garnet
Kao	Kaolin	Serp	Serpentine
Sil	Silica	Bio	Biotite
Chl	Chlorite	K	K Feldspar

3018-3100 Bleached siltstone white to purple numerous slikensides some sericite present, same as 2929-2958, numerous broken zones

3050

3100-3119 White arkosic quartzite

3100

3119-3242 Bleached siltstone white to purple some dark gray argillite same as 2929-2958. 3232-3234 borinite and cpy.

3150

3200

3242-3293 Arkosic quartzite, minor specs of black mineral with green (bo[illegible] not copper)

3250

Drill Hole No. 4
Collar Elevation
Coordinates
Bearing
Depth
Inclination 90°

Charleston Project
Cochise County Arizona

Scale
Started
Completed

Page
By

Core Recovery	Alteration	Chalcopyrite	Sphalerite	Galena	Ag	Pyrite	Rock Type

Alteration

	Sericite		Garnet
	Kaolin		Serpentine
	Silica		Biotite
	Chlorite		K Feldspar

3293-3301 Bleached siltstone white to purple same as 2929-2958

3300

3301-3303 Brecciated and calcite filled arkosic qtzt.
Beginning of sulphide zone again 6" cpy at 3303

3350

3400

3450

3500

GENERALIZED DESCRIPTIVE LOG

Charleston Lead Mine | Cochise County | James Stewart Construction Co.

HORNE(STEWART)#5 DRILL HOLE

0-12	No core
12-369	Graywacke, gray, very fine-to coarse-grained, bedding 50°, locally very thin bedded, shaley, locally arkosic, volcanoclastic, and/or conglomeratic. Clasts up to 2" diam.
91-155	Conglomeratic 50% fragments of sediments and volcanics
166-173	Fracture zone; 166-167 red gouge remainder is broken core and gouge argillic, chloritic, Fe oxide
173-182	Conglomeratic, 70° fracture, argillic
191-203	Fracture zone, gouge and broken core, moderate Fe oxide, strong argillization
203-211	Calcite and clay stringers
211-213	Fracture zone
213-219	Weak Fe oxide
219-221	Fracture zone, gouge
239-259	Conglomeratic, clasts up to 2" diam., locally well broken
259-369	Massive, dark graywacke, high angle kaolin stringers
304-305	Pyritic, leached
328-329	Gouge zone, local calcite-quartz stringers
330-	15° fracture with drusy quartz
369-390	Andesite, dark green-gray, porphyritic-aphantic; feldspar phenocrysts up to 1 cm. Argillized, kaolinized, bottom on 50° fracture
390-537	Graywacke as above, kaolinized, fractured, Fe oxide in fractures
537-551	Breccia, maroon, arkosic, shaley, with clasts of graywacke up to 2". Clay along fractures, minor pyrite
551-837	Graywacke as above
551-566	Light gray pyritic rock, 1% pyrite, very fine-grained; calcite stringers, bleached, argillized
566-568	Fracture zone, finely broken, gouge
568-582	Dark gray graywacke conglomerate, clasts of shale, graywacke, volcanics drusy calcite on fractures, kaol. on slips
637-638	Fault zone 20°
651-677	Bleached, pyritic 0.5-1% pyrite, possible galena traces in fractures drusy calcite and broken core at 665
677-728	Arkosic graywacke conglomerate
728-730	Broken core
745-753	Bleached .5% pyrite on fractures
763-774	Bleached, pyrite

	775-804	Irregular disseminated pyrite up to 3%, epidote
	821-837	Disseminated pyrite, argillic-intensity increasing toward bottom, abundant clots of epidote up to 1" diam.
837-921	Alternating graywacke and light gray porphyritic andesite	
	837-840	Andesite, phenocrystic plagioclase up to 2 mm, local clots of epidote and magnetite
	840-844	Graywacke
	844-846	Andesite
	846-850	graywacke
	850-853	Andesite — 0.1-1% disseminated pyrite
	853-862	Graywacke
	862-864	Andesite
	864-873	Graywacke
	873-875	Andesite
	875-902	Graywacke: baren
	902-903	Andesite — 0.1-1% pyrite,
	903-916	Graywacke, 909-912 gouge — trace chalcopyrite
	916-921	Andesite — increasing with
	921-936	Graywacke, galena stringer at 930 — depth to 2% pyrite
936-947	Graywacke (?) thoroughly argillized, pyritized, pyrite 1-3%, galena stringers	
	938-940	Gouge
	944	Bleb 5-8% pyrite, specks of sphalerite
947-1398	Graywacke, dark gray, fine-grained, pyritic	
	947-957	Calcite and pyrite stringers (2% pyrite), chloritized, bleached coarse euhedral pyrite
	957-975	1-3% disseminated pyrite
	975-985	Conglomeratic, tarnished pyrite decreasing to 1%, epidotization increasing with depth
	1007	1-2% irregular pyrite
	1017-1026	Intense alteration, pyrite 4-6%, blebs of sphalerite and galena stringers of galena-pyrite-epidote, trace chalcopyrite
	1026	Weakly chloritized, 1-2% pyrite
	1041	Fracture zone 20°, bleached 1' both sides, veins of quartz-calcite-epidote-galena-sphalerite
		Below 1041 irregular steep quartz-calcite-pyrite-chalcopyrite-galena stringers. 1-3% disseminated pyrite
	1065-1067	Fracture zone; quartz-calcite-pyrite-chalcopyrite-sphalerite-galena strings. Galena weakening
	1080	All stringers weak. 3% pyrite decreasing with depth disappears at 1100
	1107	0.5% pyrite increasing with depth
	1115-1117	Fracture zone; broken core and gouge

1117 Intense alteration or thermal metamorphism
1139 Pyrite decreasing with depth
1143 Chloritic hydrothermal alteration; trace galena
1147-1149 Fracture zone
1154 Fresh rock
1156 Thermal metamorphism, pyrite, epidote, recrystallization
1158 Chlorite-epidote-pyrite mineralization; trace galena, chalcopyrite
1182 Galena-pyrite-chalcopyrite stringers
1188-1191 Blebs of galena-chalcopyrite-epidote-calcite up to 1" long. Disseminated galena-sphalerite.
1193, 1195, 1197, 1200 Veins, up to 1.5", galena-pyrite-chalcopyrite-sphalerite-calcite, 15°. Disseminated galena-sphalerite
1201-1204 Broken core
1204 Chloritized graywacke; pyrite 1-2%
1212 8" quartz vein 60° 1% pyrite
1213 Graywacke, pyrite, stringers of galena
1220-1223 Quartz-pyrite vein 20°, minor galena and chalcopyrite
1218-1222 5% pyrite, 0.1% Cu, 0.1% Pb
1230 Base metal zone
1230-1235 Graywacke conglomerate, clasts of sediments and volcanics up to 2" diam. 1% pyrite
1235-1246 Graywacke, 2% pyrite, minor epidote, pyrite decreases with depth
1258 2-3% pyrite, fine-grained chlorite-epidote alteration, trace galena
1270-1281 Conglomerate; thoroughly altered, galena-calcite-sphalerite stringers
1281 3" quartz-pyrite vein 50°
1300 Base metals zone. 0.5% pyrite
1308-1316 Fracture zone, no alteration, weak Fe oxides
1325 Chloritic, argillic alteration, 2% pyrite, rock fragments up to 8"
1342 Galena-epidote-calcite stringers; alteration becoming less pervasive, more irregular
1369 No alteration
1378 1/2" galena-pyrite-chalcopyrite-sphalerite-calcite vein, 50° sulfide content increasing with depth
1398-1516 Gray arkosic sandstone conglomerate, clasts of sediments and volcanics. 0.5-1% disseminated pyrite, 1% galena and chalcopyrite. Galena-chalcopyrite-calcite stringers; chalorite-epidote, argillic alteration.

1416 Stringers of sphalerite
1428-1429 Quartz-calcite-pyrite vein
1430 Disseminated galena and chalcopyrite
1464 Sphalerite-epidote-quartz-chalcopyrite stringers
1496 Pyrite increasing to 1%
1502 1" sphalerite-pyrite-epidote-quartz vein, 25°
1510 1/4" vein same as above, 20°

] Frequency of clasts decreasing
Pyrite 0.5% decreasing

1516-1537 Gradational contact to massive light gray shale. Grades into dark very-thin-bedded shale then back to massive shale. Abundant calcite stringers. Pyrite 0.5-1%. Grades into limestone below.

1537-1556 Light gray massive limestone, slightly recrystallized, 0.1-0.2% pyrite and few calcite stringers. Badly broken core near bottom.

1556-1560 Light gray fine-grained quartzite, calcareous matrix 0.1% pyrite

1560-1579 Argillaceous sandstone, with few clasts, partially epidotized, 0.5% pyrite argillic-chloritic alteration

1579-1584 Coarse grained sandstone, no pyrite, argillic-chloritic-epidote alteration

1584-1672 Fine-grained argillaceous sandstone 0.5% disseminated pyrite, light gray to white

1554-1674 Badly broken core. Local pebbles up to 1" diam. erratic pyrite distribution. Calcareous matrix below 1618
1638-1642 No core
1650 Silicified
1654-1658 Silicified sandstone or quartz vein, 10% pyrite with galena, chalcopyrite and sphalerite
1657-1663 Gouge, high pyrite
1658-1660 Lost core
1667-1672 Gouge

1672-1700 Very fine-grained gray quartzite, very thinly bedded near top becoming more massive with depth, 40° on bedding, fine pyrite, 5-7% chalcopyrite minor galena.

1676-1700 Fine-grained, silicified, pyrite 0.5% locally, massive epidote nodules with pyrite and chalcopyrite

1700-1704 Maroon, arkosic shale, trace pyrite, minor epidote

1704-1795 Fine-grained argillaceous quartzite, light gray, 0.5% disseminated pyrite

1709 No pyrite
1714 Limestone inclusions
1718 0.5% pyrite
1729 and 1737 1/2" veins of quartz-sphalerite-chalcopyrite-galena with epidote rim
1772 Pyrite gone
1772-1782 Contact; 70°, with epidotic hornfelsic shale epidote-calcite nodules, trace pyrite
1795 End of drilling as of 24 September 1970

GENERALIZED DESCRIPTIVE LOG (Cont.)

Charleston Lead Mine Cochise County James Stewart Construction Co.

HORNE (STEWART) # 5 DRILL HOLE

1795-1805	Quartzite, light gray, fine grained, trace of pyrite along fractures. 1798-1804 Fractured and bleached zone, calcite along fractures.
1805-1817	Hornfelsic shale, dark gray, epidote nodules, pyrite and calcite in nodules and in stringers, 0.1-0.3% disseminated pyrite 1814-1817 Fracture zone, clay in stringers
1817-1824	Quartzite, gray, calcite in stringers $<$0.1% pyrite
1824-1847	Hornfelsic shale, epidote in nodules, $<$ 0.1% pyrite, dark gray with several maroon horizons; pyrite and chlorite on high-angle slips.
1847-1853	Quartzite, light gray, fine-to-medium grained, 0.1% disseminated pyrite.
1853-1873	Shale, maroon, epidote nodules, bleached with pyrite and epidote, calcite and clay on slips.
1873-1919	Hornfelsic shales, gray, epidotized; epidote-calcite-chlorite nodules with pink matrix, $<$0.1% pyrite, last 20' is maroon and coarser grained. 1914-1917 Fracture zone.
1919-1927	Quartzite, light gray, very-fine-grained; some epidote on fractures.
1927-1947	Hornfelsic shale, epidotized as above.
1947-1961	Quartzite, fine grained as above.
1961-1978	Hornfelsic shales, white to gray, epidote nodules, 0.1% disseminated pyrite. 1965-1966 Broken core, no pyrite below fracture.
1978-2014	Quartzite, light gray, fine-to-medium grained. Calcite on slips, local thin beds of hornfelsic shale.
2014-2040	Hornfelsic shale, epidote nodules with calcite, 0.1-0.2% disseminated pyrite irregularly distributed, trace of sphalerite in last 2'.
2040-2048	Quartzite, light gray, locally epidotized, sphalerite in stringers and disseminated $<$ 0.1-0.2% pyrite, trace chalcopyrite, stringers of calcite.

2048-2080	Hornfelsic shale, light to dark gray, epidote in stringers and nodules, 0.1-0.2% disseminated pyrite, trace chalcopyrite, trace galena and sphalerite in blebs and disseminated, sparse mineralization below 2064. 2069-2074 chloritized, pyrite, sphalerite, chalcopyrite, galena disseminated in friable fractured rock.
2080-2083	Quartzite, chloritized, disseminated pyrite, chalcopyrite, sphalerite, galena.
2083-2105	Quartzite, trace of chlorite, trace disseminated pyrite, stringers of epidote-calcite-pyrite-chalcopyrite-sphalerite-galena.
2105-2118	Hornfelsic shale, epidotized, calcite-pyrite-epidote-sphalerite-chalcopyrite in stringers, local disseminated chalcopyrite, pyrite 0.5% decreasing with depth.
2118-2127	Quartzite, very fine-grained, gray, epidote-calcite stringers, $<$ 0.1% pyrite.
2127-2147	Hornfelsic shale, as above. 2130 3" long sphalerite-chalcopyrite bleb.
2147-2151	Quartzite as above.
2151-2213	Hornfelsic shale as above. 2161 1' fracture zone 2165 Pyrite stringers 2169 Pyrite-epidote-calcite stringers, epidote nodules 2191-2195 Fracture zone, finely broken, argillized, 0.5-0.1% pyrite disseminated and in veins.
2213-2231	Contact zone, abundant epidote-chlorite-calcite blebs and spots, 0.5-0.1% pyrite, dark gray quartzitic to volcanic rock, local phenocrysts of pink feldspar?, local intense brecciation
2231-2313	Dark to medium gray latite to andesite porphyry, phenocrysts are epidotized. 1-3% disseminated pyrite 2269-2275 Fracture zones with gouge
2313-2316	Contact zone, chloritized, bleached, broken rock fragments
2316-2318	Black, aphanitic rock with feldspar phenocrysts and epidote blebs.
2318-2322	Quartzite, gray, fine grained, relic bedding at 45°, interbedded with metashale at bottom, epidotized.
2322-2336	Hornfelsic shale as above.

2336-2374	Quartzite, light gray, fine-to-medium grained, local epidote stringers. 2352 2" dike andesite porphyry. 2369 6" of disseminated galena.
2374-2528	Alternating quartzite and hornfelsic shale, each 5 to 10' thick. Hornfelses are epidotized with minor local epidote nodules. 0.1% pyrite average distributed irregularly with no apparent control. Broken core at 2497-2499, 2501-2507, 2514-2517
2528	End of hole.

JED:a
October 19, 1970

CHARLESTON MINE

Assay Summary

HOLE #1

Depth	% Cu	oz/Ton Ag	oz/Ton Au	% Ni	% Pb	% Zn
265	.09	0.4	--	--	.16	.44
280	.05	--	--	.03	--	--
315	1.0	--	--	--	--	--
360	.03	--	--	--	.09	.21
415	.10	--	--	--	.06	.10
510	.03	--	.03	--	.16	.21
525	.25	.7	.11	--	Tr	4.90
541	.01	--	--	--	.06	.12
642	.26	--	--	--	Tr	1.2
703 - 713	.08	--	--	.01	--	--
720	.08	--	--	--	--	11.40
810	.02	--	.02	--	--	--
860 - 887	--	--	--	.15	--	--
864	.055	.4	.02	--	.02	1.0
898	.04	0.7	.03	--	--	--
1102 - 1106	.485	0.7	Tr	--	--	--
1108	.095	.04	--	--	--	--
1106 - 1108	.10	3.0	Tr	--	0.6	--
1148	.035	.04	--	--	--	--
1300	.02	.02				
1541	.07	.3				
1632 /632	.01	--	--	.03	--	--
1636	.08	.5	--	.03	5.6	8.05

CHARLESTON PROPERTY

Assay Summary
Drill Hole #2

Footage	% Cu	% Pb	% Zn	% MoS_2	oz/ton Au	oz/ton Ag
580	.045					0.4
598	.03					0.3
620	.04					0.4
660	.035					0.3
750	.02	Tr				1.6 ✓
781	.03		0.9 ✓		.01	0.6 ✓
1005 - 1008	.43	4.88 ✓	9.2 ✓			
1028 - 1032	.07	.6	5.0	0.0021		
1028 - 1032	.084	.65 ✓	1.22 ✓		.003	.14
1028 - 1032	.049	.66	1.03			.11
1098 - 1107	.030	Tr	.08			
1107 - 1116.6	.041	Tr	.12			
1116.6 - 1128	.029	Tr	Tr			
1128 - 1138	,030	Tr	Tr			
1138 - 1148	.042	Tr	.05			
1148 - 1158	.021	Tr	Tr			
1158 - 1167	.068	Tr	.07			
1167 - 1179	.041	Tr	.05			
1175 - 1185	.16	.44	1.48 ✓	0.0028	.02	
1175 - 1185	.113	.05	1.35			.42
1175 - 1185				0.0028	.02	
1179 - 1188	.022	Tr	.06			
1188 - 1197	.051	Tr	.05			
1323 - 1331	.01	?	1.50 ✓	0.0021	.01	
1323 - 1331	.038	.40	.56			.11
1333.5 - 1337.5	.02	?	1.10 ✓	0.0023	.01	
1333.5 - 1337.5	.080	.05	.10			.04
1377 - 1382.5	.019	.12	.25			
1382.5 - 1387.5	.030	.07	.27			
1387.5 - 1391.75	.032	.07	.15			
1391.75 - 1396	.048	.24	.70 ✓			
1407 - 1411.5	.14	1.45 ✓	2.87 ✓			
1411.5 - 1416	.048	.10	Tr			
1416 - 1422.5	.029	.07	Tr			
1422.5 - 1429	.038	.10	.20			
1429 - 1434	.047	.12	.25			
1434 - 1439	.048	.02	.05			
1439 - 1444	.049	.30	.32			
1444 - 1448.5	.028	.25	.12			
1448.5 - 1453	.038	.13	.20			
1453 - 1457	.07	.66 ✓	1.40 ✓			
1457 - 1462	.16	.65 ✓	1.75 ✓			
1462 - 1467	.03	.05	.25			
1532 - 1534	.026	.21	.40			
1656.5 - 1661	.038	Tr	Tr			
1661 - 1665	.029	Tr	Tr			
1665 - 1670	.038	Tr	Tr			
1670 - 1675	.029	Tr	Tr			
1678 - 1680	.030	Tr	Tr			
1680 - 1685.5	.019	Tr	Tr			
1690.5 - 1694.5	.028	.05	.12			

Footare	% Cu	% Pb	% Zn	% MoS_2	oz/ton Au	oz/ton Ag
1694 - 1699	.028	.05	.10			
1699 - 1703	.029	.05	.12			
1703 - 1708	.027	.03	.12			
1708 - 1713	.049	.06	Tr			
1721.5 - 1726.5	.038	.36	.60 ✓			1.49 ✓
1726.5 - 1732	.101	.44	.64			1.49 ✓
1726.5 - 1732				0.0024	.02	
1726 - 1732	.10	.42	3.70 ✓	0.0024	.02	0.7
1732 -1737	.047	.46	3.40 ✓			
1737 - 1741	.076	.03	.17			
1741 - 1745.5	.028	.12	.25			
1745.5 - 1750	.020	.07	.30			
1750.5 - 1755	.037	.07	.25			
1755 - 1759.5	.028	Tr	.05			
1759.5 - 1763.5	.047	Tr	.05			
1763.5 - 1767.5	.036	.05	.12			
1767.5 - 1772.5	.029	.03	.12			
1772.5 - 1776.5	.029	.03	Tr			
1776.5 - 1780	.037	.02	Tr			
1780.5 - 1785	.029	.03	Tr			
1785 - 1789.5	.048	.05	Tr			
1789.5 - 1793.5	.029	.02	Tr			
1793.5 - 1798.5	.048	.03	.05			
1798.5 - 1803	.037	.03	.07			
1803 -1808	.029	.03	.07			
1808 -1812	.037	.14	.50 ✓			
1812 - 1816	.076	.12	.40			
1816 - 1821.5	.048	Tr	Tr			
1820.5 -	1.9 ✓	.35	6.1 ✓		.02	
1821.5 - 1826.5	.029	Tr	Tr			
1826.5 - 1831	.029	Tr	Tr			
1831 - 1836	.037	Tr	Tr			
1836 - 1841	.029	Tr	Tr			
1841 - 1845	.037	Tr	Tr			
1845.5 - 1850.5	.029.	.05	.02			
1850.5 - 1854.5	.21	.92 ✓	1.12 ✓	0.0025		
1850					.01	0.2
1850.5 - 1854	.239	.78	1.64			.27
1854.5 - 1858.5	.087	.10	.12			
1886 - 1889.5	.029	.02	Tr			
1893 - 1896.5	.057	Tr	Tr			
1896.5 - 1901	.029	Tr	Tr			
1901 - 1905	.037	.08	Tr			
1905 - 1910	.029	Tr	Tr			
1910 - 1915.5	.038	.02	Tr			
1915.5 - 1919	.019	Tr	Tr			
1923	.05		14.7 ✓			
1858.5 - 1862	.048	.34	.7 ✓			
1862 - 1867	.04	Tr	Tr			
1867.5 - 1872	.052	Tr	Tr			
1872 - 1876	.028	Tr	Tr			
1876.5 - 1881	.042	Tr	.05			
1881 - 1886	.028	.03	.03			
- 1923.5	.041	1.80 ✓	2.20			
1923.5 - 1928	.028	Tr	Tr			
1928 - 1931.5	.037	Tr	.07			

Footage	% Cu	% Pb	% Zn	% MoS_2	oz/ton Au	oz/ton Ag
1931.5 - 1935	.039	Tr	.05			
1935 - 1937.5	.038	Tr	.06			
1937.5 - 1941	.030	Tr	.05			
1941 - 1946.5	.049	Tr	.03			
1946.5 - 1951	.032	Tr	Tr			
1951 - 1956	.049	Tr	Tr			
1956 - 1961	.031	Tr	Tr			
1961 - 1965.5	.042	Tr	.07			
1965.5 - 1969	.04	Tr	Tr			
1969 - 1974	.029	Tr	.05			
1974 - 1978	.041	Tr	Tr			
1978 - 1983.6	.03	Tr	.04			
1983.6 - 1988	.028	Tr	Tr			
1988 - 1993	.032	Tr	Tr			
1993 - 1998	.052	Tr	Tr			
1998 - 2002	.03	Tr	Tr			
2002 - 2007	.028	Tr	.02			
2007 - 2011	.032	Tr	.07			
2011 - 2015	.04	Tr	.04			
2015 -2021	.042	Tr	.12			
2021 - 2024	.032	Tr	Tr			
2024 - 2027	.021	Tr	Tr			
2027 - 2031.5	.029	Tr	Tr			
2031.5 - 2036	.030	Tr	Tr			
2036 - 2040.5	.042	Tr	Tr			
2040 - 2045	.061	Tr	Tr			
2045 - 2050	.04	Tr	Tr			
2050 -2054	.049	Tr	Tr			
2054 - 2058	.027	Tr	Tr			
2058 -2063	.041	Tr	Tr			
2063 -2068	.039	Tr				
2068 - 2073	.03	Tr				
2073 - 2078	.032	Tr	.05			
2078 - 2082	.040	Tr	.03			
2082 - 2087	.059	Tr	.05			
2087 - 2092	.05	Tr	.05			
2093 - 2097	.042	Tr	.045			
2097 - 2103	.06	Tr	Tr			
2103 - 2107	.072	Tr	Tr			
2107 - 2113	.039	Tr	Tr			
2113 - 2116	.04	Tr	Tr			
2116 - 2121	.062	Tr	Tr			
2121 - 2125	.03	Tr	.12			
2125 - 2130	.042	Tr	Tr			
2130 - 2135	.049	Tr	Tr			
2135 - 2139	.041	Tr	.07			
2139 - 2144	.03		.07			
2144 - 2149	.039		Tr			
2149 - 2154	.038		.05			
2154 - 2157	.04		.03			
2157 - 2162	.031		.05			
2162 - 2167	.052		.04			
2167.5 - 2172.	.03	Tr	.07			
2172 - 2176.5	.06	Tr	.10			
2176.5 - 2181	.06	Tr	1.0 /			
2181.5 - 2185.7	.05	Tr	.9 /			
2185.7 - 2189.7	.07	Tr	.4			

Footage	% Cu	% Pb	% Zn	% MoS_2	oz/ton Au	oz/ton Ag
2189.7 - 2195	.03	.15	.15			
2195 - 2200	.03	.12	.12			
2200 - 2205	.04	.05	.07			
2205 - 2209.5	.03	.12	.12			
2209.5 - 2214	.06	Tr	.25			
2214 - 2219	.07	Tr	.25			
2219 - 2223	.06	.14	.22			
2223 - 2229.5	.11	Tr	Tr			
2229.5 - 2236	.10	Tr	Tr			
2236 - 2241	.05	Tr	Tr			
2241 - 2245.5	.04	Tr	.05			
2246.5 - 2251.5	.05	Tr	.05			
2251.5 - 2256.5	.05	Tr	Tr			
2256.5 - 2261.5	.16	Tr	Tr			
2261.5 - 2266.5	3.40 ✓	Tr	.07			.86
2261 - 2266	3.36	.05	.10			.86 ✓
2266.5 - 2272	3.56	Tr	.05	0.0066	.02	.97
2266 - 2272	3.38 ✓	.05	.08		.002	.82 ✓
2266 - 2272	2.56	.05	.09			.97
2266.5 - 2272				0.0066	.02	.70
2272 - 2278	.28	Tr	Tr			
2278 - 2283	.05	Tr	Tr			
2283 - 2288	.05	Tr	1.25 ✓			
2288 - 2291.5	.037	Tr	.12			
2291.5 - 2293.7	.049	Tr	.05			
2293.7 - 2301	.041	Tr	Tr			
2306 - 2309	.021	Tr	.03			
2309.5 - 2314.5	.019	Tr	.05			
2314.5 - 2318.5	.020	Tr	Tr			
2318.5 - 2323.5	.022	Tr	Tr			
2323.5 - 2328	.039	Tr	.40			
2328 - 2332.5	.018	Tr	.07			
2332.5 -2337	.04	Tr	Tr			
2337 - 2342	.06	Tr	.07			
2342 - 2347	.04	Tr	Tr			
2347 - 2351.5	.027	Tr	Tr			
2351 - 2356.5	.031	Tr	Tr			
2356.5 - 2361.5	.029	Tr	Tr			
2361.5 - 2366	.027	Tr	Tr			
2366 -2371	.042	Tr	.03			
2371 - 2375	.031	Tr	.05			
2375 - 2380	.032	Tr	.07			
2380 - 2384	.029	Tr	Tr			
2384 - 2388	.030	Tr	Tr			
2388 - 2393	.042	Tr	Tr			
2393 - 2397.5	.029	Tr	Tr			
2397.5 - 2402	.07	Tr	Tr			
2402 - 2407	.07	Tr	.03			
2407 - 2412	.049	Tr	.02			
2412 - 2417	.03	Tr	.02			
2417 - 2421	.041	Tr	Tr			
2421 - 242625	.032	Tr	Tr			
2426.5 - 2430.5	.029	Tr	Tr			
2430.5 - 2435.7	.019	Tr	Tr			
2435.7 - 2440	.042	Tr	Tr			
2440 - 2445.9	.027	Tr	.07			
2445.9 - 2450	.038	Tr	.05			

Footage	% Cu	% Pb	% Zn	% MoS_2	oz/ton Au	oz/ton Ag
2450 - 2456	.04	Tr	.04			
2456 - 2461	.042	Tr	Tr			
2461 - 2464	.027	Tr	.06			
2464 - 2470	.019	Tr	Tr			
2470 - 2474	.041	Tr	.05			
2474 - 2479	.02	Tr	Tr			
2479 - 2483	.032	Tr	Tr			
2483 - 2488	.029	Tr	.07			
2488 - 2492	.031	Tr	Tr			
2492 - 2497	.019	Tr	Tr			
2497 - 2502	.029	Tr	Tr			
2512 - 2515	.020	Tr	.03	0.0027		
2512 - 2516	.028					
2515 - 2526	.10	Tr	2.40			
2516 - 2520	.056			0.0029		
2515 - 2520	.053	.05	.05			.02
2578.25- 2583	.09	Tr	.30			
2583 - 2588	.028	Tr	.07			
2588 - 2593	.042	Tr	1.20 ✓			
2593 - 2598	.031	Tr	.12			
2598 - 2603	.029	Tr	Tr			
2603 - 2607	.037	Tr	.07			
2607 - 2610	.04	Tr	.05			
2610 - 2615	.028	Tr	Tr			
2615 - 2620	.031	Tr	.08			
2620 - 2624	.088	Tr	.03			
2624 - 2628.5	.12	Tr	1.12 ✓			
2628.5 - 2633.5	.010					
2633.5 - 2639.5	.010					
2639.5 - 2644	.028			0.0021		
2644 - 2648.6	.048					
2648.6 - 2652	.010					
2652 - 2657.4	.026					
2657.4 - 2662	.036					
2662 - 2666.7	.026					
2666.7 - 2672	.018					
2672 - 2677	.018					
2677 - 2682	.027					
2682 - 2687	.018					
2687 - 2692	.016					
2692 - 2695.5	.016					
2695.5 - 2701	.010					
2701 - 2705	.028					
2705 - 2709	.016					
2709 - 2714	.010					
2714 - 2719	.028					
2719 - 2724.5	.010					
2724.5 - 2728	.029					
2728 - 2733	.016					
2733 - 2737.5	.018					
2845	.016					
2850	.027					
2854	.028					
2857 - 2862	.020					
2866 - 2871	.020					

Footage	% Cu	% Pb	% Zn	% MoS_2	oz/ton Au	oz/ton Ag
2930 - 3935.5	.015					
2945 - 2947	.048					
2945 - 2947	.057	.05	.05			
2947 - 2949	1.03	.05	.05		.002	.15
2947 - 2949	1.11 ✓	.05	.05			.19
2947 - 2949	.83		.70 ✓	0.0027	.02	
2949 - 2951	.076			0.0022		
2951 - 2953	.67 ✓					
2953 - 2955	.36			0.0018		
2953 - 2955	3.40 ✓	.05	.22			.08
2955 - 2957	.048			0.0021		
2957 - 2959	5.52 ✓					
2959 - 2961	5.66 ✓				.002	1.09 ✓
2959 - 2961	4.57	.05	.05			1.09
2959 - 2961	6.76		.90	0.0020	.03	
2961 - 2963	.067					
2963 - 2964.5	.028					
2963 - 2964.5	.048	.05	.05			.46
2964.5 - 2966.5	.036					
2966.5 - 2968.5	.048					
2968.5 - 2969.5	.027					
2969.5 - 2971.5	.088					
2971.5 - 2973.5	.19					
2973.5 - 2975.5	.076					
2975.5 - 2977.5	.14					
2977.5 - 2979.5	.11					
3129.5 - 3134.5	.029					
3134 - 3138.5	.029					
3175 - 3178	.018					
3178 - 3181	.036					
3181 - 3183	.048					
3183 - 3185	.078					
3185 - 3187	.057					
3187 - 3189	.220					
3189 - 3190	.150					
3190 - 3195	.048					
3195 - 3199.5	.027					
1180 - 1184.5	.08	.73	2.03		.002	.30
1186 - 1191	.05	.50	.92		.003	.22
1197 - 1200	.05	1.15	1.85		.002	.40

CHARLESTON MINING PROPERTY
Assay Summary
Drill Hole #4

Footage	Percentage							oz/ton				ppm		
	Cu	Pb	Zn	Ni	Co	S	MoS_2	Pd	Pt	Ag	Au	Mo	Co	Ni
1180 -1184	.005	.005	.010							.20	.001	4		
1478 -1479.5	.350	1.160	9.200							.90	.001	2		
1478 -1480	.410	1.05	8.90	.010	.006					.78				
1479.5-1481	.012	.1	.12	.012	.005					.04				
1479 -1501	.02	.71	1.48			2.62		.0013	.0014	.58	.0010			
1479.5-1481	.008	.022	.100							.15	.001	2		
1481 -1486	.069	.1	1.31	.009	.008					.08				
1481 -1486	.049	.031	1.600							.15	.001	25		
1485 -1487	.080	1.32	2.50	.008	.008					.13				
1486 -1487	.056	1.345	2.800							.30	.001	1		
1487 -1494	.009	.1	.39	.010	.008					.02				
1487 -1494	.006	.060	.310							.10	.001	3		
1494 -1496	.136	1.05	1.18	.012	.010					.27				
1494 -1496	.140	1.090	1.600							.15	.001	10		
1496 -1498	.024	.10	.10	.011	.033					.02				
1496 -1498	.015	.051	.086							.10	.001	5		
1498 -1501	.247	1.37	2.85	.011	.006					.38				
1498 -1501	.220	1.275	2.400							.40	.001	10		
1590 -1591	.029	.142	.440							.20	.001	6		
1611 -1616	.160	.222	.83							.20	.001	2		
1611 -1616	.14	.19	.83			1.39		.0014	.0016	.09	.001			
1729	.01	.10	.095			1.19		.0021	.0023	.09	.001			
1762 -1773	.290	.013	.074							.15	.001	3		
1762 -1830	1.53	.17	.13			2.26		.0025	.0026	1.46	.0038			
1791 -1796	7.70	.58	.81			8.88		.0018	.0018	5.84	.0018			
1791.5-1802	.029	.049	.073							.80	.001	45		
1791.5-1802	5.40	.24	.58	.010	.004					5.25	.002			
1791.5-1802	4.950	.234	.450							.50	.001	50		
1802 -1810	.048	.1	.05	.009	.002					.11				
1802 -1810	.052	.008	.028							.10	.001	20		
1810 -1817.5	1.59	.1	.10	.009	.005					.74				
1810 -1817.5	1.800	.029	.100							.75	.001	75		
1817.5-1822	1.400	.016	.048							.45	.001	30		
1817.5-1822	1.16	.1	.05	.011	.006					.27				
1852.5-1853.5	.020	.440	.480							.20	.001	5		
1890	.02	.32	1.93			1.22		.0018	.0018	.88	.001			
1895 -1898	.28	.25	5.3							1.3	.001	2		

Footage	Percentage							oz/ton				ppm		
	Cu	Pb	Zn	Ni	Co	S	MoS_2	Pd	Pt	Ag	Au	Mo	Co	Ni
1895.5-1898.5	2.98	.26	6.40	.009	.010		.05			1.39				
1898 -1902	.18	.48	2.7							1.5	.001	2		
1896 -1903	.53	.46	13.9			7.73		.0016	.0016	2.04	.001			
1898.5-1902	.245	.37	2.00	.009	.006					1.26				
1902 -1903	.54	.40	10.0							2.2	.001	1		
1902 -1903	.365	.37	10.00	.008	.011		.05			2.16				
2023 -2025	.11	.005	.08							.1	.001	2		
2097 -2099	.78	.15	15.1							2.0	.003	1		
2097 -2099	1.15	.26	13.4			8.23		.0018	.0023	2.34	.0015			
2097.5-2099	.690	.13	17.0	.009	.018					2.02				
2099 -2101	.08	.02	2.9							.4	.002	1		
2101 -2104	.46	.03	4.0							.5	.002	1		
2099 -2104	.21	.04	1.41			.88		.0021	.0030	.088	.001			
2183 -2190	.49	.06	12.0			6.66		.0016	.0018	.58	.001			
2183.5-2190	.67	.03	8.2							.8	.002	1		
2230 -2232	.68	.03	2.4							.4	.001	3		
2230.5-2231.5	.700	.02	1.90	.009	.005					.42				
2231 -2236	.44	.10	3.5							.8	.001	3		
2231.5-2236	.44	.10	2.80	.009	.005					.67				
2249 -2249.5	1.30	.14	1.1							.7	.002	10		
2276 -2278	.004	.018	.02							.13	.002	4	90	70
2424	.01	.03	.007			3.15		.0069	.0076	.09	.0016			
2438 -2439 10"	.009	.035	17.00							.43	.002	2	50	190
2597 -2604	.365	.030	1.10							.65	.002	1	40	15
2699.5-2705.5	.080	.010	.03							.26	.002	13	40	10
1987 -1995	.05	.46	1.20							.21	.002			

#4

CARLOS ROCHIN
MANAGER
REGISTERED ASSAYER
ARIZONA REG. 7126

ROCHIN ENGINEERING AND ASSAY OFFICE

P. O. BOX 218 PHONE (AC 602) 364-8092
DOUGLAS, ARIZONA - 85607

HECTOR A. ROCHIN, Jr.
MINING ENGINEER AND
LAND SURVEYOR
ARIZONA REG. No. 2473

ASSAYERS & METALLURGICAL CHEMISTS

CERTIFICATE OF ASSAY

LOCATION:
CHARLESTON LEAD MINE
TOMBSTONE QUAD., ARIZONA

Name Western Exploration, Drawer 1217, Douglas, Arizona D.D.H. STEWART NO.5

Attn: Mr. J. Forrester		GOLD OZS	SILVER OZS	COPPER %	Pb %	Zn %	INTERVALS		BOX NO.
30800	14462	Tr	Tr	0.05$	0.25	0.79	1185	1189	129
30801	14463	Tr	Tr	0.05$	0.31	0.96	1189	1191	"
30802	14464	Tr	Tr	0.06$	0.32	0.7$	1191	1193	"
30803	14465	0.0$	0.7$	0.116	0.34	1.6$	1193	1195	"
30804	14466	Tr	0.1$	0.280	2.8$	4.27	1195	1197	"
30805	14467	Tr	0.0$	0.165	0.64	2.29	1197	1198	"
30806	14468	Tr	0.02	0.145	0.22	1.69	1198	1200	130
30807	14469	Tr	Tr	0.129	0.27	1.29	1200	1202	"
30808	14470	Tr	Tr	0.06$	0.37	1.2$	1202	1204	"
30809	14471	Tr	Tr	0.087	0.25	1.09	1204	1206	"
30810	14472	Tr	Tr	0.097	0.25	1.00	1206	1208	"
30811	14473	Tr	Tr	0.107	0.32	1.0$	1208	1210	131
30812	14474	Tr	Tr	0.07$	Tr	1.1$	1210	1212	"
30813	14475	Tr	Tr	0.07$	Tr	0.9$	1218	1220	132
30814	14476	Tr	Tr	0.089	Tr	1.2$	1220	1222	"
30815	14477	Tr	0.02	0.097	Tr	1.86	1222	1224	"
30816	14478	Tr	0.02	0.07$	Tr	1.97	1224	1226	"
30817	14479	Tr	0.1$	0.107	Tr	1.19	1226	1228	"
30818	14480	Tr	Tr	0.087	Tr	1.27	1228	1233	133
30819	14481	Tr	Tr	0.06$	Tr	Tr	1233	1237	"
30820	14482	0.02	12.32	0.087	Tr	Tr	1237	1242	"
30821	14483	Tr	Tr	0.079	Tr	Tr	1242	1243	"
30822	14484	Tr	Tr	0.06$	Tr	Tr	1281	1282	138

REMARKS:

DATE: November 19, 1970

CHARGES: $ 264.50

CARLOS ROCHIN
MANAGER
REGISTERED ASSAYER
ARIZONA REG. 7126

ROCHIN ENGINEERING AND ASSAY OFFICE

P. O. BOX 218 PHONE (AC 602) 364-8092
DOUGLAS, ARIZONA - 85607

HECTOR A. ROCHIN, Jr.
MINING ENGINEER AND
LAND SURVEYOR
ARIZONA REG. No. 2473

ASSAYERS & METALLURGICAL CHEMISTS

CERTIFICATE OF ASSAY

LOCATION:
CHARLESTON MINE
TOMBSTONE QUAD., ARIZONA
D.D.H. STEWART No. 5

Name Western Exploration, Drawer 1217, Douglas, Arizona

		GOLD OZS	SILVER OZS	COPPER %	Pb %	Zn %		INTERVALS	BOX No.
30823	14485	Tr	Tr	0.068	tr	tr	CORE	1323 - 1325	143
30824	14486	Tr	Tr	0.058	0.10	tr		1325 - 1327	"
30825	14487	Tr	Tr	0.068	0.18	tr		1327 - 1329	"
30826	14488	0.01	1.93	0.058	0.21	0.80		1329 - 1331	"
30827	14489	Tr	0.04	0.068	0.15	tr		1331 - 1332	"
30828	14490	Tr	Tr	0.087	tr	0.50		1389 - 1394	150
30829	14491	Tr	0.08	0.079	tr	1.50		1394 - 1398	"
30830	14492	Tr	Tr	0.068	tr	tr		1398 - 1403	151
30831	14493	Tr	Tr	0.087	tr	tr		1403 - 1408	"
30832	14494	Tr	Tr	0.078	tr	tr		1408 - 1413	152
30833	14495	Tr	Tr	0.079	tr	tr		1413 - 1417	"
30834	14496	Tr	Tr	0.058	tr	tr		1417 - 1422	153
30835	14497	Tr	Tr	0.068	tr	tr		1422 - 1427	"
30836	14498	Tr	Tr	0.068	tr	tr		1427 - 1432	154
30837	14499	Tr	Tr	0.097	tr	tr		1432 - 1436	"
30838	14500	Tr	Tr	0.079	tr	tr		1436 - 1441	155
30839	14316	Tr	Tr	0.050	tr	tr		1441 - 1446	"
30840	14317	Tr	Tr	0.050	tr	tr		1512 - 1517	163
30841	14318	Tr	Tr	0.050	tr	tr		1517 - 1521	"
30842	14319	Tr	Tr	0.040	tr	tr		- 1605	173
30843	14320	Tr	Tr	0.040	tr	tr		1608 - 1609	"
30844	14321	Tr	Tr	0.069	tr	tr		1609 - 1624	175
30845	14322	Tr	Tr	0.050	tr	tr		1624 - 1629	"

REGISTERED ASSAYER
CERTIFICATE NO. 7128
CARLOS ROCHIN
Signed
Arizona U.S.A.

REMARKS:

DATE: 22 Nov 70

CHARGES: $ 284.50

CARLOS ROCHIN
MANAGER
REGISTERED ASSAYER
ARIZONA REG. 7126

ROCHIN ENGINEERING AND ASSAY OFFICE

P. O. BOX 218 PHONE (AC 602) 364-8092
DOUGLAS, ARIZONA - 85607

HECTOR A. ROCHIN, Jr.
MINING ENGINEER AND
LAND SURVEYOR
ARIZONA REG. No. 2473

ASSAYERS & METALLURGICAL CHEMISTS

CERTIFICATE OF ASSAY

LOCATION:
CHARLESTON LEAD MINE
TOMBSTONE QUAD., ARIZONA
D.D.H. STEWART No.5

Name Western Exploration, Drawer 1217, Douglas, Arizona

Attn: Mr. J. Forrester	GOLD OZS	SILVER OZS	COPPER %	Pb %	Zn %		INTERVALS	BOX No.
30846 14323	Tr	Tr	0.050	tr	tr	CORE	1643 - 1645	177
30847 14324	Tr	Tr	0.030	tr	tr		1645 - 1647	"
30848 14325	Tr	Tr	0.020	tr	tr		1647 - 1649	"
30849 14326	Tr	Tr	0.040	tr	tr		1649 - 1651	"
30850 14327	Tr	Tr	0.050	tr	tr		1651 - 1653	"
30851 14328	Tr	Tr	0.040	tr	tr		1653 - 1655	178
30852 14329	Tr	Tr	0.327	1.60	2.50		1655 - 1657	"
30853 14330	Tr	Tr	0.288	0.27	0.50		1657 - 1659	"
30854 14331	Tr	Tr	0.060	tr	tr		1659 - 1662	"
30855 14332	Tr	Tr	0.040	tr	tr		1662 - 1665	"
30856 14333	Tr	0.10	0.754	tr	tr		1665 - 1667	179
30857 14334	Tr	0.04	0.536	tr	tr		1667 - 1669	"
30858 14335	Tr	Tr	0.119	tr	tr		1669 - 1672	"
30859 14336	Tr	0.34	1.310	tr	tr		1672 - 1674	"
30860 14342	Tr	Tr	0.069	tr	tr		1674 - 1676	"

REGISTERED ASSAYER
CERTIFICATE NO.
7126
CARLOS
ROCHIN
Date Signed
Arizona U. S. A.

REMARKS:

DATE: 22 Nov 70

CHARGES: $ 172.50

Final depth 400'
Elevation
Coordinates
Inclination Vertical

ASARCO
GEOLOGIC LOG

Project Charleston Chs-1

✓ · minor
tr · trace

HOLE NO. Chs 1
Sheet No. 1
Date Completed
Logged by J R King

From	To	Interval	Size	Spec	Recovery %	Total % Sulf.	Diss/Fract	Mineralization					Alteration					Rock	Remarks
								Ratio	Py	Cpy	Mo	Others	Phy	Arg	Pot	Mag	Anhy		
0	22																		PLUG BIT
22	181	159	NC		+85	6-8	3/1		+				✓	+				US por	oxidized to ≈150' alter is intense, breccia cavities occas. poss small fault 181-186
181	228	47	NC		"	5-7	3/1		+				✓	+				An por	PRPB dike
228	278	50	NC		"	4-3	3/1		+				✓	+				Δ	Heterolithic breccia with open cavities
278	356	78	NC		"	7	3/1		+				+	✓				(An por) Δ	as above. less open cavities small fault 236 & 284.
356	450	94	NC		"	6-8	3/1		+				+	✓				Δ	good breccia w/ flu NATURE as w/ MIN.
450	505	55	NC		"	3-5	4/1	100/1	+	tr			+			tr		An por	mix Gd por alter becoming more chl, mag as diss & uns. poss fault 470-490
505	690	185	NC		"	5-7	3/1	100/1	+	tr			+					Δ	beautiful heterolith breccia as seen in outcrop
690	811	121	NC		"	4-6	2/1		+				+					An por	breccia in part alter decreasing in $CaCO_3$ occurring along fract.
811	831	20	NC		"	6	4/1		+				+					Gd por	less gmss, lighter colour, alter remains same intensity
831	916	85	NC		"	4-5	2/1	20/1	+	tr			+			✓		And por	somewhat fluidized & brecciated, cpy both diss & fract
916	950	34	NC		"	3-4	1/1	15/1	+	✓	?		+			tr		Gd por	well mineral but alter decreasing silic in >>

ASARCO

GEOLOGIC LOG

HOLE NO. Chs-1
Sheet No. 2
Date Completed
Logged by J. R. King

Project Charleston Chs-1

From	To	Interval	Size	Spec	Recovery %	Total % Sulf.	Diss/Fract	Mineralization					Alteration					Rock	Remarks
								Ratio	Py	Cpy	Mo	Others	Phy	Arg	Pot	Mag	Anhy		
850	860	10	NC		-25	4	1/2		+				+			tr		Δ	intrusive breccia mod to strong alter
860	1000	40	NC		+85	5	2/1		+				+			tr		Gd por	as before. small faults 967, 998.
1000	1021	21	NX		+85	5	2/1		+				+			tr		"	as above
1021	1411	390	NX		+35	3	1/2	20/1	+	tr			✓			✓	✓	An por	alter - weak to moderate chl increasing
1411	1658	247	NX		+85	2-4	1/3	15/1	+	✓			+		tr	✓	✓	Δ	intrusive heterolithic breccia. no open cavities 1507-17, 1610-12
1658	1829	171	NX		+85	2	1/1	15/1	+	tr			+			✓	✓	Gd por	as before shows several zones of brecciation good gouge 1792-1800, 1829
1829	2151	322	NX		+85	3	1/2	20/1	+	tr			+			tr	✓	Gd por	as before alter mod to strong
2151	2312	161	NX		+85	4	1/2	25/1	+	tr			+				—	Δ-Gd por	variable por & breccia, alter strong
2312	2392	80	NX		+85	5	1/1	30/1	+	tr		? GN	+				+	Gd por	small fault - 2307 alter strong
2392	2617	225	NX		+25	4	1/2	15/1	+	✓			+			✓	✓	Δ-Gd por	as above alter mod - strong heterolith breccia in part, some stockwork veining.
2617	2879	262	NX		+85	3	1/3	10/1	+	✓			+		tr	tr	tr	Δ	Heterolith breccia & gd por - mix - an por alter mod to strong
2879	2947	68	NX		+85	2	1/4	20/1			?		+		tr	✓	tr	Gd por	as before alter wk to mod.
			END OF HOLE																

ASARCO

GEOLOGIC LOG

Depth
vation
dinates
nation

Project Charleston Chs-1

HOLE NO. Chs 1
Sheet No. 3
Date Completed
Logged by J.R.K. & S.R.D.

From	To	Interval	Size	Spec	Recovery %	Total % Sulf.	Diss/Fract	Mineralization					Alteration					Rock	Remarks
								Ratio	Py	Cpy	Mo	Others	Phy	Arg	Pot	Mag	Anhy		
2947	3005	58	Bx		+85	2	1/4	20/1	+	⌐	?		+		?	+r		Gd por	as before (in por 2947), alteration weak to moderate
3005	3038	33	Bx		+70°	2	?											cataclastic - broken - faulted	
3038	3469	431	Bx		+85°	1-2	1/4	10/1	+	⌐			+		+r	⌐		Gd por -	mix An por, alter weak to moderate, cpy more abundant
3469	3605	136	Bx		+85	2	1/3	7/1	+	⌐	?		+		⌐	+r		Gd por -	mix An por as above. some zones of better cpy
3605	3656	51	Bx		+65	2	1/2	20/1	+	+r								fault	zone
3656	3749	93	Bx		+85	1-2	1/1	30/1	+	+r			+		⌐	+r		Gd por	with some zones of An por (3600-14). alteration weak
3749	3890	141	Bx		+85	1	1/2	15/1	+	⌐	?		+		⌐	+r		Gd por	as above, small fault 3892 alter weak
3890	4002	52	Bx		+85	2	1/2	10/1	+	⌐	?		+		⌐	⌐		Gd por -	mix an por as before alteration weak small fault 3913, 3922.
	TD																		

ASARCO

GEOLOGIC LOG

+ abund
✓ minor
tr trace

ol depth -3405 Range 5023
evation
ordinates
tination Vertical

Project Charleston Chs-2

HOLE NO. Chs-2
Sheet No.
Date Completed
Logged by J R Kay - S R

From	To	Interval	Size	Spec	Recovery %	Total % Sulf.	Diss/Fract	Mineralization					Alteration					Rock	Remarks
								Ratio	Py	Cpy	Mo	Others	Phy	Arg	Pot	Mag	Anhy		
0	21																		Plug Bit
21	182		NC		+85	?	? 1/3	-					✓	+				Lus por	oxidized, with dikes of And por 80-100 132-159, alter is mod in Lus por, wk in And por numer small faults 30, 80-85, 103, 132-133, CO_3
182	619?		NC		+85	1-3	20/1		+				✓	+				Lus por "Uncle Sam"	as above, alter variable wk-mod, An por dikes 182-274-287, 429-463, pebble dikes freq assoc w/ above. Faults 166, 195-208, 219-221, 267-274, 289, 310, 376-403, 447, 460,
619	1226		Nc		+35	1-3	20/1		+			tr GN Sph	+	+				Kbv	Bronco volcanics contact approx, alter moderate min se weaker. An por 768-808, 919-923, 942-1166 breccia 118 1226 - strong alter
			↓																
			1013																
			Nx																
1226	1327		Nx		+90	1	20/1		+	tr		tr GN Sph	✓	+				An por	dike - variable alt w/ some epidote
1327	1355		Nx		+90	1-2	10/1		+				✓	+				Bisbee	sediments, silts - Bedding 10°, alter weak to mod.
1355	1407		Nx		+95	1	20/1		+					+				An por	as above, epidote common, min weak

depth
ation
dinates
ation

ASARCO

GEOLOGIC LOG

HOLE NO. Chs-2
Sheet No. 2
Date Completed
Logged by JRK + S.R.B.

Project Charleston Chs-2

From	To	Interval	Size	Spec	Recovery %	Total % Sulf.	Diss/Fract	Mineralization					Alteration					Rock	Remarks
								Ratio	Py	Cpy	Mo	Others	Phy	Arg	Pot	Mag	Anhy		
1807	1853		NX		+95	≥1	20/1		+				+tr	✓				Bisbee	[illegible] Hci mudstones alt weak to mod; fault 1560-1579 1588 1646 pebble dike 1709 bedding 7°
1853	1874		NX		+95	1	20/1		+					+				An por	[illegible]
1874	2210		NX		+95	≥1	25/1		+	?		+tr ? GN		✓			✓	Bisbee	sediment - as above alter weak pass flourite fault 2187 92, bedding 10°
2210	2268		NX		95	1-2	20/1		+					+			+	An por	breccia - pebble dike in part, Bisbee frags in A. strong anhydrite VNING
2268	2307		NX		95	≥1	10/1		+					+				Bisbee	as above, nodular mudstones, siltstone sandstone bedding 12° dip
2307	2352		NX		95	2-4	10/1		+				+	+				Peb dike	- fault zone
2352	2949		NX		95	1-4	10/1		+	+tr		+tr GN [illegible]	✓	+				Bisbee	as above alter weak - mod bedding 15° numerous An & biotite dikes, 2420-2503-40. 2572-76 2592-2625, 2671-27[illegible] 2878-2903 epi [illegible]
2949	3033		2002 BX		25	3-6	10/1						+	✓		+tr	✓	Anpor-	Gd por alter mod [illegible] bounded by a fault involves both sediment & intrusive rocks
3033	3093		Bx		65													FAULT	

ASARCO

GEOLOGIC LOG

l depth 3405
ation
dinates
nation

Project Charleston Chs-2

HOLE NO. Chs-2
Sheet No. 3
Date Completed
Logged by LRK

om	To	Interval	Size	Spec	Recovery %	Total % Sulf.	Diss/Fract	Mineralization					Alteration					Rock	Remarks
								Ratio	Py	Cpy	Mo	Others	Phy	Arg	Pot	Mag	Anhy		
3093	3245		BX		+90	1-4	15/1		+	tr		±tr GN tr	✓	✓		±✓	✓	BISBEE	limey siltstones alter mod bedding 5° dike at 3112 3149
3245	3260		BX		+90	2-4	5/1	50/1	+	tr			+		±✓		±tr	An por	as before alter strong
3260	3415		BX		+90	1-4	5/1		+	tr		tr GN SPH	✓	+			tr	BISBEE	silt st, limey silt limest minor cg. alter is mod, epi common silicification
							lost hole due to water at 3030 ft;											wedge set for Chs-2W at 3495	

ASARCO

GEOLOGIC LOG

HOLE NO. Chs-2W
Sheet No. 4
Date Completed
Logged by JRK

l depth 5028
vation
rdinates
nation Vertical ?

Project Charlestown Chs-2

From	To	Interval	Size	Spec	Recovery %	Total % Sulf.	Diss/Fract	Mineralization					Alteration					Rock	Remarks
								Ratio	Py	Cpy	Mo	Others	Phy	Arg	Pot	Mag	Anhy		
Wedge			NX																
2495	3415		3202 BX ↓		90														as described on page three
3415	3895		BX		90	1-2	1/3		+	+tr	+tr	GN	+	✓			✓	BISBEE	siltst limesilt, sandst epidote garnet alter med to strong
3895	4075		Bx		~90	1-2	1/2		+				+		+tr			An por	Gd por silicification noted
4075	4493		Dx		+90	1	1/1		+	+tr	+tr	GN	+		?		+	BISBEE	siltst alter strong silicification bedding 10°
4493	4828		Bx		+90	≥1	2/1		+	+tr	+tr	GN	✓	✓				BISBEE	limest, congl alter wk to mod silicificat variable bedding 10°
4828	4959		Bx		+85	≥1	2/1		+		+tr	GN						Paleozoic	marble alter is weak bedding 5°
4959	4980		4985 AX ↓		+90	2-4	3/1		+				+					An por	fine grained mod alteration poor core recovery silicificat noted
4980	5028		AX		+90	.5-2	3/1		+	+tr		GN						Paleozoic	marble as before contact poor core recovery alteration wk, bedding 5° small fault 5027-28

ASARCO
GEOLOGIC LOG

tr trace
✓ minor
\+ abundant

[illegible] depth 3303
[illegible]ation
[illegible]dinates
[illegible]nation Vertical

Project Charleston

Chs-3

HOLE NO. Chs-3
Sheet No. 1
Date Completed
Logged by John R. [illegible]

From	To	Interval	Size	Spec	Recovery %	Total % Sulf.	Diss/Fract	Ratio	Py	Cpy	Mo	Others	Phy	Arg	Pot	Mag	Anhy	Rock	Remarks
0	23																		Plug B,F
23	115	92	NC		+80	? 1-4	–	–	+				+	+				Δ	Breccia w/ open cavity
																			oxidation to ≈ 150'
																			pred por [illegible] + US por [illegible]
115	210	95	NC		+80	1-3	3/1		+					+				Dac por	dac→gd; phenos of
																			PLAG, Hb, Qtz Mca P[illegible]
																			alter [illegible]
																			bottom 10' [illegible]
210	560	350	NC		+75	3-6	5/1		+				+	✓				Gd por Δ	breccia in part, py-
																			filling some cavities
																			alteration - strong
																			faulting - 225, 255, 31[illegible]
																			335, 355, 458, 470, 5[illegible]
560	610	50	NC		+85	3-6	4/1		+									Gd por	as before except
			631																relative [illegible]
610	1070	460	NX		+85	2-5	3/1	100/1	+	tr		tr BN	+			tr	tr	Δ	heterolithic igneous
																			breccia [illegible]
																			frag. alter - strong
																			minor open cavit. Δ
1070	1093	23	NX		+85	2-3	5/1		+				+					Dac por	as above except
																			no py phenos [illegible]
																			plag hb qtz.
1093	1104	11	NX		+85	2-3	2/1		+				+					Δ	heterolithic breccia as
																			above alter is
																			decreasing
1104	1266	162	NX		+90	2-3	10/1		+			tr BN SPH	+				✓	Qtz Mz Por	with strong py
																			dissem plag [illegible]
																			[illegible] fault
																			at 1260 otherwise [illegible]
																			[illegible]
																			sulfide VNING is
																			[illegible] NONEXIST[illegible]

al depth 3003
vation
rdinates
ination

ASARCO

GEOLOGIC LOG

Project Charleston Chs-3

HOLE NO. Chs-3
Sheet No. 2
Date Completed
Logged by IRK

rom	To	Interval	Size	Spec	Recovery %	Total % Sulf.	Diss/Fract	Mineralization					Alteration					Rock	Remarks
								Ratio	Py	Cpy	Mo	Others	Phy	Arg	Pot	Mag	Anhy		
1266	1484	218	NX		+25	2	3/1	25/1	+	tr			+		tr	tr	✓	Gd-Por	with disseminated py [illegible] also plag [illegible] faulting 1278, 1302 some brecciation [illegible] 1453-1484
1484	1516	32	NX		+90	2	3/1	20/1	+	✓		tr GN	+			tr	✓	A	Heterolithic [illegible] breccia with [illegible]
1516	1587	71	NX		+95	1	4/1	20/1	+	✓			✓			tr	✓	An por	alter definitely decreasing [illegible] of An por of Chs-1
1587	1930	343	NX		+95	1-2	4/1	20/1	+	✓			✓			✓	✓	Gd-por	with [illegible] K spar [illegible], alter wk to strong [illegible] ser twinning [illegible] An por mix 1830-1930
1930	2103	173	NX		+95	1	8/1	15/1	+	✓			✓		tr	✓	✓	Gd-por	[illegible] relatively unjointed K-pheno [illegible]
2103	2340	237	NX		+95	≤1	4/1	10/1	+	✓			✓		✓	✓	✓	Gd por	mix and por quite possibly an intrusive breccia zone
2340	2501	399	NX		+95	1	2/1	15/1	+	✓			✓		✓	✓	tr	Gd por-	mix and por both rocks with K-spar phenos; in part rock shows definite intrusive brecciation qtz veining & veinlets prevalent

ASARCO

GEOLOGIC LOG

l depth 3003
vation
dinates
nation

Project Charleston Chs-3

HOLE NO. Chs-3
Sheet No. 3
Date Completed
Logged by JRK

om	To	Interval	Size	Spec	Recovery %	Total % Sulf.	Diss/Fract	Mineralization					Alteration					Rock	Remarks
								Ratio	Py	Cpy	Mo	Others	Phy	Arg	Pot	Mag	Anhy		
2501	2910	[illegible]	NX		~95	2	3/1	10/1	+	✓			+		✓	✓	✓	HYBRID	[illegible] alter mod to strong. rock is weakly por in places not seen in Chs holes before breccia in places fault 3254
2910	3003	93	NX		~95	≤1	2/1	15/1	+	✓			tr		tr	tr	tr	Gd por	very fresh, with K-spar phenos alter weak, [illegible] to chlorite.
		TD																	

Chs-1 - Table of Compos. Assays

0-1100	1100'	Approx.	.03% Cu or less				
1100-1650	550'	"	.09% Cu				
1650-2525	875'	"	.05% Cu or less				
2525-2665	140'		.15%	350'	.18%	455'	.16%
2665-2875	210'		.195%				
2875-2980	105'		.12%				
2980-3180	200'		.05%				
3180-3365	185'		.135%	425'	.19%		
3365-3605	240'		.233%				
3605-3905	300'		.053%				
3905-4002	97'		.169%				
2525-4002	1477'		.133%				

CHARLESTON PROJECT
Hole Chs-1

Depth	Cu	Mo	Pb	Zn
68-75	25	10	30	20
143-152	40	8	30	25
164-169	310	4	25	30
194-199	105	4	75	125
321-326	255	6	120	100
398-403	255	16	110	185
520-528	300	8	45	70
591-599	280	10	40	130
692-700	180	4	105	200
792-800	450	8	25	95
923-933	330	14	60	80
983-993	400	30	60	50
1087-1097	600	14	25	20
1257-1267	850	36	45	60
1347-1357	750	40	45	60
1442-1452	950	22	50	55
1552-1562	900	18	40	35
1632-1642	1350	14	35	20
1745-1754	20	22	30	5
1857-1867	235	2	15	10
1948-1958	610	6	35	40
1996-2006	475	4	20	5
2041-2051	135	30	20	5
2124-2134	1200	12	20	5
2207-2217	60	<2	10	5
2280-2290	630	2	10	10
2380-2390	620	10	10	5
2455-2465 10	1150	20	10	10
2525-2535 10	0.19%	12	1000	85
2612-2622 10	0.19%	18	20	20
2684-2694 10	0.19%	22	20	20
2787-2797 10	0.13%	16	15	15
2844-2854 10	0.41%	16	15	20
2919-2929	950	10	25	15
3011-3021 10	425	<2	15	15
3102-3112	495	2	10	15
3231-3241 10	1300	<2	10	30
3305-3315 10	0.20%	6	15	40
3401-3411 10	0.25%	10	15	15
3459-3469 10	0.21%	<2	10	35
3545-3554 9	0.23%	14	10	85
3626-3636	500	6	85	110
3710-3719	430	6	220	240
3849-3858 9	0.23%	18	15	35
3905-3914 9	0.26%	4	45	160
3979-3988 9	0.20	4	25	65
3992-4002 10	0.16	4	20	230

.18% - 474' 400'

.20 - 323' 325'

153'

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION	Ag ppm	Cu ppm	Pb ppm	Zn ppm	Mo ppm	As ppm
1	Chs-1 68-75	<0.2	25	30	20	10	
2	143-152	<0.2	40	30	25	8	
3	164-169 tr Cc ?	<0.2	310	25	30	4	
4	194-199		105	75	125	4	
5	321-326		255	120	100	6	5
6	Chs-1 398-403	<0.2	255	110	185	16	

oxidized

sulfide

J. R. K.
APR 2[illegible] 1974

TO:
American Smelting & Refining Company
Southwestern Exploration Division
P.O. Box 5747
Tucson, Arizona 85703

Attn.: Mr. J. R. King

REMARKS:
Trace analysis

CERTIFIED BY: William L. Lehmbeck

REGISTERED ASSAYER — CERTIFICATE NO. 9425 — WILLIAM L. LEHMBECK — DATE SIGNED 4/24/74 — ARIZONA U.S.A.

DATE REC'D:	DATE COMPL.:	JOB NUMBER:
4/20/74	4/24/74	740711

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION	Au ppm	Ag ppm	Cu ppm	Pb ppm	Zn ppm	Mo ppm			
1	CP-1 240-250		<0.2	15	50	185	2			
2	CP-1 330-350		0.2	15	65	180	2			
3	CP-1 370-395		<0.2	15	25	90	2			
4	Chs-2 4351-4356	<0.02	<0.2	10	45	40	8			
5	4470-4479	<0.02	<0.2	100	5	30	2			
6	4742-4747	<0.02	<0.2	15	65	70	2			
7	4971-4980	<0.02	<0.2	25	15	50	24			
8	Chs-2 5012-5021	<0.02	<0.2	35	50	320	2			

REGISTERED ASSAYER CERTIFICATE NO. 9425 WILLIAM L. LEHMBECK

TO: American Smelting & Refining Company

REMARKS: Trace Analysis

CERTIFIED BY:

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION	Au ppm	Ag ppm	Cu ppm	Pb ppm	Zn ppm	Mo ppm			
1	CHS-1 520-528			300	45	70	8			
2	591-599			280	40	130	10			
3	692-700			180	105	200	4			
4	792-800			450	25	95	8			
5	CHS-1 923-933	<0.02	<0.2	330	60	80	14			

D:
American Smelting & Refining Company
Southwestern Exploration Division
P.O. Box 5747
Tucson, Arizona 85703

Attn.: Mr. J. R. King

REMARKS:
Trace analysis

CERTIFIED BY:

DATE REC'D:	DATE COMPL.:	JOB NUMBER:
4/26/74	4/30/74	740759

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION	Cu ppm	Pb ppm	Zn ppm	Mo ppm
1	CHS-1 983-993	400	60	50	30
2	CHS-1 1087-1097	600	25	20	14
3	CHS-1 1257-1267	850	45	60	36
4	CHS-1 1347-1357	750	45	60	40

TO:

American Smelting & Refining Company
Southwestern Exploration Division
P.O. Box 5747
Tucson, Arizona 85703

Attn.: Mr. J. R. King

REMARKS:

Trace analysis

CERTIFIED BY:

DATE REC'D:	DATE COMPL.:	JOB NUMBER:
5/2/74	5/7/74	740816

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION		Cu ppm	Pb ppm	Zn ppm	Mo ppm
1	CHS-1	1442-1452	950	50	55	22
2		1552-1562	900	40	35	18
3		1632-1642	1350	35	20	14
4	CHS-1	1745-1754	20	30	5	22

American Smelting & Refining Company
Southwestern Exploration Division
P.O. Box 5747
Tucson, Arizona 85703

Attn.: Mr. J. R. King

REMARKS:

Trace analysis

CERTIFIED BY:

DATE REC'D:	DATE COMPL.:	JOB NUMBER:
5/9/74	5/14/74	740857

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION	Au ppm	Ag ppm	Cu ppm	Pb ppm	Zn ppm	Mo ppm
1	CHS-1 1857-1867			235	15	10	2
2	1948-1958			610	35	40	6
3	1996-2006			475	20	5	4
4	2041-2051	<0.02	<0.2	135	20	5	30
5	CHS-1 2124-2134			1200	20	5	12

D:

American Smelting & Refining Company
Southwestern Exploration Division
P.O. Box 5747
Tucson, Arizona 85703

Attn.: Mr. J. R. King

REMARKS:

Trace analysis

CERTIFIED BY: Charles E. Thompson

DATE REC'D:	DATE COMPL.:	JOB NUMBER:
5/17/74	5/22/74	740923

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION	Au ppm	Ag ppm	Cu ppm	Pb ppm	Zn ppm	Mo ppm	As ppm		
1	CHS-1 2207-2217			60	10	5	< 2			
2	2280-2290			630	10	10	2			
3	2380-2390	<0.02	<0.2	620	10	5	10	28		
4	CHS-1 2455-2465			1150	10	10	20			

D:
American Smelting & Refining Company
Southwestern Exploration Division
P.O. Box 5747
Tucson, Arizona 85703

Attn : Mr. John R. King

REMARKS:
Trace analysis

CERTIFIED BY:

DATE REC'D:	DATE COMPL.:	JOB NUMBER:
5/31/74	6/6/74	741018

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION	Cu %	Pb ppm	Zn ppm	Mo ppm					
1	CHS-1 2612-2622	0.19	20	20	18					
2	CHS-1 2525-2535	0.19	1000	85	12					

TO:
American Smelting & Refining Company
Southwestern Exploration Division
P.O. Box 5747
Tucson, Arizona 85703

Attn.: Mr. John R. King

REMARKS:
Trace analysis
Copper - single analysis

CERTIFIED BY:

REGISTERED ASSAYER — Arizona U.S.A.

DATE REC'D:	DATE COMPL.:	JOB NUMBER:
6/7/74	6/13/74	741062

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION	Ag ppm	Cu ppm	Cu %	Pb ppm	Zn ppm	Mo ppm	As ppm		
	Series Chs-1:									
1	2684-2694		>2000	0.19	20	20	22			
2	2787-2797		>2000	0.13	15	15	16			
3	2844-2854		>2000	0.41	15	20	16			
4	2919-2929	< 0.2	950		25	15	10			
5	2525-2535 (from 741062)	< 0.2						5		

D:
American Smelting & Refining Co.
Southwestern Exploration Division
P. O. Box 5747
Tucson, Arizona 85703

Attn: Mr. John R. King

REMARKS:
Trace analysis
3 Copper single analysis

CERTIFIED BY:

REGISTERED ASSAYER CHEMICAL CALIFORNIA STATE OF ARIZONA DATE SIGNED 6/17/74 Arizona U. S. A.

DATE REC'D:	DATE COMPL.:	JOB NUMBER:
6/13/74	6/17/74	741098

SKYLINE LABS, INC.
Hawley & Hawley Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION		Au ppm	Cu ppm	Cu %	Pb ppm	Zn ppm	Mo ppm
1	Chs-1	3011-3021	<0.02	425		15	15	< 2
2		3102-3112		495		10	15	2
3		3231-3241		1300		10	30	< 2
4		3305-3315		>2000	0.20	15	40	6
5		3401-3411	<0.02	>2000	0.25	15	15	10
6	Chs-1	3459-3469	<0.02	>2000	0.21	10	35	< 2

TO:
American Smelting & Refining Company
Southwestern Exploration Division
P.O. Box 5747
Tucson, Arizona 85703

Attn : Mr. W. J. Kurtz

REMARKS:
Trace analysis
3 Copper - single analysis

CERTIFIED BY: William L. Lehmbeck

DATE REC'D: 6/28/74
DATE COMPL.: 6/29/74
JOB NUMBER: 741212

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION		Cu ppm	Cu %	Pb ppm	Zn ppm	Mo ppm				
1	Chs-1	3545-3554	>2000	0.23	10	25	14				
2	Chs-1	3626-3636	500		85	110	6				
3	Chs-1	3710-3719	435		220	240	6				

TO:
American Smelting & Refining Company
Southwestern Exploration Division
P.O. Box 5747
Tucson, Arizona 85703

Attn.: Mr. Steven R. Davis

REMARKS:

CERTIFIED BY:

DATE REC'D:	DATE COMPL.:	JOB NUMBER:
7/5/74	7/9/74	741246

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION	Cu %	Pb ppm	Zn ppm	Mo ppm
1	Chs-1 3849-3858	0.23	15	35	18
2	Chs-1 3905-3914	0.26	45	160	4

J. R. K.
JUL 19 1974

REGISTERED ASSAYER CERTIFICATE NO. 9425 WILLIAM L. LEHMBECK DATE SIGNED 7/19/74 Arizona U. S. A.

TO:
American Smelting & Refining Company
Southwestern Exploration Division
P.O. Box 5747
Tucson, Arizona 85703

Attn.: Mr. S.R. Davis

REMARKS:

CERTIFIED BY: William L. Lehmbeck

DATE REC'D:	DATE COMPL.:	JOB NUMBER:
7/9/74	7/12/74	741282

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION	Cu %	Pb ppm	Zn ppm	Mo ppm	Au	Ag	As		
1	Chs-1 3979-3988	0.20	25	65	4					
2	Chs-1 3992-4002	0.16	20	230	4					

running for Au Ag As

J. R. K.

JUL 19 1974

REGISTERED ASSAYER CERTIFICATE NO. 9425 WILLIAM L. LEHMBECK ARIZONA U.S.A.

CERTIFIED BY: William L. Lehmbeck DATE: 7/16/74

TO:
American Smelting & Refining Company
Southwestern Exploration Division
P.O. Box 5747
Tucson, Arizona 85703

Attn.: Mr. S. R. Davis

REMARKS:

DATE REC'D:	DATE COMPL.:	JOB NUMBER:
7/11/74	7/16/74	741301

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION	Au ppm	Ag ppm	As ppm
1	Chs-1 3979-3988	<0.02	0.6	< 1
2	Chs-1 3992-4002	<0.02	0.8	< 1

TO:

American Smelting & Refining Company
Southwestern Exploration Division
P.O. Box 5747
Tucson, Arizona 85703

Attn.: Mr. S.R. Davis

REMARKS:

Trace analysis

CERTIFIED BY:

William L. Lehmbeck

7/29/74

DATE REC'D:	DATE COMPL.:	JOB NUMBER:
	7/29/74	741301-A

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Arizona Registered Assayer No. 9427
William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION		Cu %
1	CHS - 1	2535-2545	0.08
2		2545-2555	0.09
3		2555-2565	0.20
4		2565-2575	0.15
5		2575-2585	0.13
6		2585-2595	0.16
7		2595-2605	0.08
8		2605-2612	0.15
9		2622-2632	0.14
10		2632-2642	0.13
11		2642-2652	0.21
12	CHS - 1	2652-2662	0.17

TO: American Smelting & Refining Co.
Southwestern Exploration Division
P. O. Box 5747
Tucson, Arizona 85703

Attn: Mr. W. L. Kurtz

REMARKS: Single determinations

CERTIFIED BY: William L. Lehmbeck

REGISTERED ASSAYER CERTIFICATE NO. 9425 WILLIAM L. LEHMBECK DATE SIGNED 8/13/74 ARIZONA U.S.A.

DATE REC'D:	DATE COMPL.:	JOB NUMBER:
8/5/74	8/13/74	741520

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Arizona Registered Assayer No. 9427
William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION	Cu %
	Series CHS-1	
1	2662-2672	0.11
2	2672-2684	0.11
3	2694-2705	0.30
4	2705-2715	0.15
5	2715-2725	0.16
6	2725-2735	0.18
7	2735-2745	0.21
8	2745-2755	0.21
9	2755-2765	0.17
10	2765-2775	0.19
11	2775-2787	0.25
12	2797-2807	0.22
13	2807-2817	0.20
14	2817-2827	0.22
15	2827-2837	0.18
16	2837-2844	0.17

J. R. K.

AUG 2 3 1974

0060

JRK

TO:
American Smelting & Refining Co.
Southwestern Exploration Division
P.O. Box 5747
Tucson, Arizona 85703

Attention: Mr. John R. King

REMARKS:
Single determinations

CERTIFIED BY:

REGISTERED ASSAYER CERTIFICATE NO. 9425 WILLIAM L. LEHMBECK TUCSON, ARIZONA

8/23/74

DATE REC'D:	DATE COMPL.:	JOB NUMBER:
8/22/74	8/23/74	741656

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

J. P. K

AUG 29 1974

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION		Cu %
1	CHS - 1	2854-2865	0.26
2		2865-2875	0.24
3		2875-2885	0.15
4		2885-2895	0.18
5		2895-2905	0.12
6		2905-2915	0.10
7		2915-2919	0.10
8		2929-2940	0.14
9		2940-2950	0.12
10		2950-2960	0.12
11		2960-2970	0.11
12		2970-2980	0.09
13		2980-2990	0.05
14		2990-3000	0.05
15		3000-3011	0.05
16		3021-3030	0.03
17		3030-3040	0.05
18		3040-3050	0.04
19		3050-3060	0.04
20		3060-3070	0.04
21		3070-3080	0.04
22		3080-3090	0.10
23		3090-3103	0.08
24		3112-3120	0.06
25		3120-3130	0.04
26		3130-3140	0.09
27		3140-3150	0.09
28	CHS - 1	3150-3160	0.09

TO:
American Smelting & Refining Company
Southwestern Exploration Division
P.O. Box 5747
Tucson, Arizona 85703

Attn.: Mr. John King

REMARKS:
Single analysis

CERTIFIED BY: William L. Lehmbeck

REGISTERED ASSAYER CERTIFICATE NO. 9425 WILLIAM L. LEHMBECK ARIZONA U.S.A.

DATE REC'D:	DATE COMPL.:	JOB NUMBER:
8/26/74	8/29/74	741694

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION		Cu %
1	CHS-1	3160-3170	0.05
2		3170-3180	0.05
3		3180-3190	0.13
4		3190-3200	0.12
5		3200-3210	0.10
6		3210-3220	0.14
7		3220-3232 *	0.11
8		3242-3250 **	0.09
9		3250-3260	0.16
10		3260-3270	0.08
11		3270-3280	0.10
12		3280-3290	0.14
13		3290-3305	0.20
14		3315-3325	0.19
15		3325-3335	0.20
16		3335-3345	0.09
17		3345-3355	0.06
18		3355-3365	0.15
19		3365-3375	0.20
20		3375-3385	0.22
21		3385-3401	0.25
22		3411-3420	0.25
23		3420-3430	0.20
24		3430-3440	0.09
25		3440-3450	0.16
26		3450-3459	0.18
27		3469-3480	0.26
28		3480-3490	0.24
29		3490-3500	0.28
30		3500-3510	0.19
31		3510-3520	0.29
32		3520-3530	0.15
33		3530-3545	0.33
34		3554-3565	0.26
35	CHS-1	3565-3575	0.16

TO:
American Smelting & Refining Company
P.O. Box 5747
Tucson, Arizona 85703

Attn.: Mr. S. R. Davis

REMARKS:

* Sample marked 3220-3231
** Sample marked 3241-3250

CERTIFIED BY:

DATE REC'D:	DATE COMPL.:	JOB NUMBER:
9/13/74	9/23/74	741873

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION		Cu %								
36	CHS-1	3575-3585	0.35								
37		3585-3595	0.32								
38		3595-3605	0.22 — fault								
39		3605-3615	0.07								
40		3615-3626	0.09								
41		3636-3645	0.05								
42		3645-3655	0.02								
43		3655-3665	0.04								
44		3665-3675	0.03								
45		3675-3685	0.01								
46		3685-3695	0.01								
47		3695-3710	0.03								
48		3719-3730	0.07								
49		3730-3740	0.01								
50		3740-3750	0.02								
51		3750-3760	0.03								
52		3760-3770	0.03								
53		3770-3780	0.02								
54		3780-3790	0.03								
55		3790-3800	0.04								
56		3800-3810	0.03								
57		3810-3820	0.04								
58		3820-3830	0.07								
59		3830-3840	0.06								
60		3840-3849	0.12								
61		3858-3870	0.07								
62		3870-3880	0.07								
63		3880-3890	0.06								
64		3890-3905	0.08								
65		3914-3925	0.21								
66		3925-3935	0.08								
67		3935-3945	0.17								
68		3945-3955	0.15								
69		3955-3965	0.09								
70		3965-3979	0.22								
71	CHS-1	3988-3992	0.09								

TO:
cc: [illegible] + Clyde Davis (tag-list only) 3/12/75

REMARKS:

Page 2 of 2

CERTIFIED BY: William L. Lehmbeck

REGISTERED ASSAYER CERTIFICATE NO. 9125 WILLIAM L. LEHMBECK DATE SIGNED 9/23/74 Arizona U.S.A.

DATE REC'D:	DATE COMPL.:	JOB NUMBER:
9/13/74	9/23/74	741873

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION		Ag ppm	Cu ppm	Pb ppm	Zn ppm	Mo ppm
1	CHS-2	50-60	<0.2	5	10	65	< 2
2		150-160	<0.2	35	15	95	< 2
3		250-260	<0.2	10	15	60	2
4		350-360	<0.2	5	10	75	< 2
5		450-460	<0.2	45	35	120	< 2
6		550-560	<0.2	10	50	65	< 2
7		650-660	<0.2	5	20	65	< 2
8		750-760	<0.2	5	20	65	< 2
9		850-860	<0.2	15	30	65	< 2
10	CHS-2	950-960	<0.2	5	35	35	< 2

TO:
American Smelting & Refining Company
P.O. Box 5747
Tucson, Arizona 85703

Attn.: Mr. S. R. Davis

REMARKS:

CERTIFIED BY:

DATE REC'D:	DATE COMPL.:	JOB NUMBER:
9/27/74	10/2/74	741959

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
P.O. Box 50106, 1700 W. Grant Rd., Tucson, Arizona 85703

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION		Ag ppm	Cu ppm	Pb ppm	Zn ppm	Mo ppm
1	CHS-2	1050-1060	<0.2	10	65	75	2
2		1150-1160	<0.2	10	30	5	2
3		1250-1260	<0.2	55	15	130	< 2
4		1350-1360	<0.2	40	20	85	< 2
5		1450-1460	<0.2	5	15	35	2
6		1550-1560	<0.2	25	30	70	< 2
7		1650-1660	<0.2	5	10	35	< 2
8		1750-1760	<0.2	10	10	50	< 2
9		1850-1860	<0.2	15	50	130	2
10		1950-1960	<0.2	10	20	65	2
11		2050-2060	<0.2	5	15	70	2
12		2150-2160	<0.2	15	100	70	2
13		2190-2200	<0.2	5	20	5	2
14		2200-2210	<0.2	115	10	5	2
15		2210-2220	<0.2	35	15	50	2
16	CHS-2	2250-2260	<0.2	10	25	40	2

TO:
American Smelting & Refining Company
Southwestern Exploration Division
P.O. Box 5747
Tucson, Arizona 85703

REMARKS:

CERTIFIED BY:

Attn.: Mr. S. R. Davis

DATE REC'D: 9/30/74

DATE COMPL.: 10/7/74

741973

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION	Ag ppm	Cu ppm	Pb ppm	Zn ppm	Mo ppm				
1	Chs-2 2911-2913	20.	485	5400	7600	< 2				

D:

American Smelting & Refining Company
Southwestern Exploration Division
P.O. Box 5747
Tucson, Arizona 85703

REMARKS:

Trace analysis

CERTIFIED BY: William L. Lehmbeck

DATE REC'D: 12/20/74

DATE COMPL.: 12/30/74

JOB NUMBER: 74559

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION	Ag ppm	Cu ppm	Pb ppm	Zn ppm	Mo ppm
1	Chs-2 2988-2998	0.2	25	15	35	2
2	Chs-2 3243-3253	0.6	210	1800	2100	2

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

SAMPLE IDENTIFICATION	GOLD ppm	SILVER	COPPER	LEAD	ZINC ppm	MO ppm
Chs-2 3243-3253	<0.02					

TO:
American Smelting & Refining Company
P.O. Box 5747
Tucson, Arizona 85703

Attn.: Mr. John R. King

REMARKS:
2 Gold @ $2.50
1 Zinc - 1.25
1 Molybdenum - $1.50

CERTIFIED BY: WILLIAM L. LEHMBECK
REGISTERED ASSAYER CERTIFICATE NO. 9425 STATE OF ARIZONA
DATE SIGNED 11/4/74

CHARGES:
PREPARATION $
ANALYSIS $ 7.75

DATE REC'D:	DATE COMPL.:	JOB NUMBER:	$ 7.75
	11/11/74	742154-A	

TO:
American Smelting & Refining Company
P.O. Box 5747
Tucson, Arizona 85703

Attn.: Mr. John King

REMARKS:

CERTIFIED BY: WILLIAM L. LEHMBECK
REGISTERED ASSAYER CERTIFICATE NO. 9425 STATE OF ARIZONA
DATE SIGNED 11/4/74

DATE REC'D:	DATE COMPL.:	JOB NUMBER:
10/30/74	11/4/74	742154

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION	Au ppm	Ag ppm	Cu ppm	Pb ppm	Zn ppm	Mo ppm			
1	Chs-2 3378-3388	<0.02	<0.2	55	55	250	< 2			

American Smelting & Refining Company
Southwestern Exploration Division
P.O. Box 5747
Tucson, Arizona 85703

Attn : Mr. John R. King

REMARKS:

CERTIFIED BY: William L. Lehmbeck

DATE REC'D: 11/6/74
DATE COMPL.: 11/14/74
JOB NUMBER: 742199

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION	Au ppm	Ag ppm	Cu %	Pb ppm	Zn ppm	Mo ppm			
	Chs-2 W 4205-4215	<0.02	27	1.04	295	220	< 2			

TO: American Smelting & Refining Co.
Southwestern Exploration Div.
P. O. Box 5747
Tucson, Arizona 85703

Attn: Mr. John King

REMARKS:

CERTIFIED BY:

DATE REC'D:	DATE COMPL.:	JOB NUMBER:
3/14/75	3/26/75	750573

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION	Au ppm	Ag ppm	Cu %	Pb ppm	Zn ppm				
1	Chs 4195-4205	<0.02	6.6	0.53	210	530				

American Smelting & Refining Company
Southwestern Exploration Division
P.O. Box 5747
Tucson, Arizona 85703

Attn.: Mr. John R. King

REMARKS:

CERTIFIED BY:

DATE REC'D:	DATE COMPL.:	JOB NUMBER:
5/9/75	5/13/75	750946

SKYLINE LABS, INC.
Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION	Au ppm	Ag ppm	Cu ppm	Pb ppm	Zn ppm	Mo ppm
1	CP-1 240-250		<0.2	15	50	185	2
2	CP-1 330-350		0.2	15	65	180	2
3	CP-1 370-395		<0.2	15	25	90	2
4	Chs-2 4351-4356	<0.02	<0.2	10	45	40	8
5	4470-4479	<0.02	<0.2	100	5	30	2
6	4742-4747	<0.02	<0.2	15	65	70	2
7	4971-4980	<0.02	<0.2	25	15	50	24
8	Chs-2 5012-5021	<0.02	<0.2	35	50	320	2

REGISTERED ASSAYER CERTIFICATE NO. 9425 WILLIAM L. LEHMBECK

TO:
American Smelting & Refining Company

REMARKS:
Trace Analysis

CERTIFIED BY:

Hawley & Hawley, Assayers and Chemists Division
1700 W. Grant Rd., P.O. Box 50106, Tucson, Arizona 85703
(602) 622-4836

Charles E. Thompson
Arizona Registered Assayer No. 9427

William L. Lehmbeck
Arizona Registered Assayer No. 9425

CERTIFICATE OF ANALYSIS

ITEM NO.	SAMPLE IDENTIFICATION	Au ppm	Ag ppm	Cu ppm	Pb ppm	Zn ppm	Mo ppm
1	Chs-3 201-211	<0.02	<0.2	220	140	165	2
2	602-610	<0.02	<0.2	110	65	65	8
3	948-958	<0.02	<0.2	60	70	80	8
4	1213-1223	<0.02	<0.2	50	30	45	2
5	1486-1496	<0.02	3.2	870	820	1850	14
6	1577-1587	<0.02	0.2	185	35	110	6
7	2167-2176	<0.02	<0.2	295	40	50	16
8	2789-2799	<0.02	<0.2	940	70	55	12

TO: erican Smelting & Refining Company
thwestern Exploration Division
. O. Box 5747
Tucson, Arizona 85703
Attn: Mr. John R. King

REMARKS: Trace analysis

CERTIFIED BY: William L. Lehmbeck

REGISTERED ASSAYER CERTIFICATE NO. 9425 WILLIAM L. LEHMBECK STATE OF ARIZONA U. S. A.

DATE REC'D:	DATE COMPL.:	JOB NUMBER:
8/13/75	8/22/75	751769



SAMPLE SITES
GEOCHEMICAL OVERLAY
CHARLESTON MINING DISTRICT
COCHISE CO., ARIZONA

scale 1:24,000 · SEPT, 1973

3226 East 46th Street

Phone ~~621-0019~~ 889-5781

AMERICAN ANALYTICAL and RESEARCH LABORATORIES

ASSAYERS - CHEMISTS - METALLURGISTS

TUCSON, ARIZONA 85713

JUL 2 1973

SAMPLE SUBMITTED BY American Smelting & Refining Co. DATE June 30, 1973

SAMPLE MARKED	GOLD OZ / TON	SILVER OZ./TON	PPM COPPER	PPM LEAD	PPM ZINC	PPM MOLYBDENUM	PERCENT IRON	
TB - 1			20	131	22	25		
TB - 2			48	81	24	25		
TB - 3			161	2000+	71	33		
TB - 4			14	183	8	40		
TB - 5			68	724	666	53		
TB - 6			23	96	17	20		
TB - 7			46	44	34	17		
TB - 8			41	40	18	16		
TB - 9			14	66	8	32		
TB -10			92	44	11	20		
TB -11			35	33	79	17		
TB -12			26	39	9	13		
TB -13			19	65	61	17		
TB -14			11	21	59	22		
TB -15			21	22	57	25		
TB -16			36	18	91	20		

REGISTERED ASSAYER
CERTIFICATE NO. 0354
STATE OF ARIZONA
6/30/73
Signed
Arizona U. S. A.

Invoice # 9411

80.00

3226 East 46th Street

Phone 624-00[illegible]

AMERICAN ANALYTICAL and RESEARCH LABORATORIES

ASSAYERS - CHEMISTS - METALLURGISTS

TUCSON, ARIZONA 85713

SAMPLE SUBMITTED BY American Smelting & Refining Company

DATE August 29, 1973

SAMPLE MARKED	GOLD OZ./TON	SILVER OZ./TON	PPM COPPER	PPM LEAD	PPM ZINC	PPM MOLYBDENUM	PERCENT IRON	
TB - 17			39	200	24	19		
TB - 18			108	107	49	14		
TB - 19			26	42	25	13		
TB - 20			40	90	30	14		
TB - 21			25	49	57	10		
TB - 22			23	189	21	11		
TB - 23			25	105	17	19		
TB - 24			33	133	50	23		
TB - 25			54	879	29	12		
TB - 26			30	31	63	13		
[illegible] - 27			37	129	61	12		
TB - 28			26	36	69	11		
TB - 29			68	38	107	12		
TB - 30			28	40	80	16		
[illegible]			[illegible]	[illegible]	[illegible]	[illegible]		

8/29/73

Invoice # 9716

CHARGES $ 75.00

THIN SECTION REPORT OF SPECIMENS

FROM CHARLESTON MINE

September 24, 1969

-1/-

No. C-69-3977

Location: U.S.A.; Charleston Mine; Hole #4 @ 1,481'; H. L. Jones, Albuquerque, N. Mexico; Assay No. E-7853.

Classification: Highly altered rhyodacitic volcanic. Strongly carbonatized and saussuritized. Contains about 5% euhedral pyrite, minor v.f.g. disseminated sphalerite, and a trace of chalcopyrite. No molybdenite is present.

No. C-69-3978

Location: Ditto -3977; @ 1,500'; Assay No. E-7854.

Classification: Sample consists of small fragments up to 1/2" in size. Mineralogy as follows:

pale golden yellow sphalerite	60%
galena	10%
pyrite	5%
chalcopyrite	15%
gangue	10%

The sulphides are c.g. except for pyrite which is almost invariably surrounded and corroded by chalcopyrite. No molybdenite.
P.S. enriched in sulphide relative to sample.

No. C-69-3979

Location: Ditto -3977; @ 1,546'; Assay No. E-7855.

Classification: Porphyritic rhyodacite. Consists of rounded and corroded phenocrysts of quartz, phenocrysts of plagioclase and a rhyodacitic matrix. Sulphide mineralization is restricted to minor, f.g., disseminated pyrite.

EFP/lk

.....

THIN SECTION REPORT

ON CHARLESTON PROPERTY

November 5, 1969

Preliminary thin section work was done on fifty-four diamond drill core specimens from borehole #4, Charleston Property. The specimen classification with brief explanatory notes is presented below:

Sample	Footage	Classification	Remarks
S69-920	1435'	Quartzite	Consists to over 90% of quartz grains with overgrowth in fg cementing quartz-chlorite matrix. Minor carbonate, feldspar. Well sorted.
S69-921	1460'	Quartzite	Ditto S69-920
S69-922	1477'	Quartzite	Ditto S69-920
S69-923	1488'	Quartzite	Ditto S69-920
S69-924	1506'	Quartz-andesite porphyry	Fg plagioclase-chlorite-(hornblende) matrix with phenocryst of quartz, partly saussuritized plagioclase and hornblende. Minor carbonate replacement. Green colour of phenocrysts in hand specimen is due to epidote replacing plagioclase.
S69-925	1520'	Quartz-andesite porphyry	Ditto S69-924
S69-926	1535'	Quartz-andesite porphyry	Ditto S69-924
S69-927	1570'	Quartz-andesite porphyry	Ditto S69-924

Sample	Footage	Classification	Remarks
S69-928	1604'	Lapilli tuff	Aphanitic quartz-chlorite rich matrix, holds strongly altered fragments of silicates, now largely consisting of epidote and carbonate. Some admixed clastic material.
S69-929	1630'	Tuffaceous sandstone, possibly brecciated	Very fragmental; partly a poorly sorted quartzite, but mostly a fg chlorite carbonate rock with particles of angular quartzite. Strong carbonate metasomatism.
S69-930	1640'	Tuffaceous sandstone to greywacke	A fg quartz-chlorite matrix holds abundant angular grains of quartz and some volcanic rock fragments.
S69-931	1650'	Quartzite, poorly sorted	Abundant angular quartz cemented by fg quartz matrix, partly replaced by carbonate with epidote. Some sericite.
S69-932	1670'	Arkosic quartzite	Poorly sorted, more plagioclase grains than in S69-931.
S69-933	1700'	Quartzite, poorly sorted	Mostly quartz cemented by quartz-sericite-chlorite. Some zeolites.
S69-934	1704'	Quartzite, poorly sorted	As S69-933
S69-935	1747'	Quartzite	As S69-920; quartz shows overgrowth.
S69=936	1768'	Quartz-andesite porphyry	Ditto S69-924
S69-937	1788'	Andesite porphyry	Ditto S69-924, no quartz phenocrysts
S69-938	1800'	Recrystallized greywacke?	Fragmental. A matrix of lathy quartz contains fragments of tuff, chloritic volcanics. Abundant disseminated pyrite cubes. True nature of this rock remains doubtful.

Sample	Footage	Classification	Remarks
S69-939	1812'	Arkosic quartzite	Ditto S69-932
S69-940	1817'	Recrystallized quartzite	Consists essentially of lathy quartz, some carbon metasomatism.
S69-941	1830'	Quartzite	Ditto S69-920
S69-942	1840'	Altered intermed. volcanic	Basically an altered andesite without phenocrysts
S69-943	1860'	Arkosic quartzite	Poorly sorted, as S69-932
S69-944	1880'	Arkosic quartzite	Poorly sorted.
S69-945	1890'	Quartzite	Ditto S69-920
S69-946	1898'	Quartzite	A somewhat pebbly appearance, otherwise as entry above.
S69-947	1900'	Quartzite	Ditto S69-920
S69-948	1902'	Tuffaceous sandstone?	Very fg matrix with clastic quartz grains, disseminated pyrite. Border case between a type of mudstone and tuffaceous sandstone.
S69-949	1930'	Quartzite	Ditto S69-920, but more interstitial fg matrix with much epidote and carbonate. Minor feldspar.
S69-950	1950'	Quartzite	Poorly sorted, ditto S69-931
S69-951	1975'	Quartzite	Poorly sorted, ditto S69-931
S69-952	1994'	Altered tuff	Much replacement by carbonate in coarse particles, and by epidote-amphibole in an interlocking intergrowth.
S69-953	2002'	Greywacke	Contains abundant clastic quartz and lithic fragments in a very fg interstial quartz-chlorite-carbonate matrix.

Sample	Footage	Classification	Remarks
S69-954	2007'	Arkosic quartzite	Ditto S69-932, with abundant clastic feldspar.
S69-955	2045'	Dacite porphyry	Basically a quartz-feldspar porphyry, strong carbonate-epidote alteration. In general more sodic and silica rich than the quartz-andesite porphyries
S69-956	2070'	Arkosic quartzite	Ditto S69-954
S69-957	2090'	Arkosic quartzite	Ditto S69-954, transitional to a greywacke.
S69-958	2115'	Tuffaceous sandstone	Mixture of clastic quartz and lithic fragments in very fg matrix; similar to S69-930.
S69-959	2125'	Tuffaceous sandstone	As above entry, less coarse particles, much matrix of ashy nature.
S69-960	2140'	Quartzite	Poorly sorted, ditto S69-931
S69-961	2150'	Quartzite	As above entry
S69-962	2180'	Quartzite	Ditto S69-920; well sorted with overgrowth of quartz.
S69-963	2210'	Greywacke	Similar to S69-953. Mixture of clastic particles in an interstial fg quartz-chlorite-sericite-carbonate matrix.
S69-964	2240'	Arkosic quartzite	Transitional to a greywacke and a quartzite. Similar to S69-956
S69-965	2256'	Andesite porphyry	Ditto S69-937
S69-966	2276'	Andesite porphyry	Ditto S69-937
S69-967	2290'	Andesite porphyry	Ditto S69-937
S69-968	2300'	Quartzite	Poorly sorted, angular quartz, as S69-931

Sample	Footage	Classification	Remarks
S69-969	2330'	Tuff	A tuff with minor quartz sand; some lapilli; minor epidote.
S69-970	2340'	Tuffaceous sandstone	Mixture of quartz and lithic fragments in an ashy matrix; similar to S69-958
S69-971	2364'	Tuff to tuffaceous sandstone	Similar to above entry, finer grained.
S69-972	2374'	Tuff	Similar to S69-969
S69-973	2386'	Tuff	Similar to S69-969

POLISHED SECTION REPORT

ON CHARLESTON MINE

October 28, 1969

Three chips of diamond drill core from borehole #4, Charleston Property, Arizona, were received for polished section examination. The footages of the three specimens are given as: 1729' (S69-915); 1890' (S69-916) and 2424' (S69-917).

Specimen S69-915 @ 1729': A fine grained quartz-feldspar rich rock (latite?) carries about 5% disseminated sulfides. These are major pyrite, minor sphalerite, some galena and a very few specks of chalcopyrite. Pyrite occurs as euhedral cubes measuring up to 400 microns in diameter. Sphalerite forms very ragged, amoeba-like particles (figure 1) ranging in size up to one millimeter across. Smaller and more euhedral sphalerite grains are scattered throughout the rock matrix in minor amounts. Galena is present in trace amounts, usually in close association with sphalerite. Figure 1 shows a typical occurrence of galena as inclusions in sphalerite and as an intermittent rim around the sphalerite particle. In other places galena occurs as small isolated grains in the rock matrix. Small specks of chalcopyrite are found as inclusions in sphalerite.

Pyrite does not contain any visible inclusions of sphalerite, galena or chalcopyrite, but carries numerous inclusions of gangue constituents. A rough estimate of the relative sulfide proportion in the rock is about 85% pyrite, 10% sphalerite, $\leq$5% galena and $<<$1% chalcopyrite.

Specimen S69-916 @ 1890': A fine grained quartz rich rock with about 12 to 15% sulfides. Again the bulk of the sulfides is pyrite, here forming coarse grained lensoid to stringery aggregates. A small proportion of pyrite occurs as small disseminated euhedral grains in the rock matrix. Sphalerite and galena are present in minor amounts and form

angular disseminated grains, again showing a close affinity for each other (figure 2). Chalcopyrite occurs as small inclusions in sphalerite and also as minute grains disseminated throughout the matrix.

Sphalerite in this specimen lacks the ragged, amoeba shaped grain boundaries. It may contain inclusions of galena and chalcopyrite. Pyrite is full of inclusions of gangue constituents but free of other sulfide components. The relative sulfide proportions are estimated at 90% pyrite, 5% sphalerite and galena each and a trace of chalcopyrite. Silver minerals and lead sulfosalts were not observed.

Specimen S69-917 @ 2424': A fine grained volcanic (?) containing about 7% disseminated sulfides. These are mainly coarse grains of pyrite, small particles of sphalerite and a few specks of chalcopyrite. Galena was not observed.

Pyrite tends to form stringery aggregates measuring up to five millimeter in length. The individual euhedral pyrite grains measure up to half a millimeter across. Gangue inclusions in pyrite are less common than in the other two specimens, but a few minute specks of chalcopyrite were seen in some of the pyrites. Sphalerite is present as disseminated grains measuring up to 100 microns across. The relative sulfide proportions are roughly 95% pyrite, >3% sphalerite and <2% chalcopyrite.

The specimens were submitted for chemical analysis; the assay data will be reported when they become available.